

Executive Order: A-010-2331

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	TEST GROUP INFORMATION													
MOD YEA		TEST GROUP VEHICLE CLASS(ES)					S)		FUEL CATEGORY			FUEL TYPE		
202	2022 NFMXD07.373K					MDV5		I		SINGLE FUEL HICLE	GASOLINE			
	USEFL	JL LI	IFE (miles)		VEH	IICLE EMISS	ION C	ATEC	ORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD		
EX	H/ORVF	R	EVAP			FTP		SF	ГР	FTP		SFTP		
1	150000 150000		150000 LEV3 ULEV270 LEV3 ULEV (HOT1435 UC (LA92), SC03, FTP TEST CYCLE		(;		JLEV270 (HOT1435 (LA92), S		ULEV270 (HOT1 (LA92)		r1435 UC * 2), SC03,			*
SP	ECIAL F	FEAT	TURES & EXI SYS	IAUS TEMS		ON CONTRO	١		OBD S	TATUS	EN	GINE DISPLACEMENT (L)		
1			2TWC,2WR-	HO2S	,2HO2S,	BFI			FULL	*				
*				*				P	ARTIAL	*	1	7.3		
*	* *								TIAL WITH FINES	ALL MODELS				
			EV	APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	/ INFORMATION				
EV	AP / OR	RVR F	FAMILY	EVA	PORATIVE	STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS S			ECIAL FEATURES		
	NFMXR0	0250	NHJ	LE	V 3 OPT	7 3 OPTION2 WITH FEL			MDV5			*		
	NFMXR0	0360	NHJ	LE	V 3 OPT	ON2 WITH 1	FEL		MI	V5		*		
					ı	EMISSION C	REDIT	INFO	RMATION					
	REDIT F	FOR	FLEET AVE. EXTENDED ANTY			REDIT FOR N	ON-P	ZEV	NMOG C	REDIT FOR DO	OPTIONAL EXH. STD FOR WORK TRUCKS			
		N				N				N		N		
				•	NMOG	AND FLEET	AVE	RAGE	INFORMA	TION	•			
NMO0 RAF	CH4 RAF		FTP IMOG/NMHC RATIO		HO/NMHC RATIO	LDT (3751 LVW-850			IC NMOG+NOX FLEET STD NMOG+N LDT (3751 LVW-8500 GVW) MDV (850 + MDPV (g/mi)		00 GVW) MDV (8501-10000 GV			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)
*	*		1.10		*		*			0.178		0.247		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-010-2331

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty-five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2022 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$40,725 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 29th day of April 2021.

Allen **⊭**yons, Chief

Emissions Certification and Compliance Division

Executive Order: A-010-2331

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG+NOx (g/mi)						NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
FTP@50K	*	*	*	*	*	*	*	*	*	*	*		
FTP@UL	GASOLINE- TIER3 E10	0.176	0.270	3.3	4.2	*	*	*	6	0.001	0.010		
50°F @4K	GASOLINE- TIER3 E10	0.132	0.540	1.5	4.2	*	*	3	20				

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)
	FUEL TIPE	CERT	STD	CERT	STD
HWFET @ 50K	*	*	*		
HWFET @ UL	GASOLINE-TIER3 E10	0.103	0.270		
20°F @ 50K	*			*	*

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC0	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx	СО	PM	NMOG+NOx	СО	NMOG+NOx	co	PM
			(g/mi)	(g/mi)	(mg/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	*	*	*	0.160	2.3	3
@ UL	GASOLINE- TIER3 E10	STD	*	*	*	*	*	0.550	6.0	7
		BIN						*		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY			WHOLE \						
	FUEL TYPE	3DH	S (g/test) (@ UL	2DI	HS (g/test) (RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
NFMXR0250NHJ	GASOLINE- TIER3 E10	0.352	0.600	0.600	0.231	0.600	0.600	0.000	0.05
NFMXR0360NHJ	GASOLINE- TIER3 E10	0.377	0.600	0.600	0.356	0.600	0.600	0.000	0.05



Executive Order: A-010-2331

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

<u> </u>													
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
		FUEL ONLY EVAP & CANISTER BLEED											
EVAPORATIVE FAMILY	ORVR (g	gallon) @) UL	FUEL TYPE			IG TEST) @ UL		RIG TEST st) @ UL		ANISTER est) @ 4K		
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
NFMXR0250NHJ	GASOLINE- TIER3 E10	0.040	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.007	0.030		
NFMXR0360NHJ	GASOLINE- TIER3 E10	0.012	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.010	0.030		
	FFECTIVE	LEAK D	IAMET	ER STA	NDAR	D AND CE	RTIFICA	ΓΙΟΝ LE	VEL (INCH	IES)			
EVAPORATIVE	FAMILY	LEA	K FAMII	LY		CE	RT			STD			
NFMXR0360	NHJ	NFMXR0	360NНЈ	-001 *					0.02				
NFMXR0250	NHJ	NFMXR0	250NHJ	-001	·	,	+			0.02			

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor: NH3S: ammonia sensor: EGR: exhaust gas recirculation: HP/LP EGR: High/Low Pressure EGR: EGRC: EGR cooler: AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR: SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol`("15%"gasoline) fuel; E10: "10%" éthanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits. S = credits for some/select models

2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE Family	EXH ECS	OBD
FORD	F350 PICKUP 2WD	MDV5	7.3	SA10	NFMXR0250NHJ	1	\$
FORD	F350 PICKUP 2WD	MDV5	7.3	SA10	NFMXR0360NHJ	1	\$
FORD	F350 PICKUP 4WD	MDV5	7.3	SA10	NFMXR0250NHJ	1	\$
FORD	F350 PICKUP 4WD	MDV5	7.3	SA10	NFMXR0360NHJ	1	\$