

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE YEAI	T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2022	2 NE	MXT02.52B1			LDT2				ELECTRIC HICLE		GASOLINE		
	USEFUI	LIFE (miles)		VEF	ICLE EMISS	ION (	CATE	GORY	INTERIM / IN	FERM	IEDIATE IN-USE STD		
EXH	I/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP		
15	50000	150000	)	LEV3	ULEV50	LEV	3 CC	MPOSITE	*	PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	TWC(2), WR-HO2S, HO2S, SFI, EGR, EGRC							FULL	*				
*	*							ARTIAL ALL MODELS			2.5		
*			*					TIAL WITH FINES	*				
		E	VAPO	RATIVE &	REFUELING	(EVA	AP/OR	VR) FAMIL	(INFORMATION				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							(	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	NFMXR01	35LDF	LE	V 3 OPTI	ION2 WITH 1	FEL		LDT2			HCT		
				I	EMISSION CI	REDI	T INFC	ORMATION					
	REDIT FO	DX FLEET AVE. DR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		IO/NMHC RATIO	NMOG+NO PC+LDT ( (g			V) LDT			D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.051			0.056		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this  $\frac{16t}{16t}$  day of November 2021.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				G+NOx mi)	-	O mi)		Ox mi)	HC (mg			PM (g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	r std
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		SOLINE- R3 E10	0.026	0.050	0.4	1.7	*	*	0	4	0.00	0 0.003
50°F @4K		*	*	*	*	*	*	*	*	*		
		FUEL TYPE						NMOG+NOx (g/mi) CO (g/mi)				mi)
					E		CE	RT	STD	CER	RT	STD
HWFET @ 50K			*					•	*			
HWFET @	2) UL		GASOI	LINE-TIE	R3 E10		0.0	)14	0.050			
20°F @ 50K		COLD (	CO E10 RE	EGULAR GA	ASOLINE	(TIER3)				0.4	4	12.5

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFT	P EXHAI	JST EN	ISSION	STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS				
						US06				SC03		C	OMPOSI	E		
	FUEL TYPE			NMOG+NOx		со		М	NMOG+NOx		СО	NMOG+NC	x CO	PM		
				(g/mi)		(g/mi)	(mg	/mi)	(	g/mi)	(g/mi)	(g/mi)	(g/m	i) (mg/mi)		
@ 4K	*	C	ERT	*		*				*	*					
		S	STD	*		*				*	*					
		C	ERT	*		*	C	)		*	*	0.020	0.4	*		
@ UL	GASOLIN TIER3 E	9	STD	*		*	e	;		*	*	0.070	4.2	*		
		E	BIN									0.040				
		WHOL	LE VEH	ICLE EV	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS			
					W	HOLE V	/EHICLE	EVAPO	ORA	TIVE TEST	ING	1G				
		FUE	EL TYPI	Ξ 3	BDHS (g	/test) @	DUL		2Dł	IS (g/test)	@ UL	F	RL (g/mi)	@ UL		
				CEF	श्म	STD	FEL	CER	RL	STD	FEL	CE	RT	STD		
NFMXF	R0135LDF		SOLINE ER3 E1	102	91 0	. 400	0.400	*		0.400	0.40	0.	00	0.05		
0	ORVR / FUE	EL ON	ILY / CA	NISTER	BLEED	) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VELS		
								FU	IEL C	ONLY EVA	P & CANIS	STER BLEE	D			
EVAPORATIVE FAMILY NFMXR0135LDF ORVR / FU EVAPORATIVE FAMILY	OR	RVR (g/	gallon) (	on) @ UL Fl		L TYPE		HS RIG TEST g/test) @ UL		-	RIG TEST t) @ UL		CANISTER /test) @ 4K			
		FUEL	_ TYPE	CERT	STD			CEI	RT	STD	CERT	STD	CERT	STD		
NFMXF	R0135LDF		CASOLINE-		0.20	*		*		*	*	*	*	*		



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
NFMXR0135LDF	NFMXR0135LDF-001	*	0.02						

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG; compressed/liguefied natural gas; LPG; liguefied petroleum gas; E85; "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	MAVERICK HEV FWD	LDT2	2.5	CV1	NFMXR0135LDF	1	Р