

# NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0894

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFOR	MATION					
MODE YEAR	- I TI	EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2022	NN	SXT03.5PTA		LD	T2, LDT3			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
ı	USEFUL	LIFE (miles)		VEH	IICLE EMISS	ION C	ATE	GORY	INTERIM / IN	ITER	MEDIATE IN-USE STD		
EXH	/ORVR	EVAP			FTP		SF	ТР	FTP	SFTP			
15	0000	150000	)	LEV3	ULEV70	LEV	3 CC	MPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			NGINE DISPLACEMENT (L)		
1	1 2TWC, 2WR-HO2S, 2HO2S, TWC, DFI							FULL	*				
*	* *							ARTIAL	ALL MODELS		3.5		
*	* *							TIAL WITH FINES	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATUR									SPECIAL FEATURES				
N	NSXR02	01PEA	LI	EV 3 OPTI	ON2 WITH	FEL		LDT2			*		
N	NSXR02	01PFB	LI	EV 3 OPTI	ON2 WITH	FEL		LDT3			*		
				ı	EMISSION CI	REDIT	INFO	RMATION					
	EDIT FC	X FLEET AVE. OR EXTENDED RRANTY			REDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		HO/NMHC RATIO	PC+LDT (			LVW) LDT (3751 LV		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.051			0.056		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0894

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this //th day of March 2021.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 



# **ATTACHMENT**

# **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

## EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

### **FUEL TYPE**

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- LEV3 E10	0.032	0.070	0.3	1.7	*	*	*	4	0.002	0.003
50°F @4K	GASOLINE- LEV3 E10	0.047	0.140	0.5	1.7	*	*	*	16		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (	g/mi)
	FUELTIFE	CERT	STD	CO CERT	STD
HWFET @ 50K	*	*	*		
HWFET @ UL	GASOLINE-LEV3 E10	0.009	0.070		
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			1.1	12.5

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	2	*	*	0.027	2.1	*
@ UL	GASOLINE- LEV3 E10	STD	*	*	6	*	*	0.070	4.2	*
		BIN						0.090	(g/mi) (g/mi) .027 2.1 .070 4.2	

### WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY			WHOLE \						
	FUEL TYPE	3DH	S (g/test) @	@ UL	2DI	HS (g/test) (	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
NNSXR0201PEA	GASOLINE- LEV3 E10	0.177	0.400	0.400	0.165	0.400	0.400	0.000	0.05
NNSXR0201PFB	GASOLINE- LEV3 E10	0.177	0.500	0.500	0.165	0.500	0.500	0.000	0.05

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0894

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR	(g/gallon) @	) UL	FUEL TYPE			IG TEST ) @ UL		IG TEST	UL TEST (g/test) @ 4K STD CERT STD  * 0.014 0.020			
	FUEL TYP	PE CERT	STD			CERT	STD	CERT	STD	CERT	STD		
NNSXR0201PFB	GASOLINE TIER3 E1	1 0 07	0.20	GASOLINE- LEV3 E10		*	*	*	*	0.014	0.020		
NNSXR0201PEA	GASOLINE TIER3 E1	1 0 07	0.20	GASOLINE- LEV3 E10		*	*	*	*	0.014	0.020		
	EFFECTIV	E LEAK D	IAMET	ER STA	NDAR	D AND CE	RTIFICA	TION LEV	'EL (INCH	IES)			
EVAPORATIVE FAMILY LEAK FAMIL			LY	Y CERT				STD					
NNSXR0201	.PFB	NNSXR0	201PFB	-001	-001 *				0.02				
NNSXR0201PEA NNSXR0201PEA-			-001 *					0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection: DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	PATHFINDER 2WD	LDT2	3.5	SA9	NNSXR0201PEA	1	P
NISSAN	PATHFINDER 4WD	LDT2	3.5	SA9	NNSXR0201PEA	1	P
NISSAN	PATHFINDER 4WD PLATINUM	LDT3	3.5	SA9	NNSXR0201PFB	1	P