

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODI YEA		TES	T GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
202	2 N	NHNX	T03.5J4C		LDT3				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFU	JL LI	FE (miles)		VEF	IICLE EMISS	ION (ATE	GORY	INTERIM / IN	TER	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP				SFTP FTP			SFTP		
1	50000		150000		LEV3	ULEV70	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMIS SYSTEMS						ON CONTRO	L		OBD STATUS		E	NGINE DISPLACEMENT (L)		
1	2WU-TWC, TWC, 2WR-HO2S, 2HO2S, EGR, DFI								FULL	*	1			
*	*							F	PARTIAL	ALL MODELS		3.5		
*	*								RTIAL WITH *					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							Y EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	NHNXR0	0150	2SA		LEV 3	OPTION2			LDT3			*		
					I	EMISSION CI	REDIT	INFC	ORMATION					
	REDIT F	-OR	FLEET AVE. EXTENDED ANTY			EDIT FOR N ZERO-EVAP	ON-P				R	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N		N		
					NMOG	AND FLEET	AVE	RAGI	E INFORMA	TION				
NMOG RAF	CH4 RAF						NMOG+NOX FLEET ST PC+LDT (0-3750 LVW) (g/mi)			+NOX FLEET S (3751 LVW-850(R) + MDPV (g/m	ן נ			
*	*		1.10		0.05	0	.051		0.056 *					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2021.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>17th</u> day of December 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/i	6+NOx mi)	CO (g/mi)			NOx (g/mi)		HCI (mg/			PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD		CERT	STD CE		RT	STD
FTP@50K	*		*	*	*	*	*	*		*	* *		,	*
FTP@UL	GASOLINE- LEV3 E10		0.031	0.070	0.1	1.7	*	*		1	4	0.0	000	0.003
50°F @4K		*	*	*	*	*	*	*		*	*			
								NMOG+NOx (g/mi)			CO (g/mi)			
				FUEL TYP	E		CE	RT		STD	CER	.т.		STD
HWFET @) 50K		*	*		*								
HWFET (@ UL		0.0)15	(0.070								
20°F @ 50K		COLD C	CO E10 RE	GULAR GA	ASOLINE					0.9)		12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SET	PEXH	AUSI	EM	SSION	STAND	ARDS .	AND	CERTIFIC	ATION LE	:VELS					
					US06						SC03			COMPOSITE				
	FUEL TYPE			NMOG+NOx (g/mi)		:	CO PI (g/mi) (mg/		N	NMOG+NOx (g/mi)		со	NMOG+NOx (g/mi)		co	PM		
									/mi)			(g/mi)			(g/mi)	(mg/mi)		
@ 4K	@4K *		ERT	*			*			*		*						
-		S	STD	*			*				*	*						
	@ UL GASOLINE- LEV3 E10		CERT		*		* 0		-	*		*	0.031		0.8	*		
@ UL			ISINI		*		*	6		*		*	0.070		070 4.2			
			BIN										0.	080				
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																	
						WH	IOLE V	/EHICLE	EVAP	ORA	FIVE TEST	ING						
	EVAPORATIVE FAMILY		FUEL TYPE		3DHS (g/		/test) @		2Dł	IS (g/test)	@ UL		RL (g/mi) @ UL					
				CERT		S	TD	FEL	FEL CEI		STD	FEL		CERT		STD		
NHNXF	R01502SA		SOLINE V3 E10	10 1061		0.	500	*	0.1	23	0.500	*		0.00		0.05		
0	DRVR / FUE	EL ON	ILY / CA	NISTI	R BL	EED	EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CERT	IFICAT	TION LEV	ELS		
FUEL ONLY EV							ONLY EVAP & CANISTER BLEED											
	EVAPORATIVE FAMILY		ORVR (g/gallon) @ UL			L				HS RIG TEST g/test) @ UL		2DHS RIG (g/test) @				CANISTER (g/test) @ 4K		
		FUEL	L TYPE	CER	т ѕ	TD			CE	RT	STD	CERT	ST	D	CERT	STD		
NHNXF	R01502SA		DLINE- R3 E10	0.0	L 0	.20		OLINE- 3 E10	*	•	*	*	,	•	0.012	0.020		



HONDA MOTOR CO., LTD.

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
NHNXR01502SA	NHNXR01502SA-A00	*	0.02							

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission: SA: semi automatic transmission: CV: continuously variable transmission: SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HONDA	ODYSSEY	LDT3	3.5	SA10	NHNXR01502SA	1	P