

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	OUP IN	IFOR	MATION						
MOD YEA		TEST GRO	OUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE				
202	2 N	MAXJ03.8	8DFI		L	DT3, PC			-	SINGLE FUEL HICLE	GASOLINE				
	USEFL	JL LIFE (m	niles)		VEH	IICLE EMISS	ION C	ATE	GORY	INTERIM / IN	ERMEDIATE IN-USE STD				
EX	H/ORVF	२	EVAP			FTP		SF	ТР	FTP		SFTP			
1	50000	1	L50000		LEV3	LEV160	LEV	3 CC	MPOSITE	*		PM			
SP	ECIAL I	FEATURE	S & EXH SYS			ON CONTRO	L		OBD S	TATUS	E	NGINE DISPLACEMENT (L)			
1	DFI, AIR, 2TC, 2CAC, 2WR-HO2S, 2TWC, 2HO2S, GPF						2S,		FULL ALL MODELS						
*				*				Р	ARTIAL	*	3.8				
*				*					TIAL WITH	*					
			EV	APOF	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	(INFORMATION	1				
EV	AP / OR	VR FAMIL	Y	EVA	PORATIVE	STD CATE	GORY	,		SSION STD E CLASS	S	PECIAL FEATURES			
	NMAXR(0150161			LEV 3 OPTION2				F	PC		*			
					E	EMISSION CI	REDIT	INFO	ORMATION						
	REDIT F	IOX FLEET FOR EXTE ARRANTY	NDED	I		EDIT FOR N ZERO-EVAP	ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS			
		N				N				N		N			
					NMOG	AND FLEET	AVE	RAGE	INFORMA	TION					
NMOO RAF	NMOG/NMHC PC+LDL (0-37				0-375		V) LDT	DG+NOX FLEET STD DT (3751 LVW-8500 WR) + MDPV (g/mi)							
*	*	1.	04		*	0	.051			0.056		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 7tk day of September 2021.

Allen Kyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM	0.100	0.160	1.1	4.2	*	*	1	4	0.001	0.003
50°F @4K	GASOLINE- LEV3 E10 PREM	0.069	0.320	0.6	4.2	*	*	1	30		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)
	FUELTYPE	CERT	STD	CERT	STD
HWFET @ 50K	*	*	*		
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.008	0.160		
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			1.9	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS													
				US06			SC03				COMPOSITE			
	FUEL TYP	Έ	NMO	G+NOx	со	P	M	NMC	G+NOx	со	NMC)G+NOx	со	PM
			(g/	/mi)	(g/mi)	(៣ថ្	g/mi)	(9	g/mi)	(g/mi)	(g/mi)	CO (g/mi) 1.3 4.2 S (g/mi) @	(mg/mi)
@ 4K	*	CERT		*					*					
-		STD		*	*				*	*				
				*			1		*	*	0.088		1.3	*
@ UL	GASOLINH TIER3 E1 PREM		ГD *		*		6		*	*	0.070		4.2	*
		BIN									0	.110		
		WHOLE V	EHICLE	EVAPO	RATIVE E	MISSION	N STAN	IDARI	DS AND O	CERTIFIC		I LEVELS	5	
					WHOLE V	/EHICLE	EVAP	ORAT	IVE TEST	ſING				
	ORATIVE			E 3DHS (g/test) @ UL				2DHS (g/test) @ UL				RL (g/mi) @ UL		UL
			(CERT	STD	FEL	CEF	RT	STD	FEI	<u> </u>	CERT		STD
NMAXF	80150161	GASOLI TIER3 PREI	E10 0	0.283	0.300	*	0.2	66	0.300	*		0.01		0.05



MASERATI S.P.A.

ORVR / FUI	EL ONLY / C	ANISTER	BLEED	EVAPOF	RATIVE	EMISSION	I STANDA	RDS AN	ID C	CERTIFIC A	ATION LEV	ELS
		FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g	gallon) @	ĵ) UL	Structure <t< td=""><td colspan="2">BLEED CANISTER TEST (g/test) @ 4K</td></t<>					BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD			CERT	STD	CER	Т	STD	CERT	STD
NMAXR0150161	GASOLINE- TIER3 E10 PREM	0.04	0.20	GASOLINE- TIER3 E10 PREM		*	*	*		*	0.008	0.020
	EFFECTIVE	LEAK D	IAMET	ER STA	NDAR	D AND CE	RTIFICA	TION L	EVI	EL (INCH	ES)	
EVAPORATIVE FAMILY LEAK FAM			K FAMII	LY		CERT			STD			
NMAXR0150	NMAXR0150161 NMAXR0150161-LF1 * 0.				0.02							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MASERATI	GHIBLI TROFEO	PC	3.8	A8	NMAXR0150161	1	F
MASERATI	LEVANTE MODENA V8	LDT3	3.8	A8	NMAXR0150161	1	F
MASERATI	LEVANTE TROFEO	LDT3	3.8	A8	NMAXR0150161	1	F
MASERATI	QUATTROPORTE TROFEO	PC	3.8	A 8	NMAXR0150161	1	F