

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MOD YEA		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
202	2 NF	MXT01.6NC5		1.071					SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles)					ICLE EMISS	CATE	GORY	INTERIM / IN	TERIM / INTERMEDIATE IN-USE STD				
EXH/ORVR EVAP					FTP		SF	FTP FTP			SFTP		
1	50000	150000	,	LEV3	ULEV70	LEV 3 COMPOSIT			*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CON SYSTEMS						L		OBD S	BD STATUS		ENGINE DISPLACEMENT (L)		
1	DFI,	WR-HO2S, HO2	s, wu	Ј-ТЖС, Т	WC, TC, CA	c		FULL	ALL MODELS				
*			*				F	PARTIAL *			1.6		
*						PAF	RTIAL WITH FINES						
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATU				
	NKMXR01	L25NCG		LEV 3	OPTION2			LD	LDT1 HCT				
				I	EMISSION CI	REDIT	r info	ORMATION	·				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF							V) LDT	+NOX FLEET S1 (3751 LVW-8500 R) + MDPV (g/mi		MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	* 0.051						0.056		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>*Pth*</u> day of February 2021.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCI (mg/		-		M ni)
			CERT	STD	CERT	STD	CERT	STD		CERT	STD	CEI	RT	STD
FTP@50K		*	*	*	*	*	*	*		*	*	*		*
FTP@UL	OUL GASOLINE- TIER3 E10		0.055	0.070	0.8	1.7	*	*		*	4	0.0	01	0.003
50°F @4K		OLINE- R3 E10	0.027	0.140	0.6	1.7	*	*		*	16			
	FUEL TYPE				N	NMOG+NOx (g/mi)				CO (g/mi)				
				CE	RT		STD	CER	т		STD			
HWFET @ 50K				*			*	*		*				
HWFET @	D UL	GASOLINE-TIER3 E10						)38		0.070				
20°F @ 50K		COLD (	CO E10 RE	EGULAR GA	ASOLINE	(TIER3)					0.9	i i		10.0

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			3611		JOI EN	1133101	STANDA	ARDS A		CERTIFIC		VELS			
						US06				SC03		C	OMPOSIT	E	
	FUEL TYPE		NMOG+NOx		со	P	n N	NMOG+NOx		со	NMOG+NO	x CO	PM		
				(g/mi)		(g/mi)	(mg/	'mi)	(9	g/mi)	(g/mi)	(g/mi)	(g/m	i) (mg/mi)	
@ 4K	4K *		ERT	*		*			*		*				
-		5	STD	*		*				*	*		(g/mi) 1.6 1.6 4.2 /ELS RL (g/mi) @ 1 ERT \$ 0.00 0 CATION LEVE ED BLEED CA		
	CEF		ERT	*		*	2		*		*	0.050	1.6	*	
@ UL	JL GASOLINE- TIER3 E10		ISTO		*		6		*		*	0.070	4.2	*	
			BIN									0.070			
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
WHOLE VEHICLE EVAPORATIVE TESTING															
	EVAPORATIVE FAMILY		EL TYPE			(g/test) @ UL			2DHS (g/test) @ UL			F	RL (g/mi)	/mi) @ UL	
						STD	TD FEL CI		г	STD FEI		CE	RT	STD	
NKMXI	NKMXR0125NCG GASOLI LEV3 E		SOLINE- V3 E10	102	24 0	.300	*	0.14	6	0.300	*	0.	0.00 0.0		
0	ORVR / FUI	EL ON	ILY / CA	NISTER	BLEE	) EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VELS	
								FUE	EL O	NLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE	OF	RVR (g/	gallon) (	DUL	FUE				G TEST @UL		RIG TEST		CANISTER (test) @ 4K	
		FUEL	L TYPE	CERT	STD			CER	T	STD	CERT	STD	CERT	STD	
NKMXI	R0125NCG		DLINE- R3 E10	0.01	0.20		OLINE- 73 E10	*		*	*	*	0.003	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
NKMXR0125NCG	NKMXR0125NCG-SP2	0.00	0.02							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	SELTOS AWD	LDT1	1.6	AMS7	NKMXR0125NCG	1	F