

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MOD YEA		TEST	r group		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
202	2 N	NKMX	го2.4нн3		LDT1, LDT2				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFL	UL LII	FE (miles)		VEHICLE EMISSION CATEGOR					Y INTERIM / INTERMEDIATE IN-USE ST				
EX	H/ORVF	R	EVAP			FTP		SF	ТР	FTP		SFTP		
1	50000		150000		LEV3	SULEV30	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTRO SYSTEMS							L		OBD S	TATUS	EN	ENGINE DISPLACEMENT		
1	DFI, WR-HO2S, HO2S, WU-TWC, TWC								FULL	ALL MODELS				
*	*							P	PARTIAL	*		2.4		
*	* *								ARTIAL WITH * *					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							r	EVAP EMISSION STD VEHICLE CLASS			PECIAL FEATURES		
	NKMXRO	01338	ннс		LEV 3	LEV 3 OPTION2			LDT1			HCT		
					E	EMISSION CI	REDIT	r info	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV		REDIT FOR DOF		OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N		N		
					NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOO RAF	CH4 RAF						0-375							
*	*		1.10		*	0	.051			0.056		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this  $\frac{\mathcal{B}\mathcal{T}}{\mathcal{B}}$  day of February 2021.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	i+NOx mi)	CO (g/mi)			Ox mi)		HCHO (mg/mi)		-		PM /mi)	
			CERT	STD	CERT	STD	CERT	STD		CERT	STD	CEF	रा	STD	
FTP@50K	*		*	*	*	*	*	*		*	*	*		*	
FTP@UL	GASOLINE- TIER3 E10		0.020	0.030	0.2	1.0	*	*		*	4	0.001		0.003	
50°F @4K		SOLINE- R3 E10	0.014	0.060	0.1	1.0	*	*		*	8				
				FUEL TYP	-	NN	NMOG+NOx (g/mi)				CO (g/mi)				
				FUELTIP	CE	CERT		STD CER		t.		STD			
HWFET @	) 50K	*						*		*					
HWFET @	@ UL		0.0	0.007		0.030									
20°F @ 50K		COLD C	CO E10 RE	EGULAR GA	ASOLINE	(TIER3)					1.4			10.0	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

SFIP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																	
				US06							SC03		С	COMPOSITE			
	FUEL TY	PE		NMO	G+NC	)x	СО	PI	N	NMC	OG+NOx	со	NMOG+NC	)x	со	PM	
				(g/	/mi)		(g/mi)	(mg/	/mi)	(	g/mi)	(g/mi)	(g/mi)	(9	g/mi)	(mg/mi)	
@ 4K	4K *		CERT	*			*				*	*					
		STD					*			*		*					
	GASOLINE-		CERT		*		* 3			*		*	0.016	)	0.5	*	
@ UL			I STN I		*		*	* 6		*		*	0.070		4.2	*	
			BIN										0.030				
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																	
WHOLE VEHICLE EVAPORATIVE TE							TIVE TEST	ING									
	EVAPORATIVE FAMILY		FUEL TYPE		UEL TYPE		PE 3DHS (		S (g/test) @ UL		2DHS (g/test)		@ UL		RL (g/mi) @ l		UL
					CERT		STD FEL		CEF	RT STD		FEL	CE	CERT		STD	
NKMXF	NKMXR0133HHG		SOLINE EV3 E1(		0.248 0		300	*	0.1	71	0.300	*	0.	0.01		0.05	
0	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS								ELS								
									FU	JEL C	ONLY EVA	P & CANIS	STER BLEE	D			
	EVAPORATIVE FAMILY		ORVR (g/gal		llon) @ UL					HS RIG TEST g/test) @ UL			RIG TEST t) @ UL				
		FUE	L TYPE	CE	RT	STD			CE	RT	STD	CERT	STD	CEI	RT	STD	
NKMXF	R0133HHG		OLINE- R3 E10	0.0	00	0.20		OLINE- 73 E10	*	ł	*	*	*	0.0	11	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
NKMXR0133HHG	NKMXR0133HHG-QL1	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	SPORTAGE AWD	LDT2	2.4	SA6	NKMXR0133HHG	1	F
KIA	SPORTAGE FWD	LDT1	2.4	SA6	NKMXR0133HHG	1	F