

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST G	ROUP IN	FOR	MATION					
MODE YEAF		TEST GROUP			/EHICLE CLASS(ES)			FUEL	CATEGORY		FUEL TYPE		
2022	NJLXT02.0PTW			LDT4				PLUG-IN HYBRID ELECTRIC VEHICLE			GASOLINE		
USEFUL LIFE (miles)				VEHICLE EMISSION CATE				GORY INTERIM / IN			<b>TERMEDIATE IN-USE STD</b>		
EXF	I/ORVR	EVAP			FTP S			ТР	FTP		SFTP		
15	50000	150000		LEV3	SULEV30		-	SULEV ALONE	*		РМ		
SPECIAL FEATURES & EXHAUST EMISSION CON SYSTEMS						OL		OBD	STATUS	E	NGINE DISPLACEMENT (L)		
1	WR-HO2S, TWC, HO2S(2), DFI, TC, CAC							FULL	ALL MODELS				
*		*						ARTIAL	*		2.0		
*	*							TIAL WITH FINES	l *		1		
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	E STD CAT	EGORY	,		ISSION STD LE CLASS	S	SPECIAL FEATURES		
ľ	NJLXR01	L75M1A		LEV 3 OPTION2				LDT4			*		
				I	EMISSION	CREDIT	INFO	RMATION					
ALL	GR	CE FOR TEST OUP ZEV				G CREDIT FOR -PZEV ZERO- EVAP		FOR	FOR OPTIONAL EXH. STE FOR WORK TRUCKS				
	ALL N	MODELS	N			N		N		N			
	NMOG AND FLEET AVERAGE INFORMATION												
NMOG RAF	E RAE NMOG/NMHC RATIO PC+LDT (0-37					W) LDT (3751 LVW-8500 MDV			IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	1.10	C	0.02		0.051			0.056		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 2nd day of August 2021.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

### EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx CO (g/mi) (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)		
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	T STD
FTP@50K	( *		*	*	*	*	*	*	*	*	*	*
FTP@UL	UL GASOLINI LEV3 E1		0.0121	0.030	0.34	1.0	*	*	0	4	0.00	2 0.003
50°F @4K		SOLINE- V3 E10	0.0133	0.060	0.31	1.0	*	*	0	8		
				FUEL TYP	E		NN	NMOG+NOx (g/mi)			CO (g/mi)	
			I	FUEL ITP	E		CE	RT	STD	CER	Т	STD
HWFET @ 50K			*						*			
HWFET @ UL			GASOLINE-LEV3 E10					026	0.030			
20°F @ 50K			GASO	LINE-LEV	3 E10					0.7	4	12.5

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		S	FTP I	EXHAL	JST EN	IISSION	I STAND	ARDS /	AND	CERTIFIC	ATION LE	VELS			
			US06						SC03		C	OMPOSIT	E		
	FUEL TY	PE	NN	/IOG+N (g/mi)		CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/m	PM i) (mg/mi)	
@ 4K	*	CERT		*		*				*	*				
-		STD				*			*		*				
		CERT	CERT 0		5	4.35	4.35 1.2		0.0055		0.34	*	*	*	
@ UL	GASOLIN LEV3 E1	- SID		0.050		9.6		5	0.020		3.2	3.2 *		*	
												*			
		WHOLE V	EHIC	LE EV/	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS		
			w				HOLE VEHICLE EVAPORATIVE TESTING								
	ORATIVE	FUEL T	/PE	E 3DHS (g/test) @ UL					2DHS (g/test) @ UL				RL (g/mi) @ UL		
				CER	RL :	STD	FEL	CER	RL	STD	FEL	CE	RT	STD	
NJLXR0175M1A		GASOLI LEV3 E		0.41	12 0	.500	*	*		0.500	*	0.0	0.001 0.05		
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
							FUEL ONLY EVAP & CANISTER BLEED								
	ORATIVE	ORVR	(g/ga	llon) @	0 UL	FUEL TYPE			3DHS RIG TEST (g/test) @ UL			IG TEST ) @ UL		CANISTER g/test) @ 4K	
		FUEL TY	PE (	CERT	STD			CE	RT	STD	CERT	STD	CERT	STD	
N.TT.YI	20175M1a	GASOLIN	2- O	069	0 20		*	*		*	*	*	*	*	

0.069 0.20

LEV3 E10

NJLXR0175M1A



JAGUAR LAND ROVER LIMITED

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
NJLXR0175M1A	NJLXR0175M1A-001	*	0.02						

': not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	LAND ROVER	RANGE ROVER SPORT PHEV	LDT4	2.0	SA8	NJLXR0175M1A	1	F

## **ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION**

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV	
NUMBER		(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE
1	TZEV	27.2	27.2	*	25.79	25.79	0.57