

Executive Order: A-413-0226-2
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODE YEAF	_	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY				FUEL TYPE		
2022	NV	GAJ02.0A3T		DT2, PC			DEDICATED SINGLE FUEL VEHICLE			GASOLINE				
	USEFUL	. LIFE (miles)		VEH	IICLE EMISS	ION C	ATE	ATEGORY INTERIM / INTERMEDIATE IN-USE S						
EXH	I/ORVR	EVAP			FTP		SF	TP		FTP	SFTP			
15	0000	150000		LEV3	SULEV30	LEV	3 C	OMPOSITE		*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT			
1	DFI,	IC, CAC, AIR	, TWO	C(2), WR	-HO2S, HO2	s		FULL		*				
*	*							PARTIAL	5	SOME MODELS		2.0		
*	*							TIAL WITH	5	SOME MODELS				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	P / ORV	R FAMILY	EVAI	PORATIVI	STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
ı	VGAR01	10ACA	LE	V 3 OPT	ON2 WITH	FEL PC			*					
ı	VGAR01	35ACT	LE	V 3 OPT	ON2 WITH	FEL	LDT2			2	*			
					EMISSION CI	REDIT	INF	ORMATION		·				
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY	1		REDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG C	RI	EDIT FOR DOF	R OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N					N		N		
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TI	ON				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		IO/NMHC RATIO	NMOG+NO PC+LDT (						D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		0.03	0	.051			0.056			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-413-0226-2

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed Q3 QUATTRO vehicle model is conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three (3) deficiencies. The listed Q3 QUATTRO vehicle model is approved subject to the manufacturer paying a fine of twenty-five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2022 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$40,725 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. This Executive Order hereby cancels and supersedes Executive Order A-413-0226-1 dated June 8, 2021.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>23rd</u> day of June 2021.

Allen Lyons, Chief

**Emissions Certification and Compliance Division** 

Executive Order: A-413-0226-2
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 3 of 4

# **ATTACHMENT**

# **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

# EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

### **FUEL TYPE**

		NMOG+NOx (g/mi)				NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10	0.014	0.030	0.3	1.0	*	*	*	4	0.001	0.003
50°F @4K	GASOLINE- TIER3 E10	0.016	0.060	0.5	1.0	*	*	*	16		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUELTIFE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-TIER3 E10	0.002	0.030			
20°F @ 50K	GASOLINE-TIER3 E10			0.3	10.0	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	1	*	*	0.012	0.3	*
@ UL	GASOLINE- TIER3 E10	STD	*	*	6	*	*	0.070	4.2	*
		BIN						0.040		

### WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \						
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) (	@ UL	2DI	HS (g/test) (	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
NVGAR0110ACA	GASOLINE- TIER3 E10	0.256	0.300	0.300	0.219	0.300	0.300	0.00	0.05
NVGAR0135ACT	GASOLINE- TIER3 E10	0.323	0.400	0.350	0.245	0.400	0.350	0.00	0.05

Executive Order: A-413-0226-2
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE		_	IG TEST ) @ UL	_	RIG TEST t) @ UL	BLEED CANISTER TEST (g/test) @ 4K			
	<b>FUEL TYP</b>	E CERT	STD			CERT	STD	CERT	STD	CERT	STD		
NVGAR0110ACA	GASOLINE TIER3 E1	1 0 03	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.003	0.020		
NVGAR0135ACT		GASOLINE- TIER3 E10 0.02 0.20		GASOLINE- TIER3 E10		*	*	*	*	0.006	0.020		
	EFFECTIV	E LEAK D	IAMET	ER STA	NDAR	D AND CE	RTIFICA	TION LEV	/EL (INCF	IES)			
EVAPORATIVE	FAMILY	LEA	K FAMII	LY	Y CERT				STD				
NVGAR0135	SACT	NVGAR0	135ACT	-001	-001 *				0.02				
NVGAR0110ACA NVGAR0110ACA-			-001	•001 *					0.02				

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection: DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2022 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
AUDI	Q3 QUATTRO	LDT2	2.0	SA8	NVGAR0135ACT	1	\$
AUDI	Q3 S LINE QUATTRO	LDT2	2.0	SA8	NVGAR0135ACT	1	P
AUDI	TT COUPE QUATTRO	PC	2.0	AMS7	NVGAR0110ACA	1	P
AUDI	TT ROADSTER QUATTRO	PC	2.0	AMS7	NVGAR0110ACA	1	P