

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

|  |  |   |                                |      |          | TEST GRO                | UP II | NFOR   | MATION   |              |  |                                      |  |  |
|--|--|---|--------------------------------|------|----------|-------------------------|-------|--------|--|--------------|--|--------------------------------------|--|--|
| MODE<br>YEA  |  | TES   | T GROUP                        |      | VEHIC    | LE CLASS(E              | S)    |        | FUEL CATEGORY  |              |  | FUEL TYPE                            |  |  |
| 202:   | 3 1  | PMBX  | T02.0U3A                       |      |          | LDT3                    |       |        | DEDICATED SINGLE FUEL<br>VEHICLE                             |              |  | GASOLINE                             |  |  |
| USEFUL LIFE (miles) VE                                 |  |   |                                |      |          | IICLE EMISS             | ION ( | CATE   | GORY   | INTERIM / IN | MEDIATE IN-USE STD   |                                      |  |  |
| EXH/ORVR EVAP  |  |   |                                |      |          | FTP                     |       | SF     | ТР   | FTP          |  | SFTP                                 |  |  |
| 1  | 50000                                      |   | 150000                         |      | LEV3     | ULEV70                  | LEV   | 3 C    | OMPOSITE   | *            |  | PM                                   |  |  |
| SPECIAL FEATURES & EXHAUST EMISSION CONTROL<br>SYSTEMS |  |   |                                |      |          | L                       |       | OBD S  | TATUS  | E            | ENGINE DISPLACEMENT<br>(L)                                 |                                      |  |  |
| 1  | DFI, TC, CAC, WR-HO2S, HO2S, TWC           |   |                                |      |          |                         |       |        | FULL   | *            |  |                                      |  |  |
| *  | *  |   |                                |      |          |                         |       | F      | PARTIAL  | *            |  | 2.0                                  |  |  |
| *  | * *  |   |                                |      |          |                         |       |        | RTIAL WITH<br>FINES  | ALL MODELS   |  |                                      |  |  |
|  |  |   | EV                             | APOF | RATIVE & | REFUELING               | (EVA  | AP/OF  | RVR) FAMIL   |              | 1  |                                      |  |  |
| EVA  | EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR |   |                                |      |          |                         | GOR   | (      | EVAP EMISSION STD<br>VEHICLE CLASS                           |              |  | SPECIAL FEATURES                     |  |  |
|  | PMBXR                                      | .0170                                       | LNF                            | LE   | V 3 OPTI | ON2 WITH 1              | FEL   |        | LI   | от3          |  | *                                    |  |  |
|  |  |   |                                |      | E        | EMISSION CI             | REDI  | T INF  | ORMATION   |              |  |                                      |  |  |
|  | REDIT F                                    | FOR   | FLEET AVE.<br>EXTENDED<br>ANTY | I    |          | EDIT FOR N<br>ZERO-EVAP | ON-P  | ZEV    | NMOG CREDIT FOR DOR  |              |  | OPTIONAL EXH. STD<br>FOR WORK TRUCKS |  |  |
|  | N N  |   |                                |      |          |                         |       |        | N N  |              |  |                                      |  |  |
|  |  |   |                                |      | NMOG     | AND FLEET               | AVE   | RAG    | E INFORMA  | TION         |  |                                      |  |  |
| NMOG<br>RAF  |  | CH4 FTP<br>RAF NMOG/NMHC RATIO RATIO (g/mi) |                                |      |          | 0-375                   |       | V) LDT | +NOX FLEET S <sup></sup><br>(3751 LVW-8500<br>R) + MDPV (g/m |              | D NMOG+NOX FLEET STD<br>MDV (10,001-14,000<br>GVWR) (g/mi) |                                      |  |  |
| *  | *  |   | 1.10                           | 0    | .018     | 0                       | .044  |        |  | 0.047        |  | *                                    |  |  |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles have been determined to have seven (7) deficiencies. The listed vehicle model(s) are approved subject to the manufacturer paying a fine of one hundred twenty-five dollars (\$125) per vehicle for the third through seventh deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2023 model year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$42,450 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 2Oth day of September 2022.

Jolin U. Lang

Robin U. Lang, Chief *U* Emissions Certification and Compliance Division



FUEL TYPE

GASOLINE-

TIER3 E10

0.01

0.20

TIER3 E10

PREM

PMBXR0170LNF

0.017

\*

0.020

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

## EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

|             |                                |          |           | i+NOx<br>mi) |           | O<br>mi) |          | Ox<br>mi) | HCI<br>(mg/ | -         | -     | M<br>mi) |
|-------------|--------------------------------|----------|-----------|--------------|-----------|----------|----------|-----------|-------------|-----------|-------|----------|
|             |                                | CERT STD |           | CERT         | STD       | CERT     | STD      | CERT      | STD         | CERT      | STD   |          |
| FTP@50K     | < *                            |          | *         | *            | *         | *        | *        | *         | *           | *         | *     | *        |
| FTP@UL      | GASOLINE-<br>TIER3 E10<br>PREM |          | 0.064     | 0.070        | 1.5       | 1.7      | *        | *         | 0.5         | 4         | 0.001 | 0.003    |
| 50°F @4K    |                                | *        | *         | *            | *         | *        | *        | *         | *           | *         |       |          |
|             |                                |          |           |              |           |          |          | IOG+NO    | x (g/mi)    | CO (g/mi) |       |          |
|             | FUEL TYPE                      |          |           |              |           |          | CE       | RT        | STD         | CER       | T     | STD      |
| HWFET @ 50K |                                |          |           | *            |           |          | *        | ·         | *           |           |       |          |
| HWFET @ UL  |                                |          | GASOLIN   | E-TIER3      | E10 PREM  | 1        | 0.0      | 38        | 0.070       |           |       |          |
| 20°F @ 50K  |                                | COLD (   | CO E10 PF | REMIUM GZ    | SOLINE    | (TIER3)  |          |           |             |           | 2     | 12.5     |
|             |                                |          | SFTP EXH  | IAUST EM     | ISSION ST | TANDARD  | S AND CE |           | TION LEVE   | LS        |       |          |

|       |                            |      |                            |                  |       |              | ••••••••                         |           |       |                    |              |                   |                                   |     |               |
|-------|----------------------------|------|----------------------------|------------------|-------|--------------|----------------------------------|-----------|-------|--------------------|--------------|-------------------|-----------------------------------|-----|---------------|
|       |                            |      |                            |                  |       | US06         |                                  |           |       | SC03               |              | С                 | OMPOS                             | ITE |               |
|       | FUEL TY                    | PE   | ١                          | NMOG+N<br>(g/mi) |       | CO<br>(g/mi) | P<br>(mg                         | M<br>/mi) |       | DG+NOx<br>g/mi)    | CO<br>(g/mi) | NMOG+NC<br>(g/mi) | Dx C<br>(g/i                      |     | PM<br>(mg/mi) |
| @ 4K  | @4K *                      |      | CERT                       | *                |       | *            |                                  |           |       | * *                |              |                   |                                   |     |               |
| -     |                            | ;    | STD                        | *                |       | *            |                                  |           |       | *                  | *            |                   |                                   |     |               |
|       |                            | C    | CERT                       | *                |       | *            | 2                                | 2         |       | *                  | *            | 0.052             | 1.                                | 9   | *             |
| @ UL  | GASOLIN<br>TIER3 E<br>PREM |      | STD                        | *                |       | *            |                                  | 5         |       | *                  | *            | 0.063             | 4.                                | 2   | *             |
|       |                            |      | BIN                        |                  |       |              |                                  |           |       |                    |              | 0.070             |                                   |     |               |
|       |                            | ωно  | LE VEH                     | CLE EV           | APOR  | ATIVE E      | MISSION                          | STAN      | IDAR  | DS AND C           | ERTIFICA     | TION LEVE         | ELS                               |     |               |
|       |                            |      |                            |                  |       | HOLE \       | HOLE VEHICLE EVAPORATIVE TESTING |           |       |                    |              |                   |                                   |     |               |
|       | ORATIVE                    |      |                            | 5 3              | DHS ( | g/test) (    | g/test) @ UL                     |           |       | 2DHS (g/test) @ UL |              |                   | RL (g/mi) @ UI                    |     | UL            |
|       |                            |      |                            | CEF              | RT    | STD          | FEL                              | CEF       | RT    | STD                | FEL          | CE                | RT                                |     | STD           |
| PMBXF | R0170LNF                   | TI   | SOLINE-<br>ER3 E1(<br>PREM |                  | 28 0  | ).500        | 0.450                            | 0.3       | 30    | 0.500              | 0.450        | 0.                | 02                                | (   | 0.05          |
| C     | ORVR / FUI                 |      | NLY / CA                   | NISTER           | BLEE  | D EVAP       | ORATIVE                          | EMIS      | SION  | STANDA             | RDS AND      | CERTIFIC          | ATION L                           | EVE | LS            |
|       |                            |      |                            |                  |       |              |                                  | FU        | JEL C | NLY EVA            | P & CANIS    | TER BLEE          | D                                 |     |               |
|       | ORATIVE<br>AMILY           | 0    | RVR (g/g                   | gallon) @        | ) UL  | FUE          | L TYPE                           | _         | -     | IG TEST<br>) @ UL  | -            | t) @ UL           | 063  4.2  *    063  4.2  *    070 | -   |               |
|       |                            | FUE  | L TYPE                     | CERT             | STD   |              |                                  | CE        | RT    | STD                | CERT         | STD               | CERT                              | •   | STD           |
|       |                            | GASC | OLTNE-                     |                  |       | GAS          | OLINE-                           |           |       |                    |              |                   |                                   | T   |               |

\*

CALIFORNIA

| EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES) |                  |      |      |  |  |  |  |  |
|---|------------------|------|------|--|--|--|--|--|
| EVAPORATIVE FAMILY  | LEAK FAMILY      | CERT | STD  |  |  |  |  |  |
| PMBXR0170LNF  | PMBXR0170LNF-LNF | *    | 0.02 |  |  |  |  |  |

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2023 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE          | MAKE MODEL     |      | ENGINE (L) | TRANS TYPE | EVAPORATIVE<br>FAMILY | EXH<br>ECS | OBD |
|---------------|----------------|------|------------|------------|-----------------------|------------|-----|
| MERCEDES BENZ | GLE 350        | LDT3 | 2.0        | A9         | PMBXR0170LNF          | 1          | \$  |
| MERCEDES BENZ | GLE 350 4MATIC | LDT3 | 2.0        | A9         | PMBXR0170LNF          | 1          | \$  |