

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	OUP IN	IFORI	MATION					
MODE	- T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2023	B PB	MXJ04.4S68		L	DT4, PC		HYBRID ELECTRIC VEHICLE				GASOLINE		
	USEFUL	LIFE (miles)		VEF	ICLE EMISS	ION C	ATEC	GORY	INTERIM / IN	TER	ERMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP			FTP		SF	TP	FTP		SFTP		
15	50000	150000)	LEV3	ULEV70	LEV	3 CC	MPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	E	ENGINE DISPLACEMENT (L)		
DFI, 2TC, 2CAC, 2WU-TWC, 2TWC, 2WR-HO2S, 2HO2S								FULL	JLL *				
*			*				P	ARTIAL	ALL MODELS	4.4			
*			*					TIAL WITH FINES	TH *				
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATIO	N			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	PBMXR01	.80G05	EV 3 OPTI	CON2 WITH	FEL		PC			*			
					EMISSION CI	REDIT		RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET	T AVE	RAGE		TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HO/NMHC RATIO	NMOG+NO PC+LDT ((g			/) LDT	+NOX FLEET S (3751 LVW-850(R) + MDPV (g/m)	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\underline{6^{+}}$ day of June 2022.

Johne Schi for

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)		-	C (g/I		Ox mi)		CHO g/mi)	PM (g/mi)		
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	T STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.024	0.070	0.6	1.7	*	*	*	4	0.00	1 0.003
50°F @4K		SOLINE- R3 E10	0.021	0.140	0.6	1.7	*	*	*	16		
				FUEL TYP	E		NN	10G+N	Ox (g/mi)		CO (g/	/mi)
				FUEL ITP	E		CE	RT	STD	CER	Т	STD
HWFET @ 50K			*		*		*					
HWFET @ UL			GASOI	INE-TIER	R3 E10		0.0	27	0.070			
20°F @ 50K		COLD C	CO E10 RE	GULAR G	ASOLINE	(TIER3)				1.0)	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			55		XHAU		132101	I STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS				
						US06				SC03		C	OMPOSIT	E			
	FUEL TY	PE			OG+N (g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi))x CO (g/mi	PM) (mg/mi)		
@ 4K	*		CERT	*		*					*	*					
•			STD		*		*				*	*					
			CERT		*		*	0)		*	*	0.020	0.020 0.6			
@ UL	GASOLIN TIER3 E		STD		*		*	6	5		*	*	0.063	4.2	*		
			BIN										0.070				
		WH	OLE VE	HICL	E EV	APOR/	TIVE E	MISSION	STAN	IDAR	DS AND C	ERTIFICA	TION LEVE	LS			
WHOLE VEHICLE EVAPORATIVE TESTING																	
	ORATIVE AMILY			FUEL TYPE		PE 3DHS (DHS (g	6 (g/test) @ UL		2DHS (g/test)			@ UL	F	RL (g/mi) @	
					CER	RT :	STD	FEL	CEF	RT	STD	FEL	CE	RT	STD		
PBMXI	R0180G05	-	ASOLINI IER3 E		0.18	34 0	.300	0.500	0.2	26	0.300	0.50	0.	01	0.05		
(ORVR / FU	EL O	ONLY / C	ANI	STER	BLEE) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	/ELS		
									FU	JEL C	NLY EVA	P & CANIS	STER BLEE	D			
	ORATIVE	(ORVR (g	/gal	lon) @) UL	FUE	L TYPE			G TEST) @ UL		RIG TEST t) @ UL		CANISTER test) @ 4K		
		FU	EL TYPE	C	ERT	STD			CE	RT	STD	CERT	STD	CERT	STD		
PBMXI	R0180G05	-	SOLINE- ER3 E1(0	.05	0.20		OLINE- R3 E10	*	,	*	*	*	0.011	0.020		



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PBMXR0180G05	PBMXR0180G05-001	0.01	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BMW	7601 XDRIVE SEDAN	PC	4.4	SA8	PBMXR0180G05	1	P
BMW	X7 M601 XDRIVE	LDT4	4.4	SA8	PBMXR0180G05	1	Р