

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE YEAF		EST GROUP	VEHICLE CLASS(ES)				FUEL C	ATEGORY		FUEL TYPE			
2023	B PE		τ.DT4			SINGLE FUEL HICLE		GASOLINE					
USEFUL LIFE (miles) VEHICLE EI							CATE	TERN	ERMEDIATE IN-USE STD				
EXH	I/ORVR	EVAP			FTP		SF	FTP FTP			SFTP		
15	50000	150000)	LEV3	ULEV50	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	STATUS		ENGINE DISPLACEMENT (L)		
1	2TWC(2),DFI,2TC,2HO2S,2WR-HO2S,CAC							FULL	*				
*	* *							PARTIAL	ALL MODELS		3.0		
*						PAR	PARTIAL WITH * FINES						
		E	VAPO	RATIVE &	REFUELING	(EVA	AP/OR	RVR) FAMIL	(INFORMATION				
EVA	NP / ORV	R FAMILY	PORATIVE	E STD CATE	GOR	(EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
1	PFMXR01	40NDG	LE	V 3 OPTI	ION2 WITH 1	FEL		LDT4			HCT		
				I	EMISSION CI	REDI	T INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOF			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF					0-375							
*	*	1.10		*	0	.044		0.047 *					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 27th day of October 2022.

Jolin U. Lang

Robin U. Lang, Chief *()* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		CHO g/mi)		PM (g/mi)		
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CEF	RT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	* *	
FTP@UL		SOLINE- R3 E10	0.034	0.050	0.3	1.7	*	*	0.1	4	0.0	01	0.003
50°F @4K	GASOLINE- TIER3 E10		0.049	0.100	0.3	1.7	*	*	0.5	16			
		FUEL TYPE						IOG+N	Ox (g/mi)		CO (g/mi)		
				FUELITP	E		CE	RT	STD	CER	RT		STD
HWFET @ 50K				*			*		*				
HWFET @ UL 20°F @ 50K			GASOI	LINE-TIEF	R3 E10	0.0	31	0.050					
		COLD C	CO E10 RE	GULAR G				0.8	3		12.5		

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			Эг		ΧΠΑ		122101	1 STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS			
							US06				SC03		C	OMPOSIT	E	
	FUEL TY	PE		NM	OG+N	IOx	CO	PI	N	NMC	OG+NOx	СО	NMOG+NC	x CO	PM	
					(g/mi)		(g/mi)	(mg/	/mi)	(g/mi)	(g/mi)	(g/mi)	(g/m	i) (mg/mi)	
@ 4K	*		CERT	*			*				*	*				
_			STD		*		*				*	*				
			CERT		*		*	2			*	*	0.050	0.4	*	
@ UL	GASOLIN TIER3 E		STD		*		*	6	5		*	*	0.063	(g/mi) 0.4 4.2 ELS RL (g/mi) @ U ERT 00 ATION LEVEL D BLEED CAN TEST (g/test CERT	*	
			BIN										0.060			
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
					WHOLE VEHICLE EVAPORATIVE TESTING											
EVAPORATIVE FAMILY		FUEL TYF		UEL TYPE				DHS (g	6 (g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @ U	
				CERT				FEL CE		RT	STD	FEL	CE	RT	STD	
PFMXI	PFMXR0140NDG GASOLINE TIER3 E10			0.373 (.500 0.500		0.3	38	0.500	0.50	0 0.	00	0.05		
(ORVR / FU	EL C	ONLY / C	ANI	STER	BLEED) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	/ELS	
									FU	JEL C	NLY EVA	P & CANIS	STER BLEE	D		
	ORATIVE AMILY	(ORVR (g/gallon) @ UL		FUE			DHS RIG TEST g/test) @ UL			RIG TEST t) @ UL					
		FU	EL TYPE	C	ERT	STD]		CE	RT	STD	CERT	STD	CERT	STD	
PFMX	R0140NDG	-	SOLINE- ER3 E1(0.10	0.20		OLINE- R3 E10	*	r	*	*	*	0.015	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
PFMXR0140NDG	PFMXR0140NDG-001	*	0.02							
*										

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L) TRANS TYPE EVAPORATIVE FAMILY				OBD
FORD	BRONCO RAPTOR 4WD	LDT4	3.0	SA10	PFMXR0140NDG	1	Р