

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	DUP IN	NFOR	MATION					
MODE		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2023	PF	MXT03.54HF		LDT4				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEHICLE EMISSION CATEGOR				GORY	INTERIM / IN	TERN	ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP		FTP				SFTP FTP			SFTP		
15	0000	15000	D	LEV3	ULEV50	LEV	3 C	MPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	ENGINE DISPLACEMENT (L)			
1 DFI, SFI, 2TWC, 2WR-HO2S, 2HO2S, 2TC, CAC, EGR, EGRC								FULL	*				
*	*							ARTIAL	ALL MODELS		3.5		
*	*							TIAL WITH	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	P / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	r	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
E	FMXR02	00gdg	LE	V 3 OPTI	3 OPTION2 WITH FEL			LDT4			HCT		
E	FMXR02	60NDV	LE	IV 3 OPTI	ION2 WITH FEL			LDT4			HCT		
		1			EMISSION C	REDI		ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							EV NMOG CREDIT FOR DOP			R OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N			N		
				NMOG	AND FLEE	T AVE	RAG	E INFORMA	TION				
NMOG RAF	NMOG/NMHC:				NMOG+NOX FLEET ST PC+LDT (0-3750 LVW) (g/mi)								
*	*	1.10		*	0	0.044 0.047 *							
Soo th		mont for Vahi			porativo Ea	milv	Engir		mont Emission	Cor	trol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

This Executive Order hereby cancels and supersedes Executive Order A-010-2443 dated November 1, 2022.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this  $\frac{12th}{2}$  day of April 2023.

Rolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



**FUEL TYPE** 

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+I (g/mi					NOx (g/mi)		HO /mi)	PM (g/mi)			
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	<b>*</b>		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.032	0.050	0.7	1.7	*	*	0	4	0.00	1 0.003	
50°F @4K	*		*	*	*	*	*	*	*	*			
					E	<u>.</u>	NN	NMOG+NOx (g/mi)			CO (g/mi)		
	FUEL TYPE						CE	RT	STD	CER	Т	STD	
HWFET @ 50K				*			*		*				
HWFET @ UL			GASOI	LINE-TIE	R3 E10		0.0	010	0.050				
20°F @ 50K		COLD	CO E10 RE	EGULAR G	ASOLINE	(TIER3)				0.4	L	12.5	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																
						US06				SC03			COMPOSITE			
	FUEL TYPE				OG+NOx g/mi)	CO (g/mi)		PM g/mi)		)G+NOx g/mi)	CO (g/mi)		OG+NOx (g/mi)	CO (g/m		PM (mg/mi)
@ 4K	*		CERT		*	*				*	*					
			STD		*	*				*	*					
	DUL GASOLINE- TIER3 E10		CERT	*		*		1		*	*	0.026		.026 0.8		*
@ UL			STD			* *		6		*	*	0.063		4.2		*
			BIN									0	0.060			
		WH	OLE VE	HICL	E EVAPO	ORATIVE E	MISSION	I STAN	DAR	DS AND C	ERTIFIC	ATIO	N LEVELS	;		
						WHOLE \	/EHICLE	EVAPO	ORAT	IVE TEST	ING					
	EVAPORATIVE FAMILY		FUEL TYPE		E 3DHS (g/test) @			UL 2DHS (g/te			S (g/test) @ UL			RL (g/mi) @ UL		
					CERT	STD	FEL	CER	2T	STD	FE	L CERT		RT S		TD
PFMXR0200GDG		-	ASOLIN IER3 E	0 2989		0.500	0.500	*		0.500	0.500		0 0.000		0	. 05
PFMXR0260NDV			GASOLINE- TIER3 E10		0.2212	0.500	0.500	0.19	81	0.500	0.5	0.001		0.001 0.		. 05



LINCOLN

NAVIGATOR 4X4

LDT4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
		FUEL ONLY EVAP & CANISTER BLEED												
EVAPORATIVE FAMILY	ORVR (g/	FUEL 1	ГҮРЕ	3DHS R (g/test		-	RIG TEST st) @ UL	BLEED CANISTER TEST (g/test) @ 4K						
	FUEL TYPE	CERT STD				CERT	STD	CERT	STD	CERT	STD			
PFMXR0200GDG	GASOLINE- TIER3 E10 0.022 0.20		GASOLINE- TIER3 E10		*	*	*	*	0.0100	0.020				
PFMXR0260NDV	GASOLINE- TIER3 E10 0.01		0.20	GASOLINE- TIER3 E10		*	*	*	*	0.0107	0.020			
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)													
EVAPORATIVE	Y CERT					STD								
PFMXR0200GDG PFMXR0200GI			200GDG	-001	-001 *				0.02					
PFMXR0260	NDV	pfmxr0	260NDV	-001		*			0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER: PHEV: plug-in hybrid electric vehicle: NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits. Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION													
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD						
FORD	EXPEDITION 4X2	LDT4	3.5	SA10	PFMXR0200GDG	1	P						
FORD	EXPEDITION 4X2	LDT4	3.5	SA10	PFMXR0260NDV	1	Р						
FORD	EXPEDITION 4X4	LDT4	3.5	SA10	PFMXR0200GDG	1	Р						
FORD	EXPEDITION 4X4	LDT4	3.5	SA10	PFMXR0260NDV	1	P						
FORD	EXPEDITION STEALTH	LDT4	3.5	SA10	PFMXR0200GDG	1	Р						
FORD	EXPEDITION STEALTH	LDT4	3.5	SA10	PFMXR0260NDV	1	P						
FORD	EXPEDITION TIMBERLINE 4X4	LDT4	3.5	SA10	PFMXR0200GDG	1	P						
LINCOLN	NAVIGATOR 4X2	LDT4	3.5	SA10	PFMXR0200GDG	1	Р						
LINCOLN	NAVIGATOR 4X2	LDT4	3.5	SA10	PFMXR0260NDV	1	Р						
LINCOLN	NAVIGATOR 4X4	LDT4	3.5	SA10	PFMXR0200GDG	1	Р						

3.5

SA10

PFMXR0260NDV

1

Ρ