

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE YEAR		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2023	PF	MXV05.0VKN		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
l	USEFUL	. LIFE (miles)		VEHICLE EMISSION CATEG				GORY INTERIM / INT			ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP			FTP		SF	FTP FTP			SFTP		
15	0000	150000		LEV3	ULEV125 LEV 3 COM			OMPOSITE	*		РМ		
SPE	TEMISSIC	ON CONTRO	L		OBD S	TATUS		ENGINE DISPLACEMENT (L)					
1	:	2TWC(2),DFI,	SFI,2	WR-HO2S	,2HO2S			FULL	*				
*			*				P	PARTIAL	ALL MODELS		5.0		
*		*						TIAL WITH	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	P / ORV	R FAMILY	EVAF	PORATIVE	E STD CATE	GORY	(EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
P	FMXR01	30NDM	LE.	EV 3 OPTION2 WITH FEL				PC			НСТ		
P	FMXR01	.30ndn	LE.	LEV 3 OPTION2 WITH FEL PC HCT				PC			НСТ		
				I	EMISSION CI	REDI	T INFO	ORMATION					
	EDIT FC	X FLEET AVE. OR EXTENDED RRANTY	I		EDIT FOR N ZERO-EVAP	ON-P	ZEV	ZEV NMOG CREDIT FOR DOP			R OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF FTP NMOG/NMHC RATIO HCHO/NMHC RATIO (g/mi)				0-375								
*	*	1.10		*	0	.044			0.047		*		
Soo th		mont for Vahi			norotivo Co	milu	Enair	na Dianlaad	mont Emissio	<u> </u>	ontrol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this _____ day of November 2022.

John Schi for

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/	6+NOx mi)	CO (g/mi)			NOx (g/mi)		HO /mi)	(PM g/mi)	
			CERT	STD	CERT	STD	CERT	CERT STD		STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.062	0.125	1.2	2.1	*	*	1	4	0.002	2 0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
				FUEL TYP	-		NN	10G+N	Ox (g/mi)	CO (g/mi)			
				FUELITP	E		CE	RT	STD	CER	т	STD	
HWFET @ 50K				*			*		*				
HWFET @ UL			GASOI	LINE-TIE	R3 E10		0.0	39	0.125				
20°F @ 50K		COLD (CO E10 RE	EGULAR GA	ASOLINE	(TIER3)				3.4		10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

SFIP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS														
						US06			SC03	COMPOSITE				
	FUEL TYPE				OG+NOx	_	-		NMOG+NOx	CO	NMOG+NC		CO (mi)	PM (ma/mi)
					(g/mi)	(g/mi)	(ing	J/mi)	(g/mi)	(g/mi)	(g/mi)	(y	/mi)	(mg/mi)
@ 4K	*		CERT	*		*			*	*				
-			STD	*		*			*	*				
		I SID			*	*		1	*	*	0.087	1	1	*
@ UL	GASOLINE TIER3 E1			*		*		6	*	*	0.063	0.063		*
			BIN								0.110			
	١	WH	OLE VE	HICL	E EVAPO	ORATIVE E	EMISSION	I STANE	DARDS AND	CERTIFIC	ATION LEVE	ELS		
						WHOLE	VEHICLE	EVAPO	RATIVE TES	TING				
	ORATIVE	FUEL TY		ΈE	3DH	S (g/test) (@ UL		2DHS (g/test	I	RL (g/mi) @ UL			
					CERT	STD	FEL	CER	T STD	FEL	_ CE	RT		STD
PFMXR0130NDM		-	GASOLINE- TIER3 E10 PREM		0.186	0.300	0.300	0.24	6 0.300	0.30	0.00		0.05	
PFMXF	R0130NDN	-	ASOLIN IER3 E PREM	:10	0.170	0.300	0.300	0.15	8 0.300	0.30	00 0.00		0.05	



ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE			IG TEST) @ UL		RIG TEST est) @ UL	BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	FUEL TYPE CERT STD				CERT	STD	CERT	STD	CERT	STD		
PFMXR0130NDM	E10-EPA	0.04	0.20	GASOLINE- TIER3 E10 PREM		*	*	*	*	0.007	0.020		
PFMXR0130NDN	Е10-ЕРА 0.04 0.		0.20	GASOLINE- TIER3 E10 PREM		*	*	*	*	0.007	0.020		
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)													
EVAPORATIVE	Y CERT					STD							
PFMXR0130NDM PFM			130NDM	-001		*	r		0.02				
PFMXR0130	NDN	PFMXR0	130NDN	-001		*	·		0.02				

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	MUSTANG	PC	5.0	M6,SA10	PFMXR0130NDM	1	Р
FORD	MUSTANG CONVERTIBLE	PC	5.0	M6, SA10	PFMXR0130NDM	1	P
FORD	MUSTANG MACH 1	PC	5.0	M6, SA10	PFMXR0130NDN	1	Р