

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODE YEAF		TEST G	ROUP		VEHIC	LE CLASS(E	E CLASS(ES) FUEL CATEGORY					FUEL TYPE		
2023	3 F	PTYXV02	2.0P3C			PC DEDICATED SINGLE FUEL VEHICLE						GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								CATE	EGORY INTERIM / INTERMEDIATE IN-USE STD					
EXH	I/ORVF	र	EVAP			FTP		SF	ТР	FTP		SFTP		
15	50000		150000		LEV3	SULEV30	LEV	3 COMPOSITE *				PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L		OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	DFI, SFI, EGR, EGRC, WR-HO2S(2), TWC(2)								FULL	ALL MODELS				
*	*								PARTIAL *			2.0		
* *									TIAL WITH	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	PTYXRO	0130P72	2	LE.	V 3 OPTI	ON2 WITH	FEL		I	× ×				
					E	EMISSION CI	REDIT	r info	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N N				
					NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF					0-375					D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*		1.10	L.10 * 0.044 0.047 *							*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 10th day of February 2023.

Robin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)				O mi)		NOx (g/mi)		HO /mi)		M 'mi)	
			CERT	STD	CERT	STD	CERT STD		CERT	STD	CERT	STD	
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.0156	0.030	0.12	1.0	*	*	*	4	0.0001	0.003	
50°F @4K	*		*	*	*	*	*	*	*	*			
				FUEL TYP		<u> </u>	NM	IOG+N	Ox (g/mi)		CO (g/mi)		
				FUELITP	E		CE	RT	STD	CER	T	STD	
HWFET @ 50K				*			*	*		*			
HWFET @ UL			GASOI	LINE-TIE	R3 E10		0.0	095	0.030				
20°F @ 50K		COLD (CO E10 RE	GULAR G	ASOLINE	(TIER3)				0.6	10.0		

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SF	ΓΡΕ	ΧΗΑ	JST EN	ISSION	I STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS				
							US06				SC03		С	OMPOS	SITE		
	FUEL TYPE			NMOG+NOx (g/mi)			CO (g/mi)		PM (mg/mi)		DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)		:O mi)	PM (mg/mi)	
@ 4K	@4K *		CERT		*		*			*		*					
-		Γ	STD	*			*				*	*					
	@ UL GASOLINE- TIER3 E10		CERT		*		*	* 0.2		*		*	0.0154	0.	28	*	
@ UL			STD	*		* 6		5	*		*	0.063	4	. 2	*		
			BIN										0.030				
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																
				WHOLE VEHICLE EVAPORATIVE TESTING													
	ORATIVE AMILY	FUEL TY		FUEL TYPE		PE 3DHS (g		(g/test) @ UL		2DH		2DHS (g/test) @ UL			RL (g/m	L (g/mi) @ UL	
						CERT		FEL	CEF	RT	STD	FEL	CE	RT	STD		
PTYXR0130P72			ASOLINE IER3 E1	-	0.26	88 0	.300	0.300	*		0.300	0.300	0.0	008	8 0.05		
0	ORVR / FU	EL O	NLY/C	ANIS	STER	BLEEI) EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFICA	ATION L	.EVE	LS	
									FU	JEL C	ONLY EVA	P & CANIS	STER BLEE	D			
	ORATIVE AMILY	ORVR (g/gallo		lon) @	0 UL	FUE			HS RIG TEST g/test) @ UL			RIG TEST t) @ UL			CANISTER (test) @ 4K		
		FUE	EL TYPE	С	ERT	STD			CE	RT	STD	CERT	STD	CER	Т	STD	
PTYXF	R0130P72		SOLINE- ER3 E10	0	.003	0.20		GASOLINE- LEV3 E10		•	*	*	*	0.012	21	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PTYXR0130P72	PTYXR0130P72-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	COROLLA	PC	2.0	SCV10	PTYXR0130P72	1	F
TOYOTA	COROLLA HATCHBACK	PC	2.0	SCV10	PTYXR0130P72	1	F
TOYOTA	COROLLA HATCHBACK XSE	PC	2.0	SCV10	PTYXR0130P72	1	F