

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFOR	MATION						
MODE YEA		TEST GROUP			VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE			
202:	з і	PNSXV03	. 0PXA		PC				-	SINGLE FUEL HICLE		GASOLINE			
	USEFL	UL LIFE (	miles)		VEHICLE EMISSION				GORY	INTERIM / IN	NTERMEDIATE IN-USE STD				
EXI	H/ORVE	R	EVAP			FTP		SF	TP	FTP		SFTP			
1	50000		150000		LEV3	ULEV70	LEV	3 C	OMPOSITE	*		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L		OBD S	TATUS	EN	NGINE DISPLACEMENT (L)			
1	2TWC(2), 2HO2S, 2WR-HO2S, DFI, 2CAC, 2TC								FULL	*					
*	*								ARTIAL	ALL MODELS	ODELS 3.0				
*	*								TIAL WITH	*	]				
			EV	APOR	ATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL						
EVA	AP / OR	RVR FAM	ILY	EVAP	ORATIVE	E STD CATE	GOR	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES				
	PNSXR	0159MCC		LEV	и з орті	ON2 WITH 1	FEL		PC			*			
					E	EMISSION CI	REDI	r info	ORMATION						
		NOX FLEE	ENDED	١		EDIT FOR N ZERO-EVAP	ON-P	ZEV NMOG CREDIT FOR DOR				OPTIONAL EXH. STD FOR WORK TRUCKS			
		N				N				N		N			
					NMOG	AND FLEET	AVE	RAG	E INFORMA	TION					
NMOG RAF	CH4 RAF		TP G/NMHC Atio	HCHO/NMHC RATIO MMOG+NOX FL PC+LDT (0-375 (g/mi)											
*	*	1	.10		*	0	.044			0.047		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>//t/c</u> day of February 2022.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

#### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

	NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
*	*	*	*	*	*	*	*	*	*	*
GASOLINE- LEV3 E10 PREM	0.025	0.070	0.3	1.7	*	*	*	4	0.001	0.003
GASOLINE- LEV3 E10 PREM	0.038	0.140	0.3	1.7	*	*	*	16		
	GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10	(g/) CERT * * GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10 0.038	(g/mi)   CERT STD   * *   GASOLINE- LEV3 E10 0.025 0.070   PREM 0.038 0.140	(g/mi) (g/mi)   CERT STD CERT   * * * *   GASOLINE- LEV3 E10 0.025 0.070 0.3   PREM 0.038 0.140 0.3	(g/mi) (g/mi)   CERT STD CERT STD   * * * * *   GASOLINE- LEV3 E10 0.025 0.070 0.3 1.7   GASOLINE- LEV3 E10 0.038 0.140 0.3 1.7	(g/mi) (g/mi) (g/mi) (g/mi)   CERT STD CERT STD CERT   * * * * * *   GASOLINE- LEV3 E10 0.025 0.070 0.3 1.7 *   GASOLINE- LEV3 E10 0.038 0.140 0.3 1.7 *	(g/mi) (g/mi) (g/mi)   CERT STD CERT STD CERT STD   * * * * * * *   GASOLINE- LEV3 E10 0.025 0.070 0.3 1.7 * *   GASOLINE- LEV3 E10 0.038 0.140 0.3 1.7 * *	(g/mi) (g/mi) (g/mi) (g/mi) (mg   CERT STD CERT STD CERT STD CERT CERT STD STD CERT STD CERT STD STD STD STD CERT STD	(g/mi) (g/mi) (g/mi) (mg/mi)   CERT STD   *	(g/mi) (g/mi) (g/mi) (mg/mi) (g/mi)

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (	g/mi)
	FOELTIFE	CERT	STD	CERT	STD
HWFET @ 50K	*	*	*		
HWFET @ UL	GASOLINE-LEV3 E10 PREM	0.029	0.070		
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			0.7	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SF	IP EXHAUSI	EMISSION	SIAND	ARDS A	AND CERTIFIC	ATION L	EVEL	5		
					US06			SC03	3		COM	IPOSITE	
	FUEL TYP	ΡE		NMOG+NOx (g/mi)	CO (g/mi)	-	PM g/mi)	NMOG+NOx (g/mi)	CO (g/mi)		OG+NOx g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*		CERT	*	*			*	*				
			STD	*	*			*	*				
	GASOLINE- UL LEV3 E10 PREM		CERT	*	*	:	3	*	*	0	0.048	0.3	*
@ UL			STD	*	*		6	*	*	0.063		4.2	*
			BIN							0	.090		
		WHC	OLE VE	HICLE EVAP	ORATIVE E	MISSION	N STANI	DARDS AND (	CERTIFIC	ΑΤΙΟΙ	N LEVELS	;	
					WHOLE	VEHICLE	EVAPC	DRATIVE TES	TING				
	EVAPORATIVE FAMILY F		JEL TY	PE 3DH	DHS (g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UL		UL
				CERT	STD	FEL	CER	T STD	FEI	EL CERT			STD
PNSXR0159MCC		-	ASOLIN EV3 E PREM		0.300	0.300	0.21	.1 0.300	0.30	00 0.000			0.05



NISSAN MOTOR COMPANY, LTD.

1													
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g	FUEL TYPE					RIG TEST est) @ UL	BLEED CANISTER TEST (g/test) @ 4K					
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
PNSXR0159MCC	GASOLINE- TIER3 E10 PREM	0.04	0.20	GASOLINE- LEV3 E10 PREM		*	*	*	*	0.010	0.020		
I	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE	LEAK FAMILY				CE	RT		STD					
PNSXR0159	MCC	PNSXR0	159MCC	-001		ł	۲		0.02				

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	Z	PC	3.0	M6, SA9	PNSXR0159MCC	1	P