

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFOR	MATION					
MODI YEA		TEST	GROUP		VEHIC	LE CLASS(E	S)		FUEL (CATEGORY		FUEL TYPE		
202	3 1	PNSXV	703.0NHA			PC			-	SINGLE FUEL HICLE		GASOLINE		
	USEF	UL LIF	E (miles)		VEF	IICLE EMISS	ION (CATE	GORY	INTERIM / IN	INTERIM / INTERMEDIATE IN-USE STI			
EXH/ORVR EVAP						FTP		SF	ТР	FTP		SFTP		
1	50000		150000		LEV3	ULEV125	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	E	ENGINE DISPLACEMENT (L)			
1	2TWC(2), 2HO2S, 2WR-HO2S, DFI, 2CAC, 2TC								FULL	*				
*	*							F	PARTIAL	TIAL ALL MODELS		3.0		
*	*							PAF	TIAL WITH	*		1		
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	AP / OF	RVR F	AMILY	EVAF	PORATIVE	E STD CATE	GOR	(SSION STD E CLASS	S	SPECIAL FEATURES		
	PNSXR	0159M	1CB	LE	V 3 OPTI	ON2 WITH 1	FEL]	2C		*		
					I	EMISSION CI	REDI	T INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG C	REDIT FOR DOI	ર	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N		N		
					NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF		CH4 RAF RATIO FTP NMOG/NMHC RATIO HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-37 (g/mi)					0-375		V) LDT	+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*		1.10		*	0	.040			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-015-0918 dated March 17, 2022.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>17th</u> day of January 2023.

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	6+NOx mi)	-	O mi)		Ox mi)	HCI (mg/	-		PM J/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	< *		*	*	*	*	*	*	*	*	*	*	
FTP@UL	LE	SOLINE- V3 E10 PREM	0.046	0.125	0.5	2.1	*	*	*	4	0.001	0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
							NN	/IOG+NC	Ox (g/mi)		CO (g/mi)		
	FUEL TYPE						CE	RT	STD	CER	Т	STD	
HWFET @ 50K				*			*	r	*				
HWFET @ UL			GASOLINE-LEV3 E10 PREM 0)18	0.125				
20°F @	50K	COLD (CO E10 PF	REMIUM GA	ASOLINE	(TIER3)					5	10.0	
			SFTP EXH	IAUST EM	ISSION ST	TANDARD	S AND CE	ERTIFIC	ATION LEVE	LS			
1													

						US06				SC03			CO	MPOSITE		
	FUEL TY	PE		lOG+N (g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+ (g/m		CO (g/mi)	PM (mg/mi)	
@ 4K	*	CERT	*			*				*	*					
0		STD		*		*				*	*					
		CERT		*		*				*	*	0.00	51	0.6	*	
@ UL	GASOLIN LEV3 E1 PREM	_	*			*		5		*	*	0.063		4.2	*	
		BIN										0.11	LO			
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
					W	HOLE \	/EHICLE	EVAP	ORA	TIVE TEST	ING					
	ORATIVE	FUEL TY	FUEL TYPE		Ξ 3DHS (g		g/test) @ UL		2DHS (g/test) @		@ UL		RL (g/mi) @ U) UL	
				CER	श्म ः	STD	FEL	CEF	RT	STD	FEL		CER	т	STD	
PNSXF	R0159MCB	GASOLII LEV3 E PREM	10	0.23	33 0	. 300	0.300	0.2	11	0.300	0.30	0	0.000		0.05	
C	ORVR / FUB	EL ONLY /	CANI	STER	BLEED) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIF	ICAT	ION LEV	ELS	
								FU	JEL C	ONLY EVA	P & CANI	STER BL	EED			
	ORATIVE AMILY	ORVR	g/gal	llon) @	0 UL	FUE	L TYPE			IG TEST) @ UL		RIG TES st) @ UL			ANISTER est) @ 4K	
		FUEL TYP	PE C	ERT	STD			CE	RT	STD	CERT	STD)	CERT	STD	
PNSXF	R0159MCB	GASOLINE TIER3 E1		0.01	0.20		OLINE- 73 E10	*		*	*	*		0.014	0.020	

PREM

PREM



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PNSXR0159MCB	PNSXR0159MCB-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
INFINITI	Q50	PC	3.0	SA7	PNSXR0159MCB	1	P
INFINITI	Q50 AWD	PC	3.0	SA7	PNSXR0159MCB	1	P
INFINITI	Q50 AWD RED SPORT	PC	3.0	SA7	PNSXR0159MCB	1	P
INFINITI	Q50 RED SPORT	PC	3.0	SA7	PNSXR0159MCB	1	P