

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFOR	MATION					
MODE		TEST GRO	UP		VEHICLE CLASS(ES)					ATEGORY		FUEL TYPE		
2023 PNSXV02.0AVA						PC DEDICATED SING VEHICLE					GASOLINE			
	USEFU	JL LIFE (mi	les)		VEH	HICLE EMISSION CATEGORY INTERIM / INTERMEDIATE I					IEDIATE IN-USE STD			
EXI	I/ORVF	ξ Ε	VAP			FTP		SF	ТР	FTP		SFTP		
1!	50000	15	50000		LEV3	ULEV50	LEV	3 C	MPOSITE	*		PM		
SPE	ECIAL F	EATURES	& EXH SYST			ON CONTRO	L		OBD S	TATUS	EN	ENGINE DISPLACEMENT		
1	TWC(2), HO2S, WR-HO2S, SFI, DFI, CAC, TC								FULL	ALL MODELS				
*				*				P	ARTIAL	*		2.0		
*	* *								TIAL WITH *					
			EV	APOF	RATIVE &	REFUELING	(EVA	AP/OR	VR) FAMIL	(INFORMATION				
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR									SSION STD E CLASS	PECIAL FEATURES			
	PNSXRO	119PCA		LE	V 3 OPTI	ON2 WITH 1	FEL		I	PC *				
					E	EMISSION CI	REDI	T INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N N				
					NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF					0-375					D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.1	0		*	0	.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>15th</u> day of August 2022.

Jolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				G+NOx mi)		O mi)		Ox mi)	HC (mg	-	(PM g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL		SOLINE- V3 E10	0.027	0.050	0.1	1.7	*	*	*	4	0.001	0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
							NN	IOG+N	Ox (g/mi)		CO (g/mi)		
FUEL TYPE						CE	RT	STD	CER	Т	STD		
HWFET @ 50K						*		*					
HWFET @ UL			GASO	LINE-LEV	'3 E10		0.0	07	0.050				
20°F @	50K	COLD	CO E10 RE	EGULAR G	ASOLINE	(TIER3)				0.8		10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFTF	P EXHAL	JST EN	IISSION	I STAND	ARDS	AND	CERTIFIC	ATION LE	VELS			
						US06				SC03		С	OMPO	SITE	
	FUEL TYPE		N	NMOG+NOx (g/mi)		CO PM (g/mi) (mg/			i) (g/mi)		CO (g/mi)	NMOG+NO (g/mi)		CO /mi)	PM (mg/mi)
@ 4K	*	CEF	т	*		*				*	*				
-		ST	2	*		*				*	*				
		CEF	۲T.	*		*		1	*		*	0.025	0	.2	*
@ UL	GASOLIN LEV3 E1	SID		*		*	* 6		*		*	0.063	4	.2	*
		BI	1									0.090			
		WHOLE	VEHI	CLE EV	APOR/	ATIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVI	ELS		
					W	HOLE \	/EHICLE	EVAP	ORA	FIVE TEST	ING				
	ORATIVE			: 3	3DHS (g/		(g/test) @ UL		2DHS (g/test)		@ UL		RL (g/mi) @ UI		UL
					CERT S		FEL	CEF	RL	STD	FEL	CE	RT	STD	
PNSXR0119PCA		GASOI LEV3		0.2	22 0	.300	0.300	0.2	30	0.300	0.300	0.0	000	0 0.05	
C	DRVR / FUR	EL ONLY	′ / CA	NISTER	BLEEI) EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFIC	ATION	LEVE	LS
								FU	IEL C	ONLY EVA	P & CANIS	STER BLEE	ED		
	ORATIVE MILY	ORV	ORVR (g/gallon) @ UL		FUE	FUEL TYPE		3DHS RIG TEST (g/test) @ UL			RIG TEST t) @ UL			D CANISTER (g/test) @ 4K	
		FUEL T	YPE	CERT	STD			CE	RT	STD	CERT	STD	CER	T	STD
PNSXF	R0119PCA	GASOLI TIER3		0.05	0.20		OLINE- 73 E10	*		*	*	*	0.00	0.007 0	



L											
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)											
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD								
PNSXR0119PCA PNSXR0119PCA-001 * 0.02											
*: not applicable: #: pounds: l	; not applicable; #: pounds; UL; useful life; PC; passenger car; LDT; light-duty truck; LDT1; LDT<6000#GVWR.0-3750#LVW; LDT2;										

LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	ALTIMA SR	PC	2.0	SCV8	PNSXR0119PCA	1	F