

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODI YEA		TEST GROUP	VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE				
202	2023 PHYXT03.5TT5 LDT3							DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFU	L LIFE (miles)		VEF	ICLE EMISS	ION (CATE	GORY	INTERIM / INTERMEDIATE IN-USE S				
EX	H/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP		
1	50000	150000)	LEV3	ULEV70	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION (SYSTEMS						L		OBD S	TATUS	E	ENGINE DISPLACEMENT (L)		
1	DFI, SFI, 2WR-HO2S, 2HO2S, 2TWC, 2TC, CAC							FULL	ALL MODELS				
*	* *							ARTIAL *			3.5		
*			*				PAF	TIAL WITH *					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATURES												
	PHYXR0	162TTG		LEV 3	OPTION2			LDT3			HCT		
				I	EMISSION CI	REDI	T INFO	ORMATION					
	REDIT F	OX FLEET AVE. OR EXTENDED RRANTY		EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N				N		N		
				NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF					0-375					D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.044	1		0.047 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\frac{9th}{2}$ day of March 2022.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	i+NOx mi)	-	O mi)		Ox mi)		CHO g/mi)		PM g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	L GASOLINE- TIER3 E10		0.038	0.070	0.3	1.7	*	*	*	4	0.002	0.003	
50°F @4K	GASOLINE- TIER3 E10		0.033	0.140	0.2	1.7	*	*	*	16			
								IOG+N	Ox (g/mi)		CO (g/mi)		
	FUEL TYPE					CE	RT	STD	CER	T	STD		
HWFET @ 50P				*			*	,	*				
HWFET @ UL 20°F @ 50K		JL GASOLINE-TIER3 E10						14	0.070				
		COLD (CO E10 RE	GULAR G	SOLINE	(TIER3)				0.4	1	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		031 5	1113310	N STANDA	ARDS A		CERTIFIC		VELO			
						US06				SC03		CC	OMPOSITE		
	FUEL TY	PE		NMOG+I (g/mi		CO (g/mi	Pl) (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/mi)	PM (mg/mi)	
@ 4K	*		CERT	*		*				*	*				
•			STD	*		*				*	*				
		C	CERT	*		*	3	3		*	*	0.034	0.5	*	
@ UL	GASOLIN TIER3 E		STD	*		*	e	5		*	*	0.063	4.2	*	
			BIN									0.070			
		ωно	DLE VEH	ICLE EV	APOR	ATIVE	EMISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS		
						VHOLE	VEHICLE	EVAPO	PORATIVE TESTING						
	ORATIVE	FU	EL TYP	E :	BDHS	(g/test)	@ UL		2DH	IS (g/test)	@ UL	F	RL (g/mi) @	≬UL	
				CE	RT	STD	FEL	CER	T	STD	FEL	CEI	RT	STD	
PHYXF	R0162TTG		SOLINE EV3 E10	0 1	98	0.500	*	0.18	35	0.500	*	0.0	00	0.05	
(ORVR / FU	EL ON	NLY / CA	NISTER	BLEE	D EVA	PORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LEV	ELS	
								FU	EL C	ONLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE	0	RVR (g/	gallon) (@ UL	FU	EL TYPE	-	-	IG TEST) @ UL	-	RIG TEST t) @ UL		ANISTER est) @ 4K	
		FUE	L TYPE	CERT	STE)		CEF	RT	STD	CERT	STD	CERT	STD	
PHYXE	R0162TTG		OLINE- R3 E10	0.13	0.2)	SOLINE- V3 E10	*		*	*	*	0.002	0.020	



A									
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PHYXR0162TTG	PHYXR0162TTG-JX1	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

Î	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
	GENESIS	GV80 AWD	LDT3	3.5	SA8	PHYXR0162TTG	1	F