

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE YEAI		EST GROUP		VEHIC	LE CLASS(E	S)	FUEL CATEGOR			FUEL TYPE			
2023	B PH	IYXT02.5MP5			T.DT2				SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION							CATE	TEGORY INTERIM / INTERMEDIATE IN-USE S					
EXH	I/ORVR	EVAP			FTP		SFTP FTP			SFTP			
150000 150000				LEV3	ULEV70	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	E	ENGINE DISPLACEMENT		
1	1 DFI, SFI, WR-HO2S, HO2S, TWC, TC, CAC							FULL	ALL MODELS				
*	*							PARTIAL	*		2.5		
*						PAF	RTIAL WITH FINES	*					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	PHYXR01	44MPG		LEV 3	OPTION2			LDT2			HCT		
				I	EMISSION CI	REDI	T INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N	N			
				NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF					0-375	-						
*	*	1.10		*	0	.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>26th</u> day of April 2022.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		-	O mi)		Ox mi)		HCHO (mg/mi)		PM (g/mi)
			CERT	STD	CERT STD CI		CERT	STD	CERT	STD	CER	T STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.045	0.070	0.5	1.7	*	*	*	4	0.00	2 0.003
50°F @4K	GASOLINE- TIER3 E10		0.030	0.140	0.2	1.7	*	*	*	16		
					E		NN	NMOG+NOx (g/mi)			CO (g/	'mi)
		FUEL TYPE						RT	STD	CER	Т	STD
HWFET @ 50K		*					*	•	*			
HWFET @ UL		L GASOLINE-TIER3 E10						20	0.070			
20°F @ 50K		COLD (	CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.5	5	12.5

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		031 6	100	1 STANDA	ARDS F	AND	CERTIFIC		VELS		
					US06					SC03		CC	OMPOSITE	
	FUEL TY	PE		NMOG+l (g/mi		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/mi)	PM (mg/mi)
@ 4K	*		CERT	*		*				*	*			
•			STD	*		*				*	*			
		(	CERT	*		*	2	2		*	*	0.040	0.5	*
@ UL	@ UL GASOLINE- TIER3 E10				*		* 6		ł.		*	0.063	4.2	*
			BIN									0.070		
		ωно	DLE VEH	ICLE EV	APOR	ATIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS	
WHOLE VEHICLE EVAPORATIVE TESTING														
	ORATIVE AMILY			E	BDHS (	(g/test) @ UL			2DHS (g/test) @		@ UL	F	RL (g/mi) @	) UL
					CERT		FEL	CER	Т	STD	FEL	CEI	RT	STD
PHYXF	R0144MPG		SOLINE EV3 E10	0 2	47 (	0.400	*	0.23	35	0.400	*	0.0	00	0.05
(	ORVR / FUI	EL OI	NLY / CA	NISTEF	BLEE	D EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LEV	ELS
								FU	EL C	ONLY EVA	P & CANIS	TER BLEE	D	
	ORATIVE AMILY	0	)RVR (g/	gallon) (	@ UL	FUE	L TYPE	_	-	IG TEST ) @ UL	-	tig test t) @ UL	BLEED C TEST (g/t	ANISTER est) @ 4K
		FUE	L TYPE	CERT	STD			CEF	RT	STD	CERT	STD	CERT	STD
PHYXE	R0144MPG		OLINE- R3 E10	0.01	0.20		OLINE- 73 E10	*		*	*	*	0.010	0.020



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PHYXR0144MPG	PHYXR0144MPG-TM1	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HYUNDAI	SANTA FE AWD	LDT2	2.5	AMS8	PHYXR0144MPG	1	F
HYUNDAI	SANTA FE FWD	LDT2	2.5	AMS8	PHYXR0144MPG	1	F