

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	DUP II	NFORM	ATION					
MODE YEAR		EST GROUP	VEHICLE CLASS(ES				FUEL CATEGORY				FUEL TYPE		
2023	PV	VXJ02.0U70		LDT2, LDT3, PC				HYBRID ELECTRIC VEHICLE			GASOLINE		
USEFUL LIFE (miles) VEHICLE EMI							EMISSION CATEGORY INTERIM / IN			TERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP			SFT	ГР	FTP		SFTP		
15	150000 150000			LEV3	LEV3 ULEV70 LEV			3 COMPOSITE *		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT (L)		
1 DFI, TC, CAC, 2HO2S, WR-HO2S, TWC								FULL	*	*			
*	*							ARTIAL	*		2.0		
*	*							FIAL WITH	ALL MODELS				
I		E	VAPC	ORATIVE &	REFUELING	(EVA	P/OR	R) FAMIL	(INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	(EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
PVVXR0107E63 LEV 3 OPTIC						PTION2 PC					*		
E	vvxr01	07E64		LEV 3 OPTION2				LDT2			*		
E	vvxr01	42E50		LEV 3	LEV 3 OPTION2			LDT3			*		
E	vvxr01	42E53	LEV 3 OPTION2				PC			*			
E	vvxr01	42E54		LEV 3 OPTION2				LDT2			*		
				I	EMISSION C	REDI	T INFO	RMATION					
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	EV NMOG CREDIT FOR DOP			R OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N			N		
				NMOG	AND FLEE		RAGE	INFORMA	TION				
NMOG RAF	NMOG/NMHC			-	NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)						NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.044		0.047			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED: The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have three deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$25 per vehicle for the third deficiency for vehicles listed in the test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2023 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$42,450 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 28^{μ} day of July 2022.

John Schi for

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

CERT

STD

BIN

GASOLINE-

LEV3 E10

PREM

@ UL

*

*

*

*

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

					NMOG+NOx CO (g/mi) (g/mi)				NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)			
				CERT	STD	CERT	STD	CERT	STD	CER	Т	STD	CERT	•	STD	
FTP@50	ĸ	*		*	*	*	*	*	*	*		*	*		*	
FTP@U	GASOLINE- JL LEV3 E10 PREM			0.0312	0.070	0.61	1.7	*	*	* *		4 0.00		5	0.003	
50°F @4	K LE	SOLIN V3 E1 PREM		0.0206	0.140	0.45	1.7	*	*	*		16				
FUEL TYPE						NN	NMOG+NOx (g/mi)			CO (g/mi)						
				FUELTIFE				CE	CERT STD			CERT		STD		
HWFET	HWFET @ 50K			*					r -	*						
HWFET	Г@UL			GASOLINE-LEV3 E10 PREM					0.0185 0.070)					
20°F @	@ 50K		GAS	ASOLINE-COLD CO LOW OCTANE								0.71		10.0		
			S	FTP EXH	AUST E	MISSION S	TANDARDS	AND CE	RTIFIC	CATION LE	EVEI	S				
						US06			SC03			COMPOSI			ITE	
	FUEL 1	FUEL TYPE		NMOG (g/I		CO (g/mi)	PM (mg/mi)	NMOG (g/r	-	CO (g/mi)		IOG+NOx (g/mi)	CC (g/m		PM (mg/mi)	
@ 4K	*		CERT	*	r	*		*	·	*						
		S		k k	,	*		*	,	*						

1.5

6

*

*

*

*

0.033

0.063

0.070

0.76

4.2

*

*



	WHOLE VEH		APOR	ATIVE E	MISSION	I STANDAR	RDS AND C	ERTIFIC	CATIO	N LEVE	ELS			
			WHOLE VEHICLE EVAPORATIVE TESTING											
EVAPORATIVE FAMILY	FUEL TYP			S (g/test) @ U		2DHS (g/test) @ UL				RL (g/mi) @ UL				
			CERT S		FEL	CERT	STD	FE	L	CE	RT	STD		
PVVXR0107E63	GASOLINE LEV3 E10 PREM		0.2172 0.		*	0.1598	0.300	*		0.0	001	0.05		
PVVXR0107E64	GASOLINE LEV3 E10 PREM	10 0.2172		.400	*	0.1598	0.400	*		0.001		0.05		
PVVXR0142E50	GASOLINE LEV3 E10 PREM		0.1726 0.		*	0.1804	0.500	*	*		001	0.05		
PVVXR0142E53	GASOLINE LEV3 E10 PREM		26 0	.300	*	0.1804	0.300	*	*		001	0.05		
PVVXR0142E54	GASOLINE LEV3 E10 PREM		26 0	.400	*	0.1804	0.400	*		0.001		0.05		
ORVR / FU	EL ONLY / CA	NISTER	BLEE) EVAP	ORATIVE	EEMISSION	N STANDAF	RDS AN	D CEF	RTIFIC	ATION LI	EVELS		
						FUEL (ONLY EVAP	P & CAN	IISTEF	R BLEE	ED			
EVAPORATIVE FAMILY	ORVR (g/	gallon) @	lon) @ UL		L TYPE	3DHS RIG TEST (g/test) @ UL		-	2DHS RIG T (g/test) @		-			
	FUEL TYPE	CERT S				CERT	STD	CERI	г :	STD	CERT	STD		
PVVXR0107E63	GASOLINE- TIER3 E10 PREM	0.052	0.052 0.20 LEV		OLINE- 73 E10 PREM	*	*	*		*	0.010	4 0.020		
PVVXR0107E64	GASOLINE- TIER3 E10 PREM	0.052	0.20	GASOLINE- LEV3 E10 PREM		*	*	*		*	0.010	4 0.020		
PVVXR0142E50	GASOLINE- TIER3 E10 PREM	0.004	GASOLI 0.004 0.20 LEV3		OLINE- 73 E10 PREM	*	*	*		*	0.009	9 0.020		
PVVXR0142E53	GASOLINE- TIER3 E10 PREM	0.004	0.20	LEV	OLINE- 73 E10 PREM	*	*	*		*	0.009	9 0.020		
PVVXR0142E54	GASOLINE- TIER3 E10 PREM	0.004	0.20	LEV	OLINE- 73 E10 PREM	*	*	*		* 0.0099		9 0.020		
	EFFECTIVE	LEAK D	IAME	TER ST	ANDAR	D AND CE	ERTIFICAT	FION LI	EVEL	(INCH	IES)			
EVAPORATIVE FAMILY LEAK FAMILY						CERT					STD			
PVVXR0142E53		PVVXR0	PVVXR0142E53-001			*				0.02				
PVVXR0142	E54	PVVXR0	2VVXR0142E54-001			*				0.02				
PVVXR0142	E50	PVVXR0	VVXR0142E50-001			*				0.02				
PVVXR0107	E63	PVVXR0	VVXR0107E63-001			*				0.02				
PVVXR0107	'E64	PVVXR0	107E6	4-001		•	*		0.02					

CALIFORNIA AIR RESOURCES BOARD

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR;3751-5750#LVW; LDT3: LDT 6001-8500#GVWR;3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR;5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
VOLVO	S60 B5	PC	2.0	SA8	PVVXR0142E53	1	\$
VOLVO	S60 B5 AWD	PC	2.0	SA8	PVVXR0142E53	1	\$
VOLVO	V60CC B5 AWD	LDT2	2.0	SA8	PVVXR0142E54	1	\$
VOLVO	XC40 B4	PC	2.0	SA8	PVVXR0107E63	1	\$
VOLVO	XC40 B4 AWD	LDT2	2.0	SA8	PVVXR0107E64	1	\$
VOLVO	XC40 B5 AWD	LDT2	2.0	SA8	PVVXR0107E64	1	\$
VOLVO	XC60 B5	PC	2.0	SA8	PVVXR0142E53	1	\$
VOLVO	XC60 B5 AWD	LDT2	2.0	SA8	PVVXR0142E54	1	\$
VOLVO	XC90 B5 AWD	LDT3	2.0	SA8	PVVXR0142E50	1	\$