

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRC	UP II	NFOR	MATION					
MODI YEA	TEST (ST GROUP		TEST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE
202	2023 PMA		XJ03.0DFI		LDT3, PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USE	FUL	LIFE (miles)		VEH	IICLE EMISS	ION (CATE	GORY	INTERIM / IN	TERM	IEDIATE IN-USE STD		
EX	H/OR	VR	EVAP			FTP		SF	TP	FTP		SFTP		
1	50000	0	15000)	LEV3	ULEV125	LEV	3 CC	MPOSITE	*		PM		
SPI	ECIAL	L FEA	ATURES & EX			ON CONTRO	L		OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	DFI,	, 2T	C, 2CAC, 21	R-HO	2S, 2TWC	, 2H02S, G	PF		FULL	ALL MODELS				
*				*				Р	ARTIAL	AL *		3.0		
*				*				PAR	TIAL WITH	*				
			E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATION				
EV	AP / O	ORVR	RFAMILY	EVA	PORATIVE	E STD CATE	GORY	(SSION STD E CLASS	SF	PECIAL FEATURES		
	PMAX	R015	60161		LEV 3 OPTION2				PC			*		
					E	EMISSION CI	REDI	T INFO	ORMATION					
	REDIT	r fof	(FLEET AVE. R EXTENDED RANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		1	N			N				N		N		
					NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH RA		FTP NMOG/NMHO RATIO		HO/NMHC RATIO	NMOG+NOX FLE PC+LDT (0-3750 (g/mi)						MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	,	1.04		*	0	.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 22^{n} day of July 2022.

John Schi for

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM	0.106	0.125	0.9	2.1	*	*	2	4	0.001	0.003
50°F @4K	GASOLINE- LEV3 E10 PREM	0.071	0.250	0.4	2.1	*	*	1	16		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)
	FUEL TIPE	CERT	STD	CERT	STD
HWFET @ 50K	*	*	*		
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.017	0.125		
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			1.0	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SF	TP EXHAUST	EMISSION	STAND	ARDS A	ND CERTIFIC	ATION LI	EVELS			
					US06			SC03		CON	COMPOSITE		
	FUEL TYP	ΡE		NMOG+NOx	CO	Р	M N	MOG+NOx	со	NMOG+NOx	со	РМ	
				(g/mi)	(g/mi)	(mg	J/mi)	(g/mi)	(g/mi)	(g/mi)	(g/mi)	(mg/mi)	
@ 4K	*	С	ERT	*	* *			* *					
-		S	STD	*	*			*	*				
			ERT	*	*	:	1	*	*	0.126	1.0	*	
@ UL	GASOLINI TIER3 E: PREM		STD	*	*	,	6	*	*	0.063	4.2	*	
		E	BIN							0.150			
		WHOL	LE VE	HICLE EVAP	ORATIVE E	MISSION	STAND	ARDS AND C	CERTIFIC	ATION LEVEL	S		
					WHOLE \	/EHICLE	EVAPO	RATIVE TEST	ING				
	ORATIVE			PE 3DH	S (g/test) @) UL	:	2DHS (g/test)	@ UL	RL	RL (g/mi) @ UL		
				CERT	STD	FEL	CERT	STD	FEI	_ CER1	г	STD	
PMAXF	80150161	TIE	SOLIN ER3 E PREM		0.300	*	0.266	6 0.300	*	0.01		0.05	



MASERATI S.P.A.

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
				FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g	FUEL TYPE			IG TEST) @ UL	_	RIG TEST st) @ UL	BLEED CANISTER TEST (g/test) @ 4M						
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD			
PMAXR0150161	GASOLINE- TIER3 E10 PREM	0.04	0.20	GASOLINE- TIER3 E10 PREM		*	*	*	*	0.008	0.020			
	EFFECTIVE	LEAK D	IAMET	ER STA	NDARI	D AND CE	RTIFICA	TION LE	VEL (INCH	IES)				
EVAPORATIVE FAMILY LEAK F			K FAMII	Y		CERT			STD					
PMAXR0150	PMAXR0	PMAXR0150161-LF1			÷	*		0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MASERATI	GHIBLI GT	PC	3.0	A8	PMAXR0150161	1	F
MASERATI	GHIBLI MODENA AWD	PC	3.0	A8	PMAXR0150161	1	F
MASERATI	GHIBLI MODENA RWD	PC	3.0	A8	PMAXR0150161	1	F
MASERATI	LEVANTE GT	LDT3	3.0	A8	PMAXR0150161	1	F
MASERATI	LEVANTE MODENA	LDT3	3.0	A8	PMAXR0150161	1	F
MASERATI	QUATTROPORTE GT	PC	3.0	A8	PMAXR0150161	1	F
MASERATI	QUATTROPORTE MODENA AWD	PC	3.0	A 8	PMAXR0150161	1	F
MASERATI	QUATTROPORTE MODENA RWD	PC	3.0	A 8	PMAXR0150161	1	F