

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	OUP IN	FOR	MATION					
MODE YEAR				VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2023	PP	RXV04.0S82		PC DED:				-) SINGLE FUEL HICLE	GASOLINE			
	USEFUL	LIFE (miles)		VEF	IICLE EMISS	ION C	ATE	GORY	INTERIM / IN	ITE	ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP		FTP				SFTP FTP			SFTP		
15	0000	150000		LEV3	ULEV70	LEV	3 C	OMPOSITE	*		PM		
SPE	CIAL FE	ATURES & EXI SYS		ON CONTRO	L		OBD S	OBD STATUS		ENGINE DISPLACEMENT (L)			
1		2TWC, MAP, DE	'I,2W	R-H02S,2	2HO2S			FULL	*				
2	2 T W	C, MAP, DFI, 20	IR-HO	2S,2HO2S	,2TC,CAC		P	PARTIAL	SOME MODELS	;	3.7, 4.0		
*	*						PAR	TIAL WITH	SOME MODELS				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	,		SSION STD E CLASS		SPECIAL FEATURES		
F	PRXR01	15R82	LE	V 3 OPTI	3 OPTION2 WITH FEL			PC			*		
F	PPRXR0170R92 LEV 3 OPTION2 W				ON2 WITH	TH FEL PC			PC		*		
				I	EMISSION CI	REDIT	INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	EV NMOG CREDIT FOR DOP			R OPTIONAL EXH. STD FOR WORK TRUCKS		
N N									N		N		
				NMOG	AND FLEET		RAG		TION				
NMOG RAF						0-375							
*	*	1.10		*	0	.044			0.047		*		
Cas th			I. N.4.	alala Eur				Diamla .		- (Control Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicle models 718 Boxster GTS 4.0 and 718 Cayman GTS have been determined to have three (3) deficiencies, and the vehicle models, 911 Turbo, 911 Turbo Cabriolet, 911 Turbo S and 911 Turbo S Cabriolet have been determined to have four (4) deficiencies. The listed vehicle models with three (3) deficiencies are approved subject to the manufacturer paying a fine of twenty-five dollars (\$25) per vehicle for the third deficiencies are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2023 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$42,450 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-019-0320 dated July 27, 2022.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 2/at day of October 2022.

Jolin U. Lang

Robin U. Lang, Chief *U* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)			CO (g/mi)		NOx (g/mi)		HO mi)	-	
		CERT STD CERT STD		CERT	STD	CERT	STD	CERT	STD			
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM		0.051	0.070	0.4	1.7	*	*	0	4	0.002	0.003
50°F @4K		*	*	*	*	*	*	*	*	*		
					F		NN	IOG+N	Ox (g/mi)	CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CER	CERT	
HWFET @ 50K		*						•	*			
HWFET @ UL			GASOLIN	E-TIER3	E10 PREM	1	0.0	22	0.070			
20°F @ 50K			GASOLIN	E-TIER3	E10 PREM	1				0.8		10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	-												•			
					US06				SC03				COMPOSITE			
	FUEL TYP	PE		NMOG+NOx		CO	Р	PM)G+NOx	СО	NMO	OG+NOx	со	РМ	
				((g/mi)	(g/mi)	(mg	(mg/mi)		g/mi)	(g/mi)	(g/mi)	(g/mi)	(mg/mi)	
@ 4K	4K * C		CERT	*		*			*		*					
			STD	*		*				*	*					
			CERT		*	*	:	2		*	*	0.035		0.4	*	
@ UL	GASOLINE TIER3 E1 PREM	ER3 E10 STD		*		*		6		*	*	0.063		063 4.2		
			BIN	BIN								0.080				
		WH	OLE VE	HICL	E EVAPO	RATIVE E	MISSION	STAN	DAR	DS AND (CERTIFIC	ATIO	N LEVELS	;		
						WHOLE	VEHICLE	EVAPO	ORAT	IVE TEST	ſING					
	EVAPORATIVE FAMILY		FUEL TYPE		3DHS (g/test) @ UL				2DHS (g/test) @ UL				RL (g/mi) @ UL			
					CERT	STD	FEL	CER	T	STD	FEI	L CERT		:	STD	
		-	GASOLINE- TIER3 E10 PREM		0.184	0.300	0.300	0.24	15	0.300	0.30	300 0.00		0.00 0		
		-	GASOLINE- TIER3 E10 PREM		0.242	0.300	0.300	0.23	30	0.300	0.30	0.00		0.00 0.05		



ORVR / FUI	EL ONLY / CA	NISTER	BLEED	EVAPOF	RATIVE	EMISSION	I STANDAI	RDS AN	ID C	CERTIFIC A	ATION LEV	ELS			
		FUEL ONLY EVAP & CANISTER BLEED													
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE		3DHS R (g/test			G TEST @UL	BLEED CANISTER TEST (g/test) @ 4K							
	FUEL TYPE	IEL TYPE CERT S		STD		CERT	STD	CER	Т	STD	CERT	STD			
PPRXR0115R82	GASOLINE- TIER3 E10 PREM	3 E10 0.02 0.20 7		GASOLINE- TIER3 E10 PREM		*	*	*		*	0.008	0.020			
PPRXR0170R92	GASOLINE- TIER3 E10 0.01 0.20 PREM		GASOLINE- TIER3 E10 PREM		*	*	*		*	0.004	0.020				
	EFFECTIVE	LEAK D	IAMET	ER STA	NDARI	D AND CE	RTIFICA	TION L	EV	EL (INCH	ES)				
EVAPORATIVE	Y CERT					STD									
PPRXR0115	-001 *					0.02									
PPRXR0170R92 PPRXR0170R92-					-001 *						0.02				

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
PORSCHE	718 BOXSTER GTS 4.0	PC	4.0	AMS, M6	PPRXR0115R82	1	\$
PORSCHE	718 CAYMAN GT4	PC	4.0	AMS7,M6	PPRXR0115R82	1	P
PORSCHE	718 CAYMAN GTS 4.0	PC	4.0	AMS7,M6	PPRXR0115R82	1	\$
PORSCHE	718 SPYDER	PC	4.0	AMS7,M6	PPRXR0115R82	1	P
PORSCHE	911 SPORT CLASSIC	PC	3.7	м7	PPRXR0170R92	2	P
PORSCHE	911 TURBO	PC	3.7	AMS8	PPRXR0170R92	2	\$
PORSCHE	911 TURBO CABRIOLET	PC	3.7	AMS8	PPRXR0170R92	2	\$
PORSCHE	911 TURBO S	PC	3.7	AMS8	PPRXR0170R92	2	\$
PORSCHE	911 TURBO S CABRIOLET	PC	3.7	AMS8	PPRXR0170R92	2	\$