

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE YEAI		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2023	3 PI	PRXV02.5B82	KV02.5B82 PC						SINGLE FUEL HICLE	GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISS							CATEGORY INTERIM / INTERMEDIATE IN-USE						
EXH	I/ORVR	EVAP			FTP		SF	FTP FTP			SFTP		
15	50000	150000		LEV3	LEV160	LEV 3 COMPOSIT			*		РМ		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	TWC, DFI, 2HO2S, HO2S, TC, CAC							FULL	- *				
*	*							PARTIAL	ALL MODELS		2.0, 2.5		
*			*				PAF	RTIAL WITH FINES					
		E	/APOF	RATIVE &	REFUELING	(EVA	AP/OF	RVR) FAMIL	(INFORMATION				
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						Y	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	PPRXR01	L15R82	LE	V 3 OPTI	ION2 WITH 1	FEL		I	PC *				
				I	EMISSION CI	REDI	T INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	V NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	NMOG/NMHC HCHO/NMHC PC+LDT (0-37							_	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.01	0	.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 27^{th} day of July 2022.

John Schi for

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

PPRXR0115R82

TIER3 E10

PREM

0.02

0.20

TIER3 E10

PREM

0.008

*

0.020

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	-	-	O mi)		Ox HCH mi) (mg/r			-	PM (g/mi)	
			CERT	STD	CERT STD C		CERT	STD	CERT	STD	CERT	STD	
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- L TIER3 E10 PREM		0.110	0.160	0.4	4.2	*	*	0	4	0.001	0.003	
50°F @4K	*		*	*	*	*	*	*	*	*			
								NMOG+NOx (g/mi) CO (g/mi)					
				FUEL TYP	E		CE	RT	STD	CER	T	STD	
HWFET @) 50K			*			*		*				
HWFET @	@ UL	GASOLINE-TIER3 E10 PREM						52	0.160				
20°F @	50K		GASOLIN	E-TIER3	E10 PREM	1				0.8	3	10.0	
			SFTP EXH	AUST EM	ISSION ST		S AND CE		ATION LEVE	LS			

				-	-		-	-			-	-				
					ι	JS06				SC03	3		CON	IPOSITE		
	FUEL TYI	PE		OG+N((g/mi)	Ox	CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+ (g/mi		CO (g/mi)	PM (mg/mi)	
@ 4K	*	CERT	*		* *		*			*	*					
-		STD				*				*	*					
		CERT	*			*	0	0		* *		0.085		0.3	*	
@ UL	GASOLINI TIER3 E PREM	_	*			*		*		*	*	0.063		4.2	*	
												0.12	0			
		WHOLE VE	HICL	E EVA	PORA	TIVE E	MISSION	STAN	IDAR	DS AND C	CERTIFICA	TION LE	VELS	S		
					WHOLE VEHICLE EVAPORATIVE TESTING											
	ORATIVE	FUEL TYPE		30	OHS (g	g/test) @ UL			2DHS (g/test) @ UL			RL (g/m		(g/mi) @	ii) @ UL	
				CER	RT STD		FEL	CE	RT	STD	FEL	EL C		Г	STD	
PPRXR0115R82		GASOLIN TIER3 H PREM		0.18	4 0	.300 0.300		0.2	45	0.300	0.30	0	0.00		0.05	
C	DRVR / FUE	EL ONLY /	CANIS	STER I	BLEED	EVAP	ORATIVE	EMIS	SION	I STANDA		CERTIFI	CATI	ON LEV	ELS	
								FL	JEL C		P & CANIS	STER BL	EED			
EVAPORATIVE FAMILY		ORVR (g/gall	lon) @	UL	FUE	L TYPE		OHS RIG TEST g/test) @ UL			2DHS RIG TEST (g/test) @ UL		BLEED CANIS TEST (g/test) (
		FUEL TYP	EC	ERT	STD			CE	RT	STD	CERT	STD		CERT	STD	
		GASOLINE	-			GAS	OLINE-									

*



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PPRXR0115R82	PPRXR0115R82-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
PORSCHE	718 BOXSTER	PC	2.0	AMS7,M6	PPRXR0115R82	1	Р
PORSCHE	718 BOXSTER S	PC	2.5	AMS7,M6	PPRXR0115R82	1	Р
PORSCHE	718 BOXSTER T	PC	2.0	AMS7,M6	PPRXR0115R82	1	P
PORSCHE	718 CAYMAN	PC	2.0	AMS7,M6	PPRXR0115R82	1	Р
PORSCHE	718 CAYMAN S	PC	2.5	AMS7,M6	PPRXR0115R82	1	P
PORSCHE	718 CAYMAN T	PC	2.0	AMS7,M6	PPRXR0115R82	1	Р