

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFOR	MATION					
MODE YEAI							S)		FUEL C	ATEGORY	FUEL TYPE			
2023	2023 PHNXV01.5LDB PC							DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
USEFUL LIFE (miles) VEHICL							ION (	CATE	GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP						FTP		SF	ТР	FTP	SFTP			
15	50000		150000		LEV3	ULEV50	LEV	3 C	OMPOSITE	*		РМ		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)			
1	L TWC, WR-HO2S, HO2S, DFI, TC, CAC								FULL	*	1			
*	* *							P	ARTIAL	ALL MODELS		1.5		
*	* *								RTIAL WITH *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATURES										PECIAL FEATURES			
1	PHNXRO	01272	ABA		LEV 3	OPTION2			I	PC		*		
					E	EMISSION CI	REDI	r info	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY								NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N		N		
					NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF		FTP MOG/NMHC RATIO		O/NMHC RATIO	HC NMOG+NOX FLE PC+LDT (0-375 (g/mi)						D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*		1.10		0.05	0	.044			0.047 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>27th</u> day of May 2022.

John Schi for

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

	_											
				6+NOx mi)		O mi)	N( (g/	Ox mi)	HC (mg	-	(	PM g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		SOLINE- V3 E10	0.022	0.050	0.4	1.7	*	*	0	4	0.000	0.003
50°F @4K		*	*	*	*	*	*	*	*	*		
					<b></b>		NN	NMOG+NOx (g/mi) CO (g/mi)				ni)
FUEL TYPE						CE	RT	STD	CER	Т	STD	
HWFET @ 50K		*							*			
HWFET @ UL		GASOLINE-LEV3 E10						08	0.050			
20°F @	50K	COLD (	CO E10 RE	EGULAR GA	ASOLINE	(TIER3)				0.4		10.0

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFT	P EXHAI	JST EN	ISSION	STANDA	ARDS A	AND	CERTIFIC	ATION LE	VELS			
						US06				SC03		C	OMPOSI	TE	
	FUEL TYI	PE		NMOG+N (g/mi)		CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)	)x CC (g/n		
@ 4K	*		ERT	*		*			*		*				
		5	STD	*		*				*	*				
		С	ERT	*		*	1	-		*	*	0.017	0.	0.4 *	
@ UL	GASOLIN LEV3 E1		STD	*		*	e	5		*	*	0.063	4.:	2 *	
			BIN									0.080			
		WHO	LE VEH	ICLE EV	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS		
					W	HOLE V	<b>EHICLE</b>	EVAPC	RA	IVE TEST	ING				
	ORATIVE MILY	FUE	EL TYPI	= 3	BDHS (g	/test) @	0 UL		2DH	IS (g/test)	@ UL	F	RL (g/mi)	@ UL	
				CEF	RT :	STD	FEL	CER	Т	STD	FEL	CE	RT	STD	
PHNXR	R0127ABA		SOLINE V3 E10	0 1	74 0	. 300	*	0.15	55	0.300	*	0.	00	0.05	
C	DRVR / FUE	EL ON	NLY / CA	NISTER	BLEED	EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VELS	
								FU	EL C	NLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE MILY	OF	RVR (g/	gallon) (	DUL	FUE	L TYPE			IG TEST ) @ UL		t) @ UL		CANISTER j/test) @ 4K	
		FUEI	L TYPE	CERT	STD			CEF	RL	STD	CERT	STD	CERT	STD	
PHNXR	R0127ABA		DLINE- R3 E10	0.01	0.20		OLINE- 3 E10	*		*	*	*	0.004	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PHNXR0127ABA	PHNXR0127ABA-A00	*	0.02						

': not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HONDA	CIVIC 5DR	PC	1.5	М6	PHNXR0127ABA	1	P