

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFOR	MATION					
MODEL YEAR TEST GROUP					VEHIC	LE CLASS(E	S)		FUEL C	CATEGORY		FUEL TYPE		
202	3 1	PHNXV0	3.0GCC			PC			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFL	UL LIFE	E (miles)		VEH	IICLE EMISS	ION (CATE	GORY	INTERIM / INTERMEDIATE IN-USE ST				
EXH/ORVR EVAP						FTP		SF	тр	FTP		SFTP		
1	50000		150000		LEV3	ULEV70	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUS SYSTEMS						ON CONTRO	L		OBD S	TATUS	E	ENGINE DISPLACEMENT (L)		
1	WU-TWC, TWC, 2WR-HO2S, HO2S, DFI, TC, CAC								FULL	*				
*	* *							F	PARTIAL ALL MODELS			3.0		
*	*							PAF	RTIAL WITH *					
			EV	APOF	RATIVE &	REFUELING	(EVA	AP/OF	RVR) FAMIL		1			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								Y	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	PHNXR	0149AB	BA		LEV 3	OPTION2			PC			*		
					E	EMISSION CI	REDI	T INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N				N				N		N		
					NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	G CH4 RAF		FTP OG/NMHC RATIO	C HCHO/NMHC RATIO NMOG+NOX F PC+LDT (0-37 (g/mi										
*	*		1.10	(0.05	0	.044			0.047 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>/9th</u> day of September 2022.

Polin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

	-			G+NOx mi)		O mi)		Ox mi)	HC (mg	-		PM (g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	T STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		SOLINE- V3 E10	0.041	0.070	0.6	1.7	*	*	1	4	0.00	0 0.003
50°F @4K		*	*	*	*	*	*	*	*	*		
			• •		-	<u>.</u>	NN	IOG+N	Ox (g/mi)		CO (g/	mi)
			FUEL TYPE						STD	CER	Т	STD
HWFET @ 50K		*						,	*			
HWFET @ UL 20°F @ 50K		GASOLINE-LEV3 E10)22	0.070			
		COLD	CO E10 RE	EGULAR G	ASOLINE	(TIER3)				0.5	5	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFT	P EXHAL	JST EN	IISSION	STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS			
						US06				SC03		C	OMPOSIT	E	
	FUEL TYPE		1	NMOG+NOx		CO	P	N	NMC)G+NOx	СО	NMOG+NC	x CO	PM	
				(g/mi)		(g/mi)	(mg	/mi)	(g/mi)	(g/mi)	(g/mi)	(g/m) (mg/mi)	
@ 4K	*	C	ERT	*		*				*	*				
		S	STD	*		*				*	*				
		C	ERT	*		*	1			*	*	0.040	0.8	*	
@ UL	GASOLIN LEV3 E1	S	STD	*		*	e	;		*	*	0.063	4.2	*	
		E	BIN									0.080			
		WHOL	E VEH		APOR/	TIVE E	MISSION	STAN	IDAR	DS AND C	ERTIFICA	TION LEVE	LS		
				WHOLE VEHICLE EVAPORATIVE TESTING											
	ORATIVE AMILY	FUE	EL TYPE	Ξ 3	DHS (g	g/test) @	D UL		2Dł	IS (g/test)	@ UL	F	RL (g/mi) (@ UL	
				CEF	RT	STD	FEL	CEF	RT	STD	FEL	CE	RT	STD	
PHNXF	R0149ABA		OLINE- V3 E10	0 1	78 0	.300	*	0.2	15	0.300	*	0.	00	0.05	
0	ORVR / FUE	EL ONI	LY / CA	NISTER	BLEE) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	/ELS	
								FU	JEL C	NLY EVA	P & CANIS	STER BLEE	D		
	EVAPORATIVE FAMILY		RVR (g/g	g/gallon) @ UL		FUE	FUEL TYPE		3DHS RIG TEST (g/test) @ UL		-	RIG TEST t) @ UL		CANISTER /test) @ 4K	
		FUEL	TYPE	CERT	STD			CE	RT	STD	CERT	STD	CERT	STD	
PHNXF	R0149ABA		LINE- 3 E10	0.01	0.20		OLINE- 3 E10	*	r	*	*	*	0.010	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PHNXR0149ABA	PHNXR0149ABA-E00	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
ACURA	TLX TYPE-S	PC	3.0	SA10	PHNXR0149ABA	1	P