

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP II	NFOR	MATION					
MODE		EST GROUP		VEHIC	VEHICLE CLASS(ES) F				ATEGORY		FUEL TYPE		
2023	B PH	YXT01.6M13			1.072				ELECTRIC HICLE		GASOLINE		
	USEFUL	LIFE (miles)		VEF	IICLE EMISS	ION (CATE	GORY	INTERIM / IN	FERMEDIATE IN-USE STD			
EXI	I/ORVR	EVAP			FTP		SF	TP	FTP		SFTP		
1	50000	150000		LEV3	SULEV30	LEV	3 CC	MPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMENT (L)		
1 DFI, WR-HO2S, HO2S, WU-TWC, TWC, TC, CAC, EGR, EGRC								FULL	ALL MODELS				
*						Р	ARTIAL	*		1.6			
*			*					RTIAL WITH *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	AP / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	/	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	PHYXR01	.37M1G		LEV 3	OPTION2	LDT2)Т2		HCT		
				I	EMISSION CI	REDI	r info	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY										OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET		RAGE		TION				
NM()(÷/NMH(;				IO/NMHC RATIO	NMOG+NO PC+LDT ((g			/) LDT			IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	* * 1.10 * 0.044								0.047 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $5^{\#}$ day of May 2022.

John Schi for

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I		C (g/i	-		Ox mi)		HO /mi)		PM (g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	T STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.025	0.030	0.1	1.0	*	*	*	4	0.00	2 0.003
50°F @4K	GASOLINE- TIER3 E10		0.018	0.060	0.0	1.0	*	*	*	8		
				FUEL TYP	E		NN	IOG+N	Ox (g/mi)		CO (g/	/mi)
			l	FUEL ITP	E		CE	RT	STD	CER	Т	STD
HWFET @ 50P				*		*		*	*			
HWFET @ UL			GASOI	INE-TIEF	R3 E10		0.0	07	0.030			
20°F @ 50K		COLD (CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.5	5	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361				122101	I STANDA	ARDS A		CERTIFIC		VELO			
						ι	JS06				SC03		COMPOSITE			
	FUEL TY	PE)G+N g/mi)		CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi))x CC (g/n	-	PM (mg/mi)
@ 4K	*	* CEF		*		*					*	*				
•		ſ	STD		*		*				*	*				
			CERT		*		*	2	2	*		*	0.018	0.	0.1	
@ UL	GASOLIN TIER3 E		STD		*		*	* 6		*		*	0.063	4.3	2	*
			BIN										0.030			
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
WHOLE VEHICLE EVAPORATIVE TESTING																
	ORATIVE Amily	FUEL TY		E	3DHS (g/		g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @		UL	
				CEF		T S	TD	FEL	CER	CERT STD		FEL	CE	RT	RT ST	
PHYXI	R0137M1G		ASOLINE EV3 E1(0.21	L4 0.	400	*	0.24	42	0.400	*	0.	0.00 0.0		
(orvr / Fui	EL O	NLY / C	ANIS	TER	BLEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VE	LS
									FU	EL C	NLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE	ORVR (g		gallo	on) @) UL				HS RIG TEST g/test) @ UL			lig test) @ UL	BLEED CA TEST (g/te		
		FUE	EL TYPE	CE	RT	STD			CEF	RT	STD	CERT	STD	CERT		STD
PHYXE	R0137M1G		SOLINE- ER3 E10	0.	.03	0.20		OLINE- 73 E10	*		*	*	*	0.008		0.020



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PHYXR0137M1G	PHYXR0137M1G-TMH	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HYUNDAI	SANTA FE HYBRID	LDT2	1.6	AMS6	PHYXR0137M1G	1	F
HYUNDAI	SANTA FE HYBRID BLUE	LDT2	1.6	AMS 6	PHYXR0137M1G	1	F