

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR		IFORI	MATION					
MODE YEAR		EST GROUP		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2023	PH	YXT01.6M2T		LDT2				PLUG-IN HYBRID ELECTRIC VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEHICLE EMISSION CATEGOR				GORY	INTERIM / IN	ITER	ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP			FTP		SF	TP FTP			SFTP		
15	0000	150000		LEV3	SULEV30	LEV	3 CC	MPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						OL		OBD	STATUS	E	ENGINE DISPLACEMENT (L)		
1	DFI, WR-HO2S, HO2S, WU-TWC, TWC, TC, CAC, EGR, EGRC							FULL	ALL MODELS				
*	*								*		1.6		
*	* PARTIAL WITH FINES								l *				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	E STD CATE	EGORY	,		ISSION STD LE CLASS	S	PECIAL FEATURES		
E	PHYXR01	.06M2G		LEV 3	LEV 3 OPTION2			I	DT2		HCT		
				I	EMISSION	CREDIT	INFC	RMATION					
GROUP AVE. CR					REDIT FOR NON-PZI			EDIT FOR V ZERO- AP		FOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
ALL MODELS N							N		N		N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	NIM()(2/NIMH(* D(*+1))) /0_37				(0-3750								
*	*	1.10		*		0.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>16</u>th day of May 2022.

Johna Sahi for

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx CO (g/mi) (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)		
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL	L GASOLINE- TIER3 E10		0.024	0.030	0.1	1.0	*	*	*	4	0.002	2 0.003
50°F @4K		SOLINE- R3 E10	0.020	0.060	0.2	1.0	*	*	*	8		
					F		NN	NMOG+NOx (g/mi)			CO (g/n	ni)
				FUEL TYP	E		CE	RT	STD	CER	Т	STD
HWFET @ 50K			*					r	*			
HWFET @ UL		IL GASOLINE-TIER3 E10					0.0	008	0.030			
20°F @ 50K		COLD (CO E10 RE	GULAR G	ASOLINE	(TIER3)				0.2	2	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

SFIP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS												VELO				
						US06				SC03		COMPOSITE				
	FUEL TY	PE		NMOG+ (g/mi		CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/mi	PM (mg/mi)		
@ 4K	ικ *		CERT	*		*				*	*					
•			STD	*		*	*		*		*					
		(CERT	*		*	2	2	*		*	0.020	0.1	*		
@ UL	GASOLINE- TIER3 E10				STD	*		*	e	5		*	*	0.063	4.2	*
			BIN									0.030				
		ωно	DLE VEH		'APOR	ATIVE E	EMISSION	STAN	IDAR	DS AND C	ERTIFICA	TION LEVE	LS			
					WHOLE VEHICLE EVAPORATIVE TESTING											
	ORATIVE			E	3DHS (HS (g/test) @ UL			2DHS (g/test) @ UL		@ UL	F	RL (g/mi) ((g/mi) @ UL		
				CE	RT	STD	FEL	CEF	RT	STD	FEL	CE	RT	STD		
PHYXR0106M2G		-	SOLINE EV3 E1(102	58	0.400	*	0.1	97	0.400	*	0.0	0.00			
(ORVR / FU	EL OI	NLY / C/	ANISTEF	R BLEE	D EVAF	PORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFICA	TION LEV	'ELS		
								FU	JEL C	ONLY EVA	P & CANIS	TER BLEE	D			
	EVAPORATIVE FAMILY		ORVR (g/ga				-		HS RIG TEST g/test) @ UL		-	t) @ UL	-			
		FUE	L TYPE	CERT	STD			CE	RT	STD	CERT	STD	CERT	STD		
PHYXE	R0106M2G		OLINE- R3 E10	0.09	0.20)	*	*	r	*	*	*	*	*		



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
PHYXR0106M2G	PHYXR0106M2G-TMP	0.00	0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	HYUNDAI	SANTA FE PLUG- IN HYBRID	LDT2	1.6	AMS 6	PHYXR0106M2G	1	F

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL PHEV TYPE		UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV	
NUMBER		(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE
1	TZEV	45.8	46.1	*	40.5	40.7	0.76