

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP II	NFOR	MATION					
MODE YEAI	T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2023	3 PI	IYXV01.6SB5			PC			-	SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMIS							CATE	GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD		
EXI	I/ORVR	EVAP			FTP		SF	TP	FTP		SFTP		
1!	50000	150000		LEV3	ULEV70	LEV	3 C	OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CO SYSTEMS						L		OBD S	TATUS	E	NGINE DISPLACEMENT (L)		
1	SFI, W	R-HO2S, HO2S	, WU-	-TWC, TW	C, EGR, EG	RC		FULL	ALL MODELS				
*			*				F	PARTIAL	*		1.6		
*			*				PAR	TIAL WITH	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								SSION STD E CLASS	S	SPECIAL FEATURES		
	PHYXR0	L20SBG		LEV 3	OPTION2			I	2C		HCT		
		·		I	EMISSION CI	REDI	T INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET		RAG		TION				
NMOG RAF	G CH4 FTP RAF NMOG/NMHC RATIO RATIO (g/mi)				0-375		V) LDT	+NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $22^{\prime\prime}$ day of July 2022.

John Schi for

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	i+NOx mi)	-	O mi)		Ox mi)		:HO J/mi)	(PM g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	950K *		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.036	0.070	0.1	1.7	*	*	*	4	0.000	0.003
50°F @4K		SOLINE- R3 E10	0.081	0.140	0.1	1.7	*	* *		16		
					-		NN	IOG+N	Ox (g/mi)		CO (g/n	ni)
	FUEL TYPE				CE	RT	STD	CER	Т	STD		
HWFET @ 50K				*			*		*			
HWFET @ UL		GASOLINE-TIER3 E10					0.0	21	0.070			
20°F @ 50K										0.6	5	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			3611			133101	ISTANDA			CERTIFIC		VELS		
						US06				SC03		C	OMPOSI	E
	FUEL TY	PE	1	NMOG+N (g/mi)		CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/m	
@ 4K	@4K *		CERT			*			*		*			
•		;	STD	*		*				*	*			
			CERT	*		*	2	2	*		*	0.037	0.1	. *
@ UL	GASOLIN TIER3 E		STD	*		*	e	5		*	*	0.063	4.2	*
			BIN									0.070		
		wно	LE VEHI	CLE EV	APOR/	TIVE E	MISSION	STANE	DAR	DS AND C	ERTIFICA	TION LEVE	LS	
					W	HOLE \	/EHICLE	EVAPO	RA	IVE TEST	ING			
	ORATIVE AMILY	FUEL TYPE		= 3	3DHS (g/		g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @	
				CEF	RT	STD	FEL	CER	Т	STD	FEL	CE	RT	STD
PHYXI	R0120SBG		SOLINE- V3 E10	0.2	13 0	.300	*	0.25	0	0.300	*	0.	0.00 0.0	
(ORVR / FU	EL ON	NLY / CA	NISTER	BLEED) EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VELS
								FUE	EL C	NLY EVA	P & CANIS	TER BLEE	D	
	EVAPORATIVE ORVR FAMILY		RVR (g/ថ្	gallon) (DUL 🗿	FUE	L TYPE			G TEST) @ UL		IG TEST) @ UL		CANISTER /test) @ 4K
		FUE	L TYPE	CERT	STD			CER	RT	STD	CERT	STD	CERT	STD
PHYXE	R0120SBG		OLINE- R3 E10	0.01	0.20		OLINE- 73 E10	*		*	*	*	0.007	0.020



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PHYXR0120SBG	PHYXR0120SBG-QX1	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

M	AKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HYU	UNDAI	VENUE	PC	1.6	M6, SCV1	PHYXR0120SBG	1	F