

Executive Order: A-413-0283

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION												
MODI YEA		EST GROUP	VEHICLE CLASS(ES)			S)		FUEL CATEGORY			FUEL TYPE	
202	2023 PVGAV08.0GLB PC					DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
	USEFUL	LIFE (miles)		VEH	IICLE EMISS	ION C	CATE	GORY	INTERIM / INTERMEDIATE IN-USE			
EX	H/ORVR	EVAP			FTP		SF	TP	FTP		SFTP	
1	50000	150000)	LEV3	LEV160	LEV	3 CC	MPOSITE	*		PM	
SPECIAL FEATURES & EXHAUST EMISSION SYSTEMS					ON CONTRO	L		OBD S	TATUS	EI	NGINE DISPLACEMENT (L)	
SFI, AIR, 4WU-TWC, 2TWC, 4TC, 2CAC, 4WR-HO2S, 4HO2S							FULL	*				
*			*				Р	ARTIAL	ALL MODELS		8.0	
* *							ARTIAL WITH *		1			
		E,	/APOF	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	INFORMATION	١		
EV	AP / ORV	R FAMILY	EVAI	PORATIVE	STD CATE	GORY EVAP EMIS VEHICLE				s	PECIAL FEATURES	
	PVGAR02	200GCB	LE	V 3 OPTI	ON2 WITH I	FEL	PC				*	
		•			EMISSION C	REDIT	INFO	ORMATION	•			
					EDIT FOR NON-PZE\ ZERO-EVAP			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS	
n n					N				N			
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION			
NMOG RAF	NMOG/NMHC PC+111 /0-37/			0-375	60 LVW) LDT (3751		+NOX FLEET S (3751 LVW-8500 R) + MDPV (g/m)	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	* * 1.10 * 0.04					.044		0.047 *			*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-413-0283

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 6th day of October 2022.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Jolin U. Kang

Executive Order: A-413-0283

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP **FUEL TYPE** NMOG+NOx CO NOx **HCHO** PΜ (g/mi) (g/mi) (mg/mi) (g/mi) (g/mi) **CERT STD CERT STD CERT STD CERT** STD **CERT STD** FTP@50K GASOLINE-FTP@UL TIER3 E10 0.145 0.160 0.9 4.2 4 0.001 0.003 PREM 50°F @4K NMOG+NOx (g/mi) CO (g/mi) **FUEL TYPE CERT STD CERT STD** HWFET @ 50K * * * **HWFET @ UL** 0.035 0.160 GASOLINE-TIER3 E10 PREM 20°F @ 50K COLD CO E10 PREMIUM GASOLINE (TIER3) 2.6 10.0 SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	3	*	*	0.080	1.0	*
@ UL	GASOLINE- TIER3 E10 PREM	STD	*	*	6	*	*	0.063	4.2	*
		BIN						0.140		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY				WHOLE \						
	FUEL TYPE	3DH	S (g/test) @	D UL	2DI	HS (g/test) (RL (g/mi) @ UL			
			CERT	STD	FEL	CERT	STD	FEL	CERT	STD
	PVGAR0200GCB	GASOLINE- TIER3 E10 PREM	0.434	0.300	0.500	0.340	0.300	0.500	0.00	0.05

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

		ORVR (g/gallon) @ UL			FUEL ONLY EVAP & CANISTER BLEED								
E	EVAPORATIVE FAMILY				FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
		FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
•	PVGAR0200GCB	GASOLINE- TIER3 E10 PREM	0.03	0.20	GASOLINE- TIER3 E10 PREM	*	*	*	*	0.007	0.020		



Executive Order: A-413-0283

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
PVGAR0200GCB PVGAR0200GCB-001		*	0.02					

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BUGATTI	CHIRON	PC	8.0	AMS7	PVGAR0200GCB	1	P
BUGATTI	CHIRON PUR SPORT	PC	8.0	AMS7	PVGAR0200GCB	1	P
BUGATTI	CHIRON SUPER SPORT	PC	8.0	AMS7	PVGAR0200GCB	1	P