

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP II	NFOR	MATION					
MODI YEA		TEST GROUP		VEHIC	VEHICLE CLASS(ES)				ATEGORY		FUEL TYPE		
202	3 F	FMXT05.2AHS		LDT4 DEDICATED SI VEHIC						GASOLINE			
	USEFL	JL LIFE (miles)		VEH	IICLE EMISS	ION (CATE	GORY	INTERIM / IN	ERN	IEDIATE IN-USE STD		
EX	H/ORVF	R EVAI		FTP		SF	ТР	FTP		SFTP			
1	50000	15000	LEV3	ULEV125	LEV	EV 3 COMPOSITE *				PM			
SPECIAL FEATURES & EXHAUST EMISSION CON SYSTEMS						L		OBD S	STATUS		ENGINE DISPLACEMENT (L)		
1	2TWC, 2WR-HO2S, 2HO2S, SFI, CAC, SC							FULL	*				
*	* *							PARTIAL ALL MODELS		5.2			
*			*				PAR	RTIAL WITH *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	AP / OR	VR FAMILY	APORATIVE	E STD CATE	GOR	(VAP EMISSION STD VEHICLE CLASS SPECIAL FEATURES					
	PFMXRC	260NDV	I	EV 3 OPTI	ON2 WITH	FEL		LI	LDT4 HCT				
				E	EMISSION CI	REDI	T INFO	ORMATION					
	REDIT F	OX FLEET AVE OR EXTENDEI ARRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMH RATIO	сно	HO/NMHC RATIO							D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

This Executive Order hereby cancels and supersedes Executive Order A-010-2442-1 dated April 12, 2023.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 3Oth day of October 2023.

Robin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)			O mi)		Ox mi)		HO /mi)		PM ⊭/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TP@UL TIER3 E10 PREM		0.064	0.125	1.3	2.1	*	*	1	4	0.0006	0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
	FUEL TYPE							IOG+NC	Dx (g/mi)		CO (g/mi)		
				FUELITP	E		CE	RT	STD	CER	Т	STD	
HWFET @	HWFET @ 50K *						*	r -	*				
HWFET @	@ UL		GASOLIN	E-TIER3	E10 PREM	1	0.0	29	0.125				
20°F @	20°F@50K COLD CO E10 PREMIUM GASOLINE (TIER3)									2.2	2	12.5	
			SFTP EXH	IAUST EM	ISSION S	TANDARD	S AND CE	RTIFIC	ATION LEVE	LS			

				US06						SC03		C	COMPOSITE		
	FUEL TY	PE	N	IMOG+N (g/mi)		CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi))x CO (g/mi)	PM (mg/mi)	
@ 4K	* C		т	*		*	*			*	*				
-		ST		*		*			*		*				
		CER	Т	*		* 3		3	*		*	0.049	1.6	*	
@ UL	GASOLIN TIER3 E PREM				*		* 6		*		*	* 0.063		*	
		BIN										0.070			
		WHOLE	/EHI	CLE EV	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS		
			WHOLE VEHICLE EVAPORATIVE TESTING												
	ORATIVE	FUEL TYPE		3	DHS (g	g/test) @ UL			2Dł	IS (g/test)	@ UL			RL (g/mi) @ UL	
				CEF	CERT		FEL	CEF	RL	STD	FEL	CE	RT	STD	
PFMXR0260NDV		GASOLINE- TIER3 E10		10.2	21 0	.500	0.500	0.198		0.500	0.50	0 0.	00	0.05	
0	ORVR / FUE	EL ONLY	/ CA	NISTER	BLEED) EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFICA	TION LEV	ELS	
FUEL ONLY EVAP & CANISTER BLEED															
EVAPORATIVE FAMILY		ORVR (g/ga		jallon) @	0 UL	FUE	3 FUEL TYPE		DHS RIG TEST (g/test) @ UL			RIG TEST t) @ UL			
		FUEL T	/PE	CERT	STD			CE	RT	STD	CERT	STD	CERT	STD	
PFMXR0260NDV		GASOLI TIER3		0.01	0.20		OLINE- R3 E10	*		*	*	*	0.011	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)														
EVAPORATIVE FAMILY	EVAPORATIVE FAMILY LEAK FAMILY CERT STD													
PFMXR0260NDV	PFMXR0260NDV PFMXR0260NDV-001 * 0.02													
*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751- 8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium- duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$; full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT:														

hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL		VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	F150 RAPTOR R	4WD	LDT4	5.2	SA10	PFMXR0260NDV	1	Р