

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GF	ROUP IN	NFOI	RMATION					
MODE	- T	TEST GROUP			VEHICLE CLASS(ES)				CATEGORY		FUEL TYPE		
2023	PK	MXT01.6P23		LDT2					-IN HYBRID RIC VEHICLE		GASOLINE		
	USEFUL	LIFE (miles)		VEF	IICLE EMIS	SION C	CATE	GORY	INTERIM / I	NTE	ERMEDIATE IN-USE STD		
EX⊦	I/ORVR	EVAP			FTP		S	FTP	FTP		SFTP		
15	0000	150000		LEV3	SULEV30	LEV	3 0	COMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CON SYSTEMS								OBD	STATUS		ENGINE DISPLACEMENT (L)		
1	DFI, WR-HO2S, HO2S, WU-TWC, TWC, TC, CAC, EGR, EGRC							FULL	ALL MODELS	ALL MODELS			
*	*							PARTIAL	*		1.6		
*	* PAI								H *				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	E STD CAT	EGORY	,		AISSION STD		SPECIAL FEATURES		
J	KMXR01	.06P2G		LEV 3 OPTION2			LDT2			HCT			
		·			EMISSION	CREDI	r inf	ORMATIO	N				
ALL	GR	E FOR TEST OUP EV	AV				G CREDIT FOR I-PZEV ZERO- EVAP		r foi	R OPTIONAL EXH. STD FOR WORK TRUCKS			
	ALL N	ODELS	N			N	1	N		N			
				NMOG	AND FLE	ET AVE	RAC		ATION				
NMOG RAF	BAF NMOG/NMHC RATIO PC+LDI (U-				750 LVW) LDT (3751 LVW			00	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	1.10		*		0.044			0.047		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>14th</u> day of June 2022.

John Schi for

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	r std	
FTP@50K	< *		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.013	0.030	0.1	1.0	*	*	*	4	0.001	1 0.003	
50°F @4K	GASOLINE- TIER3 E10		0.014	0.060	0.1	1.0	*	*	*	8			
					E		NN	NMOG+NOx (g/mi)			CO (g/mi)		
				FUEL TYPE					STD	CER	т	STD	
HWFET @ 50P		К *						•	*				
HWFET @ UL			GASOI	INE-TIEF		0.0	07	0.030					
20°F @ 50K		COLD (CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.3	3	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		1031		33101	STANDA	ARD3		CERTIFIC	ATION LE	VELS			
				US06					SC03		COMPOSITE					
	FUEL TYPE			NMOG	NOx		СО	P	М	NMC)G+NOx	CO	NMOG+	NOx	CO	PM
				(g/n	i)		(g/mi)	(mg	/mi)	(g/mi)	(g/mi)	(g/mi	i)	(g/mi)	(mg/mi)
@4K *			CERT	*		* *					*	*				
-		Γ	STD	*			*				*	*				
			CERT	*			*	1	-		*	*	0.01	2	0.1	*
@ UL	GASOLIN TIER3 E		STD *				*	* 6			*	*	0.063		4.2	*
		BIN											0.030			
		WHO	OLE VEH	ICLE E	VAPO	DRA'	TIVE E	MISSION	STAN	IDAR	DS AND C	ERTIFICA	TION LE	VELS	S	
						WF	IOLE V	EHICLE	EVAP	ORA	FIVE TEST	ING				
	ORATIVE AMILY	VE FUEL TY		E	3DHS (g/		(g/test) @ UL			2DHS (g/test		@ UL		RL (g/mi) @) UL
				CI	CERT ST		TD	FEL	CEF	RT	STD	FEL	L CERT		Г	STD
PKMXF	R0106P2G	-	ASOLINE EV3 E1(0	0.258 0.		400	*	0.1	97	0.400 *		0.00		0.05	
0) DRVR / FUB	EL O	NLY / C	NISTE	R BL	EED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIF	CATI	ION LEV	ELS
									FL	JEL C	ONLY EVA	P & CANIS	STER BL	EED		
	ORATIVE AMILY			R (g/gallon) @ UL			FUE	3 FUEL TYPE		3DHS RIG TEST (g/test) @ UL			2DHS RIG TEST (g/test) @ UL			ANISTER est) @ 4K
		FUE	EL TYPE	CER	S	TD			CE		STD	CERT	STD		CERT	STD
PKMXF	R0106P2G		SOLINE- ER3 E10	0.09	0.	20		*	,		*	*	*		*	*

CALIFORNIA

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
PKMXR0106P2G	PKMXR0106P2G-NQP	0.00	0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	KIA	SPORTAGE PLUG- IN HYBRID	LDT2	1.6	AMS 6	PKMXR0106P2G	1	F

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV	
NUMBER		(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE
1	TZEV	50.4	50.3	*	44.8	44.1	0.80