

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MODE YEAR		EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY				FUEL TYPE	
2023	PK	MXV01.6J2T			PC					N HYBRID C VEHICLE		GASOLINE	
	USEFUL	LIFE (miles)		VEF	IICLE EMIS	SION C	ATE	GORY		INTERIM / INT	ERI	MEDIATE IN-USE STD	
EXH	/ORVR	EVAP			FTP		SF	тр		FTP	SFTP		
15	0000	150000		LEV3	SULEV30	LEV	3 C	OMPOSITE	:	*		PM	
SPECIAL FEATURES & EXHAUST EMISSION CON SYSTEMS						OL		OBD	ST	TATUS	E	NGINE DISPLACEMENT (L)	
1	DFI, WR-HO2S, HO2S, WU-TWC, TWC, TC, CAC, EGR, EGRC							FULL		ALL MODELS			
*			*							*		1.6	
*	*						PAF	RTIAL WIT FINES	Ή	*			
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAP / ORVR FAMILY EVAPORATIVE ST						STD CATEGORY EVAP EMISSION S VEHICLE CLAS				SPECIAL FEATURES			
PKMXR0106J2G				LEV 3 OPTION2				PC			HCT		
				I	EMISSION	CREDIT	INF	ORMATIO	N				
GROUP A				MOG+NOX FLEET VE. CREDIT FOR ENDED WARRANTY		EET NMOG CRE		EV ZERO-			OR	OPTIONAL EXH. STD FOR WORK TRUCKS	
ALL MODELS					N				N		N		
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		O/NMHC ATIO	NMOG+N PC+LDT			LVW) LDT		MOG+NOX FLEET STE LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10		*		0.044				0.047	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this _____ day of June 2022.

Elma Sahi for

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)
	CERT STD			STD	CERT STD		CERT	STD	CERT	STD	CER	T STD
FTP@50K	50K *		*	*	*	*	*	*	*	*	*	*
FTP@UL	IL GASOLINE- TIER3 E10		0.017	0.030	0.1	1.0	*	*	*	4	0.00	1 0.003
50°F @4K	GASOLINE- TIER3 E10		0.016	0.060	0.3	1.0	*	*	*	8		
	FUEL TYPE						NN	NMOG+NOx (g/mi)			CO (g/	/mi)
			l	FUEL ITP	E		CE	RT	STD	CER	Т	STD
HWFET @ 50K		к *						•	*			
HWFET @ UL			GASOI	INE-TIEF	R3 E10		0.0	07	0.030			
20°F @ 50K		COLD C	CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.2	2	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			55	PE	λΠΑι		1122101	I STAND	4805	AND	CERTIFIC	ATION LE	VELS				
				US06					SC03					COMPOSITE			
FUEL TYPE		PE		NM	OG+N	Юx	со	Р	М	NMC)G+NOx	СО	NMOG+N	Ox	СО	РМ	
				((g/mi)		(g/mi)	(mg	/mi)	(g/mi)	(g/mi)	(g/mi)	((g/mi)	(mg/mi)	
@4K *			CERT		*		*				*	*					
_			STD		*		*				*	*					
			CERT		*		*	4	1		*	*	0.015		0.1	*	
@ UL GASOLINE- TIER3 E10			STD		*		*		5		*	*	0.063		4.2	*	
			BIN										0.030				
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																	
						W	HOLE \	/EHICLE	EVAP	ORA	IVE TEST	ING					
	ORATIVE	E FUEL TYP		FUEL TYPE 3DF CERT		3DHS (g/) UL		2DHS (g/test) @		@ UL	IL F		RL (g/mi) @ UL		
								RT .	STD	FEL	CEF	RT	STD	FEL	CE	CERT	
PKMXI	R0106J2G	_	ASOLINE LEV3 E1		0.2	58 0	.300	*	0.1	97	0.300	*	0.00		0.05		
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																	
EVAPORATIVE FAMILY								FUEL ONLY EVAP & CANISTER BLEED									
		ORVR (g/gallon) @ UL		0 UL							RIG TEST t) @ UL			O CANISTER (g/test) @ 4K			
		FU	EL TYPE	C	ERT	STD			CE		STD	CERT	STD		RT	STD	
PKMXI	R0106J2G	-	SOLINE- ER3 E10	1 0	.09	0.20		*	*	•	*	*	*		*	*	

CALIFORNIA

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
PKMXR0106J2G	PKMXR0106J2G-MQP	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2023 MODEL YEAR: VEHICLE MODELS INFORMATION

1 KIA SORENTO PLUG- IN HYBRID PC 1.6 AMS6 PKMXR0106J2G 1 F	MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
	1	KIA		PC	1.6	AMS 6	PKMXR0106J2G	1	F

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	/AY (MILES)	ZEV	
NUMBER	FREVIIFE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE	
1	TZEV	48.0	47.8	*	42.6	42.7	0.78	