

Executive Order: A-003-0825

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

	TEST GROUP INFORMATION												
MODE YEAR	- П	T TEST GROUP VEHICLE CLASS(ES)			S)		FUEL CATEGORY			FUEL TYPE			
2024	2024 RMBXT03.0HY2 LDT4						HYBRID ELECTRIC VEHICLE				GASOLINE		
	USEFUL	. LIFE (miles)		VEH	IICLE EMISS	ION (CATE	ORY	INTERIM / IN	TERM	MEDIATE IN-USE STD		
EXH	I/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP		
15	0000	150000)	LEV3	SULEV30	LEV	3 CC	MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS					L		OBD S	TATUS	EN	IGINE DISPLACEMENT (L)			
1	DFI,	IC, SCE, CAC	, WR	-но2s, н	02S, TWC(2	!)		FULL	*				
*			*				Р	ARTIAL	*		3.0		
*	* *							IAL WITH ALL MODELS					
		E,	/APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	/ INFORMATIO	V			
EVA	AP / ORV	R FAMILY	EVA	PORATIVE	STD CATE	GORY	Y EVAP EMISSION STD VEHICLE CLASS SPECIAL FEAT			PECIAL FEATURES			
I	RMBXR01	70LNF	LE	V 3 OPT	ON2 WITH	FEL		LDT4			*		
				ı	EMISSION CI	REDI	ΓINFO	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON ZERO-EVAP					NIMOG CEEDIT EOD DOD			D	OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N								N		N		
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION				
NMOG RAF	2 2 1 1 1 NMOG/NMHC 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			0-375			(3751 LVW-850)	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
*	*	1.10	10 * 0.03			.037			0.038		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0825

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have seven deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of one hundred twenty five dollars (\$125) per vehicle for the third through seventh deficiencies in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2024 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$45,563 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 10th day of July 2023.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Rolin U. Lang

Executive Order: A-003-0825 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F))
--	---

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP **FUEL TYPE**

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM	0.026	0.030	0.3	1.0	*	*	*	4	0.000	0.003
50°F @4K	*	*	*	*	*	*	*	*	*		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUELTIFE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.008	0.030			
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			0.4	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			US06			SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	1	*	*	0.018	0.5	*
@ UL	GASOLINE- TIER3 E10 PREM	STD	*	*	6	*	*	0.057	4.2	*
		BIN						0.020		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \						
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) @	D UL	2DI	HS (g/test) (@ UL	RL (g/n	ni) @ UL
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
RMBXR0170LNF	GASOLINE- TIER3 E10 PREM	0.328	0.500	0.450	0.330	0.500	0.450	0.02	0.05

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

						FUEL C	NLY EVAF	& CANIS	TER BLEE	D	
	EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL		FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K		
		FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
	RMBXR0170LNF	GASOLINE- TIER3 E10	0.01	0.20	GASOLINE- TIER3 E10 PREM	*	*	*	*	0.017	0.020



Executive Order: A-003-0825

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
RMBXR0170LNF	RMBXR0170LNF-LNF	*	0.02					

': not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES BENZ	GLS 450 4MATIC	LDT4	3.0	A9	RMBXR0170LNF	1	\$