

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP I	NFOR	MATION					
MODE YEA		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE			
2024	1 RO	GMXT02.0500	LDT3 DEDICATED SINGLE FUEL VEHICLE							GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION						ION	CATE	GORY	ORY INTERIM / INTERMEDIATE IN-USE S				
EXH/ORVR EVAP					FTP		SF	тр	FTP		SFTP		
1!	50000	150000)	LEV3	SULEV30	LEV	3 C	OMPOSITE	*		*		
SPE	ECIAL FI	EATURES & EXHAUST EMISSION CONTROL SYSTEMS OBD STATUS ENGINE DISPLA						IGINE DISPLACEMENT (L)					
1	Т	C, CAC, DFI,	WR-I	HO2S, TW	C, HO2S			FULL	ALL MODELS				
*			*				F	PARTIAL	*	2.0			
*			*				PAF	RTIAL WITH FINES	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						Y		SSION STD E CLASS	SPECIAL FEATURES			
1	RGMXR0	15740B	LE	V 3 OPTI	ION2 WITH	FEL		LI	тз		HCT		
				I	EMISSION CI	REDI	T INF	ORMATION					
	REDIT FO	DX FLEET AVE. DR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOF			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET		RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		CHO/NMHC RATIO				N) LDT	+NOX FLEET S1 (3751 LVW-8500 R) + MDPV (g/mi		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.037			0.038		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 24 day of February 2023.

Tolin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				G+NOx mi)	-	O mi)		Ox mi)	HC (mg	-	(PM g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	· STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL		SOLINE- ER3 E10	0.026	0.030	0.8	1.0	*	*	*	4	0.002	2 0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
								IOG+N	Ox (g/mi)		CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CER	Т	STD	
HWFET @) 50K		*						*				
HWFET (@ UL		GASOI	LINE-TIE	R3 E10		0.0	0.002 0.03					
20°F @ 50K		COLD (CO E10 RE	EGULAR G	ASOLINE	(TIER3)				2.5	5	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SFT	P EXHA	JST EN	IISSION	I STAND	ARDS	AND	CERTIFIC	ATION LE	VELS			
						US06				SC03		С	OMPOS	ITE	
	FUEL TY	PE		NMOG+N (g/mi)	-	CO (g/mi)	Pi (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)		-	PM (mg/mi)
@ 4K	*	с	ERT	*		*				*	*				
_			STD	*		*			*		*				
		С	ERT	*		*	1	-		*	*	0.013	0	. 6	*
@ UL	GASOLIN TIER3 E		STD	*		*	e	5		*	*	0.057	4	. 2	*
		I	BIN									0.050			
	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
				WHOLE VEHICLE EVAPORATIVE TESTING											
	ORATIVE	FUE	EL TYPI	= 3	BDHS (g	g/test) @	DUL		2Dł	IS (g/test)	@ UL	F	RL (g/m	CO PN (g/mi) (mg/r 0.6 * 4.2 * /mi) @ UL STD 0.05 N LEVELS EED CANISTE GT (g/test) @ 4 ERT STD	UL
				CEF	RT	STD	FEL	CEF	RL	STD	FEL	CE	RT		STD
RGMXR	R015740В		SOLINE ER3 E1(102	92 0	.500	0.450	0.2	64	0.500	0.450	0.	00	(0.05
C	DRVR / FUB	EL ON	ILY / CA	NISTER	BLEE) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION L	EVE	LS
								FU	EL C	NLY EVA	P & CANIS	STER BLEE	D		
EVAPORATIVE FAMILY		OF	ORVR (g/gallon				L TYPE			IG TEST) @ UL		RIG TEST t) @ UL			
		FUEL	L TYPE	CERT	STD			CE	RT	STD	CERT	STD	CER	Г	STD
RGMXF	R015740B		DLINE- R3 E10	0.02	0.20		OLINE- R3 E10	*		*	*	*	0.01	2	0.020



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
RGMXR015740B	RGMXR015740B-LK1	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CADILLAC	XT5 AWD	LDT3	2.0	SA9	RGMXR015740B	1	F
CADILLAC	XT5 FWD	LDT3	2.0	SA9	RGMXR015740B	1	F
CADILLAC	XT6 AWD	LDT3	2.0	SA9	RGMXR015740B	1	F
CADILLAC	XT6 FWD	LDT3	2.0	SA9	RGMXR015740B	1	F
CHEVROLET	BLAZER AWD	LDT3	2.0	A9	RGMXR015740B	1	F
CHEVROLET	BLAZER FWD	LDT3	2.0	A9	RGMXR015740B	1	F