

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP II	NFOR	MATION					
MODE YEAI	T	EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2024	l RE	MXT02.0U1X		LDT2 DE				-	SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								CATEGORY INTERIM / INTERMEDIATE IN-USE					
EXH	I/ORVR	EVAP		FTP SF				FTP	SFTP				
15	50000	LEV3	ULEV50	LEV 3 COMPOSITE			*		*				
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	IGINE DISPLACEMENT (L)		
1	TWC	, WR-HO2S, H	02s,	DFI, MFI	, тс, сас			FULL	*				
*	* *							PARTIAL	ALL MODELS		2.0		
*						PAF	ARTIAL WITH FINES						
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS SPECIAL			PECIAL FEATURES		
1	RBMXR01	L20U11	LE	V 3 OPTI	ON2 WITH	FEL		LI	от2	*			
				I	EMISSION CI	REDI	T INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							EV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF												
*	*	1.10	10 * 0.03					0.038 *					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this  $\underline{28th}$  day of July 2023.

im Jacoubian for

Robin U. Lang, Chief Emissions Certification and Compliance Division



**FUEL TYPE** 

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

## EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)			C (g/I	O mi)		Ox mi)	HC (mg	-		PM (g/mi)	
			CERT	STD	CERT STD C		CERT	STD	CERT	STD	CERT	STD	
FTP@50K	к *		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.021	0.050	0.5	1.7	*	*	*	4	0.001	0.003	
50°F @4K		SOLINE- R3 E10	0.012	0.100	0.3	1.7	*	*	*	16			
				FUEL TYP	E		NN	10G+N	Ox (g/mi)		CO (g/m	i)	
			l	CE	RT	STD	CER	т	STD				
HWFET @ 50K		K *							*				
HWFET @ UL			GASOI	INE-TIEF	R3 E10		0.0	09	0.050				
20°F @ 50K		COLD C	CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.5		12.5	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		<b>HAU</b>		22101	ISTANDA	ARDS A		CERTIFIC		VELO				
				US06							SC03		C	COMPOSITE			
	FUEL TY	PE		NMO (g	G+N( ı/mi)	Ох	CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)	)x C( (g/r	-	PM (mg/mi)	
@4K *			CERT		*		*			*		*					
•			STD	*			*			*		*					
	DUL GASOLINE- TIER3 E10 BIN		CERT		*		*			*		*	0.016	0.	5	*	
@ UL			STD		*		*	* 6		*		*	0.057	4.	2	*	
			BIN										0.070				
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																	
WHOLE VEHICLE EVAPORATIVE TESTING																	
EVAPORATIVE FAMILY		FUEL TYP		E	3DHS (g/		g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @		UL		
					CERT		TD	FEL	CER	Т	STD	FEL	CE	RT	STD		
RBMXR0120U11			ASOLINE IER3 E1		0.19	1 0.	400	0.300	0.18	9	0.400	0.300	0.	0.01		0.05	
(	ORVR / FUI	EL O	ONLY / C	ANIST	ter e	BLEED	EVAP	ORATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LI	EVE	LS	
									FUE	EL O	NLY EVA	P & CANIS	TER BLEE	D			
EVAPORATIVE FAMILY		0	ORVR (g/gal		lon) @ UL		FUE			DHS RIG TEST (g/test) @ UL			tig test () @ UL	BLEED CA TEST (g/tes			
		FUI	EL TYPE	CE	RT	STD			CER	RT.	STD	CERT	STD	CERT		STD	
RBMXI	XR0120U11 GASOLINE- TIER3 E10 0.10 0.		0.20	GASOLINE- TIER3 E10		*		*	*	*	0.015	5	0.020				



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
RBMXR0120U11	RBMXR0120U11-01	0.01	0.02							

': not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
BMW	X1 M35I	LDT2	2.0	AMS7	RBMXR0120U11	1	Р