

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP I	NFOR	MATION					
MODE YEAI	T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2024	l RG	MXV06.2093			PC			HYBRID VE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION							CATE	CATEGORY INTERIM / INTERMEDIATE IN-U					
EXH	I/ORVR	EVAP	FTP SI				TP FTP			SFTP			
1	50000	150000)	LEV3	ULEV125	LEV	3 C	OMPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S			ENGINE DISPLACEMENT (L)		
1		DFI, 2WR-H	102S,	2TWC, 2	HO2S			FULL	ALL MODELS				
*	*							PARTIAL	*		6.2		
*			*				PAR	PARTIAL WITH * FINES					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							Y EVAP EMISSION STD			SPECIAL FEATURES		
1	RGMXR01	.2150A	LE	V 3 OPTI	CON2 WITH	FEL		PC			HCT		
					EMISSION C	REDI	T INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY										OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N			N N					
				NMOG	AND FLEE		RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF RATIO FTP NMOG/NMHC RATIO HCHO/NMHC RATIO NMOG+NOX FL PC+LDT (0-37 (g/mi)					0-375					D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.037			0.038 *				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-006-2415 dated July 24, 2023.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\underline{/4tk}$ day of August 2023.

Robin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				6+NOx mi)		O mi)		Ox mi)		CHO g/mi)		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CEF	RT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10 PREM		0.041	0.125	0.2	2.1	*	*	*	4	0.0	01	0.003
50°F @4K		*	*	*	*	*	*	*	*	*			
							NN	IOG+N	Ox (g/mi)		CO (g	g/mi)	
				FUEL TYP	E		CE	RT	STD	CEF	RL	T STD	
HWFET @) 50K			*			*	* *					
HWFET @ UL			GASOLIN	E-TIER3	E10 PREM	0.0	001	0.125					
20°F @	50K	COLD (CO E10 PH	REMIUM GA	ASOLINE				0.	9		10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			55		XHAU		122101	ISTANDA	ARD2	AND	CERTIFIC	ATION LE	VELS				
			L L L L L L L L L L L L L L L L L L L								SC03		C	COMPOSITE			
	FUEL TY	PE			OG+N (g/mi)	Ox	CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)	NMOG+N (g/mi)		CO g/mi)	PM (mg/mi)	
@ 4K	*		CERT	*			*				*	*					
-			STD				*				*	*					
	GASOLINE @ UL TIER3 E1 PREM		CERT	*			*		*		*	0.021		0.2	*		
@ UL			STD	*			* 6		5	*		*	0.057		4.2	*	
		BIN											0.120				
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																	
WHOLE							HOLE \	LE VEHICLE EVAPORATIVE TESTING									
	EVAPORATIVE FAMILY		FUEL TYPE		PE 3DHS (g		g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UI			UL	
					CER	CERT STD		FEL	CEF	RT	STD	FEL	CE	ERT		STD	
RGMXR012150A		_	ASOLINE IER3 E1 PREM		0.42	25 0	. 300	0.500	0.3	45	0.300	0.50	D 0.	0.00		0.05	
(ORVR / FU	EL C	ONLY/C	ANI	STER	BLEED	EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CERTIFIC	ATION	LEVE	LS	
									FU	JEL C	ONLY EVA	P & CANIS	STER BLEI	ED			
	EVAPORATIVE FAMILY		ORVR (g/ga		illon) @ UL		FUE	FUEL TYPE		3DHS RIG TEST (g/test) @ UL			RIG TEST t) @ UL			CANISTER test) @ 4K	
		FU	EL TYPE	C	ERT	STD			CE	RT	STD	CERT	STD	CE	RT	STD	
RGMXR012150A		-	SOLINE- ER3 E1(PREM		.04	0.20	TIE	OLINE- R3 E10 PREM	*		*	*	*	0.00	038	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
RGMXR012150A	RGMXR012150A-LK1	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CHEVROLET	CORVETTE E-RAY	PC	6.2	SA8	RGMXR012150A	1	F