

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP II	NFOR	MATION					
MODE		TEST GROUP		VEHIC	CLE CLASS(ES) FU				ATEGORY		FUEL TYPE		
2024	4 R	BMXV03.0B07		PC DEDICA				-	SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION						ION	CATEGORY INTERIM / INTERMEDIATE IN-USE S						
EXI	I/ORVR	EVAP			FTP		SF	ТР	FTP		SFTP		
1!	150000 150000 L			LEV3	ULEV125	LEV	3 C	OMPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	TWC, WR-HO2S, HO2S, DFI, TC, CAC							FULL	*				
*	*							PARTIAL	ALL MODELS		3.0		
*	*							TIAL WITH	*				
I		E	VAPO	RATIVE &	REFUELING	(EV/	AP/OF	RVR) FAMIL					
EVA	AP / OR	VR FAMILY	EVA	PORATIVE	E STD CATE	GOR	Y EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	RBMXR0	150G30	LF	IV 3 OPTI	ION2 WITH	FEL	PC			*			
					EMISSION C	REDI	T INFO	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N				
				NMOG	AND FLEE		RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO	• • • • • •	HO/NMHC RATIO	NMOG+NO PC+LDT ((g								
*	*	1.10		*	0	.037	37 0.038				*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 3/at day of March 2023.

Rolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I				NOx (g/mi)		HCHO (mg/mi)		PM g/mi)	
		CERT STD CE		CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	ж *		*	*	*	*	*	*	*	*	*	*
FTP@UL	UL GASOLINE- TIER3 E10		0.023	0.125	0.2	2.1	*	*	*	4	0.000	0.003
50°F @4K		SOLINE- R3 E10	0.032	0.250	0.3	2.1	*	*	*	16	16	
				NN	NMOG+NOx (g/mi)			CO (g/mi)				
	FUEL TYPE				CE	RT	STD	CER	Т	STD		
HWFET @ 50K			*						*			
HWFET @ UL		L GASOLINE-TIER3 E10						04	0.125			
20°F @ 50K		COLD (CO E10 RE	GULAR GA	ASOLINE	(TIER3)				0.9)	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		031 6	1122101	N STANDA	ARDS A		CERTIFIC		VELO			
					US06					SC03		C	OMPOSIT	1	
	FUEL TY	PE		NMOG+ (g/mi		CO (g/mi)				DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/mi	PM (mg/mi)	
@ 4K	*		CERT	*		*				*	*				
•			STD	*		*				*	*				
		(CERT	*		*	C)		*	*	0.027	0.5	*	
@ UL	GASOLIN TIER3 E		STD	*		*	e	5		*	*	0.057	4.2	*	
			BIN									0.120			
		WHC	DLE VEH		'APOR	ATIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS		
					V	VHOLE	VEHICLE	EVAPO	ORAI	TIVE TEST	ING				
	ORATIVE AMILY	FUEL TYPE		≘ 3DHS (g		(g/test) @ UL			2DHS (g/test)		@ UL	F	RL (g/mi) @ l		
				CE	RT	STD	FEL	CER	R	STD	FEL	CE	RT	STD	
RBMXF	R0150G30		SOLINE ER3 E1	102	19	0.300	0.300	0.23	34	0.300	0.30	0.0	01	0.05	
(ORVR / FUI	EL O	NLY / CA	ANISTEF	R BLEE	D EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LEV	'ELS	
								FU	EL C	NLY EVA	P & CANIS	TER BLEE	D		
	ORATIVE AMILY	0)RVR (g/	gallon) (@ UL	FUE	FEL CE 0.300 0.2 ORATIVE EMIS F L TYPE 3E OLINE- CE	-	HS RIG TEST g/test) @ UL		-	RIG TEST t) @ UL		CANISTER g/test) @ 4K	
		FUE	EL TYPE	CERT	STD			CEF	RT	STD	CERT	STD	CERT	STD	
RBMXF	R0150G30		OLINE- R3 E10	0.04	0.2)	OLINE- R3 E10	*		*	*	*	0.004	0.020	



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
RBMXR0150G30	RBMXR0150G30-001	0.00	0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%' ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL VEH CLASS ENGINE (L) TRANS TYPE EVAPORATIVE EXH ECS										
BMW	8401 CONVERTIBLE	PC	3.0	SA8	RBMXR0150G30	1	P				
BMW	8401 COUPE	PC	3.0	SA8	RBMXR0150G30	1	P				
BMW	8401 GRAN COUPE	PC	3.0	SA8	RBMXR0150G30	1	P				
BMW	8401 XDRIVE CONVERTIBLE	PC	3.0	SA8	RBMXR0150G30	1	Р				
BMW	8401 XDRIVE COUPE	PC	3.0	SA8	RBMXR0150G30	1	P				
BMW	8401 XDRIVE GRAN COUPE	PC	3.0	SA8	RBMXR0150G30	1	Р				