

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

JEL TYPE ASOLINE ATE IN-USE STD SFTP * E DISPLACEMENT (L)										
TE IN-USE STD SFTP * DISPLACEMENT										
SFTP * DISPLACEMENT										
* DISPLACEMENT										
y										
3.6										
SPECIAL FEATURES										
*										
FOR OPTIONAL EXH. STD FOR WORK TRUCKS										
N										
NMOG AND FLEET AVERAGE INFORMATION										
*										
RCRXR0125FEH LEV 3 OPTION2 WITH FEL LDT3 *   EMISSION CREDIT INFORMATION EMISSION CREDIT INFORMATION NMOG CREDIT FOR NON-PZEV ZERO- EXTENDED WARRANTY NMOG CREDIT FOR NON-PZEV ZERO- EVAP NMOG CREDIT FOR DOR OPTIONAL EXH. FOR WORK TRUE   ALL MODELS N N N N   MMOG CREDIS NMOG AND FLEET AVERAGE INFORMATION NMOG+NOX FLEET STD LDT (3751 LVW-8500 NMOG+NOX FLEET MDV (10,001-14,0										

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 26th day of July 2023.

tim Jacoubian for

Robin Ø. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

### EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

#### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	i+NOx mi)		O mi)		Ox mi)		:HO J/mi)		PM (g/mi)
		CERT STD CERT STD CERT		STD CERT		STD	CER	T STD				
FTP@50K	( *		*	*	*	*	*	*	*	*	*	*
FTP@UL	IL GASOLINE- LEV3 E10		0.0201	0.030	0.07	1.0	*	*	*	4	0.00	04 0.001
50°F @4K		*	*	*	*	*	*	*	*	*		
								10G+N	Ox (g/mi)		CO (g/	/mi)
FUEL TYPE						CE	RT	STD	CEF	RT	STD	
HWFET @ 50K			*					•	*			
HWFET @ UL			GASOLINE-LEV3 E10					072	0.030			
20°F @ 50K		G	ASOLINE-	COLD CO	LOW OCT	NE				0.6	1	12.5

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS															
				US06 SC03					COI	MPOSITE						
	FUEL TYPE				NMOG+NOx (g/mi)		CO (g/mi)					CO (g/mi)	NMOG+NOx (g/mi)		CO (g/mi)	PM (mg/mi)
@4K *			CERT		*		*		*		*					
-		;		STD		*		*		*		*				
		CERT			*		*	0.	. 4		*	*	0.01	.37	0.11	*
@ UL	@ UL GASOLINI LEV3 E1		STD		*		*	e	5		*	*	0.0	57	4.2	*
			BIN										0.0	30		
		WHO	OLE VE	HICL	E EV/	APORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION L	EVEL	S	
						W	HOLE \	/EHICLE	EVAPO	ORA	IVE TEST	ING				
	ORATIVE	FUEL TYP		FUEL TYPE		TYPE 3DHS (g		/test) @	DUL		2DHS (g/test) @ UL RL (g/mi) @ U				) UL	
					CER	RT :	STD	FEL	CER	RL	STD FE			CERT		STD
RCRXR0125FEH			ASOLIN EV3 E1	_	0.19	19 0	. 500	0.450	0.24	75	0.500	0.45	0	0.00	0	0.05
C	DRVR / FUE	EL O	NLY/C	ANIS	STER	BLEED	) EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIF	FICAT	ION LEV	ELS
									FU	EL C	NLY EVA	P & CANIS	STER B	LEED		
	ORATIVE ORVR		ORVR (g	/gall	lon) @	UL	3DHS RI FUEL TYPE (g/test)			2DHS F (g/tes	RIG TES t) @ UL		BLEED CANISTER EST (g/test) @ 4K			
		FUE	EL TYPI	EC	ERT	STD			CEI	RT	STD	CERT	ST	)	CERT	STD
RCRXF	R0125FEH		SOLINE V3 E10	0	. 053	0.20		*	*		*	*	*		*	*

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
RCRXR0125FEH	RCRXR0125FEH-LF1	*	0.02							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

## 2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	CHRYSLER	PACIFICA HYBRID	LDT3	3.6	CV1	RCRXR0125FEH	1	P

### **ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION**

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	/AY (MILES)	ZEV
NUMBER	FREVITE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE
1	TZEV	48.00	48.25	*	43.28	38.86	0.78