

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP II	NFOR	MATION					
MODE YEAI	T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE		
2024	l RI	YXV01.8P33			PC			ELECTRIC HICLE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMIS						E EMISSION CATEGORY INTERIM / INT					ERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP		SF	ТР	FTP		SFTP		
15	150000 150000 LEV3			LEV3	SULEV30	LEV	3 COMPOSITE *			*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	ENGINE DISPLACEMENT (L)			
1	SFI, EGR, EGRC, WR-HO2S, TWC(2), HO2S							FULL	*				
*	*							ARTIAL	ALL MODELS		1.8		
*	*							TIAL WITH FINES	*				
•		E	VAPO	RATIVE &	REFUELING	(EV/	AP/OR	VR) FAMIL	(INFORMATION	1			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						(EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	RTYXR01	.30J72	LE	V 3 OPTI	ION2 WITH	FEL		PC			*		
				I	EMISSION CI	REDI	T INFC	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N		N		
				NMOG	AND FLEET		RAGE		TION				
NMOG RAF	CH4 RAF					0-375							
*	*	1.10		*	0	.037			0.038		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 26th day of July 2023.

im Jacoubian for

Robin Ø. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

	_											
			NMOG (g/I	i+NOx mi)		O mi)	N((g/i	Dx mi)		HO /mi)		PM /mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL		OLINE- R3 E10	0.0249	0.030	0.06	1.0	*	*	*	4	0.0001	0.003
50°F @4K		*	*	*	*	*	*	*	*	*		
						NN	NMOG+NOx (g/mi)			CO (g/mi)		
	FUEL TYPE				CE	RT	STD	CER	T	STD		
HWFET @ 50K			*						*			
HWFET @	@ UL		GASOLINE-TIER3 E10				0.0	104	0.030			
20°F @ 50K		COLD (CO E10 RE	GULAR G	ASOLINE	(TIER3)				0.6	0	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS													
				US06						SC03		C	OMPOSIT	E
	FUEL TY	PE	•	NMOG+N (g/mi)		CO (g/mi)	P (mg	M /mi)		DG+NOx g/mi)	CO (g/mi)	NMOG+NC (g/mi)	x CO (g/mi	PM (mg/mi)
@ 4K	*	C	ERT	*	*					*	*			
		S	STD	*		*				*	*			
		C	ERT	*	*		* 0.3		*		*	0.0208	0.06	*
@ UL	GASOLIN TIER3 E	9	STD	*		*	e	5		*	*	0.057	4.2	*
		E	BIN									0.030		
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
WHOLE VEHICLE EVAPORATIVE TESTING														
	ORATIVE AMILY	FUE	EL TYPE	= 3	DHS (g	g/test) @	0 UL		2DH	IS (g/test)	@ UL	F	RL (g/mi) (∄ UL
				CEF	RT	STD	FEL	CER	T	STD	FEL	CE	RT	STD
RTYXF	R0130J72		SOLINE- ER3 E10	10 16	0 803	.300	0.300	0.17	67	0.300	0.300	0.0	004	0.05
(ORVR / FU	EL ON	LY / CA	NISTER	BLEED) EVAP	ORATIVE	EEMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	/ELS
								FU	EL C	NLY EVA	P & CANIS	STER BLEE	D	
	ORATIVE AMILY	OR	RVR (g/g	gallon) @	DUL	FUE	L TYPE			IG TEST) @ UL		RIG TEST t) @ UL		CANISTER test) @ 4K
		FUEL	TYPE	CERT	STD			CEF	RT	STD	CERT	STD	CERT	STD
RTYXF	R0130J72		DLINE- 3 E10	0.001	0.20		*	*		*	*	*	*	*



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
RTYXR0130J72	RTYXR0130J72-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	COROLLA HYBRID	PC	1.8	CV1	RTYXR0130J72	1	P
TOYOTA	COROLLA HYBRID AWD	PC	1.8	CV1	RTYXR0130J72	1	P