

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC	UP IN	NFOR	MATION					
MODE YEAR		TEST GROUP			VEHICLE CLASS(ES)				CATEGORY		FUEL TYPE		
2024	RJ	LXJ02.0RTX		LDT2, PC					SINGLE FUEL		GASOLINE		
l	USEFUL	. LIFE (miles)		VEHICLE EMISSION CATEGOR				GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP S				FTP FTP			SFTP		
15	150000 150000			LEV3	SULEV30 LEV 3 STAND-				*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTE SYSTEMS								OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	WR-	HO2S, TWC,	HO2S (2), DFI,	TC, CAC			FULL	*				
*			*				Р	ARTIAL	ALL MODELS		2.0		
*						TIAL WITH FINES	*	1					
		E	/APOI	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATION	1			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
F	RJLXR01	40P1Z		LEV 3	LEV 3 OPTION2			LDT2			*		
F	RJLXR01	60P1Z		LEV 3 OPTION2			PC			*			
					EMISSION CI	REDIT	r info	ORMATION					
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	PZEV NMOG CREDIT FOR DOP			R OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N			N			N		
				NMOG	AND FLEET	AVE	RAGE		TION				
NMOG RAF				HO/NMHC RATIO NMOG+NOX FLEET S PC+LDT (0-3750 LV (g/mi)									
*	*	1.10		*	0	.037			0.038		*		
See th	o Attach	ment for Vehi		dels Eva	norative Fa	milv	Engir	na Displace	ment Emission		trol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

The listed vehicle models have been certified on the condition that the manufacturer provide all the on-board diagnostic data required by 13 CCR Section 1968.2(h)(1) by March 20, 2023. Failure to submit the required demonstration data by the specified date, or failure of the submitted demonstration data to show compliance with the test procedures, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified and subject to a civil penalty of up to \$42,450 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this <u>2nd</u> day of February 2023.

Rolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/I	i+NOx mi)	CO (g/mi)			NOx (g/mi)		HO /mi)		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	r std	
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- LEV3 E10		0.026	0.030	0.3	1.0	*	*	*	4	0.00	2 0.003	
50°F @4K		OLINE- V3 E10	0.045	0.060	0.4	1.0	*	*	*	8			
					F		NN	NMOG+NOx (g/mi)			CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CER	Т	STD	
HWFET @ 50K				*			*	*					
HWFET @ UL			GASO	LINE-LEV	3 E10		0.0	001	0.030				
20°F @ 50K			GASO	LINE-LEV	3 E10					0.7		10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

						US06				SC03			COM	POSI	TE	
	FUEL TYPE				OG+NOx	CO	F	PM	NMOG+NOx		СО	NMOG+NOx		со		РМ
					(g/mi)	(g/mi)	(g/mi) (mg		(g /	mi)	(g/mi)	(g/mi)	(g/m	ni)	(mg/mi)
@ 4K	*		CERT		*	*			ł	*	*					
-		STD		*	*			ł	*	*						
	@ UL GASOLINE- LEV3 E10		CERT	0	0.016	5.4	5.4 5		0.0	009	0.6		*			*
@ UL			STD	0.050		9.6	9.6		0.0	020	20 3.2		* *		*	
			BIN										*			
		WН	OLE VE	HICL	E EVAPO	ORATIVE E	MISSIO		DARD	S AND C	ERTIFIC	ΑΤΙΟΙ	N LEVELS	;		
						WHOLE \	/EHICLE	EVAPO	RATI\	/E TEST	ING					
	EVAPORATIVE FAMILY		FUEL TYPE		3DH	S (g/test) @	(g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UL			JL
					CERT	STD	FEL	CER	Т	STD	FEL	CERT			S	STD
RJLXR0140P1Z		_	ASOLIN LEV3 E	0 227		0.400	*	*		0.400	*		0.00		0.05	
RJLXR0160P1Z			ASOLIN LEV3 E		0.238	0.300	*	*		0.300	*	0.00		0.		.05



JAGUAR LAND ROVER LIMITED

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
				FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE			IG TEST) @ UL		RIG TEST t) @ UL	BLEED CANISTE TEST (g/test) @ 4						
	FUEL TYPE	CERT	STD]		CERT	STD	CERT	STD	CERT	STD			
RJLXR0140P1Z	GASOLINE- LEV3 E10	0.01	0.20	GASOLINE- LEV3 E10		*	*	*	*	0.018	0.020			
RJLXR0160P1Z	GASOLINE- LEV3 E10 0.01 0.20		0.20	GASOLINE- LEV3 E10		*	*	*	*	0.010	0.020			
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)													
EVAPORATIVE	Y CERT					STD								
RJLXR0160P1Z RJLXR0160			160P1Z	-001		*	r		0.02					
RJLXR0140	P1Z	RJLXR0	140P1z	-001		÷	r		0.02					

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
JAGUAR	F-PACE P250	LDT2	2.0	SA8	RJLXR0140P1Z	1	P
JAGUAR	XF P250	PC	2.0	SA8	RJLXR0160P1Z	1	P
JAGUAR	XF P300 AWD	PC	2.0	SA8	RJLXR0160P1Z	1	P
LAND ROVER	RANGE ROVER VELAR P250	LDT2	2.0	SA8	RJLXR0140P1Z	1	P