

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR 2024 U	RM	EST GROUP		VEHIC										
		LNV04.0M14		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE				
U	ISEFUL			PC			1	DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
		LIFE (miles)		VEF	IICLE EMISS	ION C	ATEC	GORY	INTERIM / IN	TERMEDIATE IN-USE STD				
EXH/0	ORVR	EVAP			FTP		SF	ТР	FTP	SFTP				
150	0000	150000		LEV3	ULEV125	LEV	3 CC	MPOSITE	*	*				
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS OBD STATUS							EN	IGINE DISPLACEMENT (L)						
1	2TWC (2	2), 2WR-HO2S	, 2но 2САС	•	, AIR, 2TC	:,		FULL	*					
*			*				Р	ARTIAL	ALL MODELS	4.0				
*			*					TIAL WITH	*	1				
		EV	APOF	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	(INFORMATION					
EVAP	P / ORVI	R FAMILY	EVAF	PORATIVE	E STD CATE	GORY	,		SSION STD E CLASS	SF	PECIAL FEATURES			
RM	MLNR01	64M14	LE	LEV 3 OPTION2 WITH FEL				PC			*			
				I	EMISSION CI	REDIT	INFC	ORMATION						
	DIT FO	X FLEET AVE. OR EXTENDED RRANTY	1		EDIT FOR N ZERO-EVAP	ON-P	N-PZEV NMOG CREDIT FOR I			OPTIONAL EXH. STD FOR WORK TRUCKS				
		N			N				N	N				
				NMOG	AND FLEET	AVE	RAGE		TION					
	PC+LDL (0-37				0-375									
*	*	1.10		*	0	.051			0.051		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this ______ day of August 2023.

tolmo Schi for

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM	0.099	0.125	0.8	2.1	*	*	1.1	4	*	0.003
50°F @4K	GASOLINE- TIER3 E10 PREM	0.128	0.250	0.9	2.1	*	*	1.2	16		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUELTIPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.043	0.125			
20°F @ 50K	GASOLINE-TIER3 E10 PREM			1.3	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS													
					US06			SC03	3		COMPOSITE			
	FUEL TYP	ΡE		NMOG+NOx	CO	Р	М	NMOG+NOx	со	NMOG	i+NOx	СО	РМ	
				(g/mi)	(g/mi)	(mg	ı/mi)	(g/mi)	(g/mi)	(g/r	ni)	(g/mi)	(mg/mi)	
@ 4K	@ 4K *		CERT	*	*			*	*					
-			STD	*	*			*	*					
	GASOLINE- DOUL TIER3 E10 PREM		CERT	*	*		*	*	*	0.074		0.71	*	
@ UL			STD	*	*		6	*	*	0.057		4.2	*	
			BIN							0.0	90			
		wно	DLE VE	HICLE EVAP	ORATIVE E	MISSION	STAN	DARDS AND	CERTIFIC	ATION L	EVELS		·	
					WHOLE \	VEHICLE	EVAPC	DRATIVE TES	ΓING					
	EVAPORATIVE FAMILY F		EL TY	PE 3DH	S (g/test) @	@ UL		2DHS (g/test) @ UL				RL (g/mi) @ UL		
				CERT	STD	FEL	CER	T STD	FEI	FEL CERT			STD	
RMLNF	R0164M14		SOLIN EV3 E1 PREM		0.300	0.275	0.23	95 0.300	0.27	75	0.001			



MCLAREN AUTOMOTIVE LIMITED

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
		FUEL ONLY EVAP & CANISTER BLEED											
EVAPORATIVE FAMILY	ORVR (g/	gallon) @) UL	FUEL TYPE		3DHS R (g/test	IG TEST) @ UL	_	RIG TEST st) @ UL	BLEED CANISTER TEST (g/test) @ 4			
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
RMLNR0164M14	GASOLINE- LEV3 E10 PREM	0.04	0.20	GASOLINE- LEV3 E10 PREM		*	*	*	*	0.008	0.020		
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE	LEA	LEAK FAMILY			CE	RT		STD					
RMLNR0164	RMLNR0164M14-L14				0.0	02		0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxvgen sensor: WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOx sensor: PMS: PM sensor: RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission: AMS: automated manual-selectable transmission: OT: other transmission: AER: all-electric range: EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MCLAREN	750S COUPE	PC	4.0	AMS7	RMLNR0164M14	1	P
MCLAREN	750S SPIDER	PC	4.0	AMS7	RMLNR0164M14	1	P