

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE YEAR		TEST GROUP			VEHICLE CLASS(ES)				CATEGORY		FUEL TYPE		
2024	RF	MXT03.03V7		LDT4				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
ļ	USEFUL	LIFE (miles)		VEF	IICLE EMISS	CATE	GORY	INTERIM / IN	TE	ERMEDIATE IN-USE STD			
EXH	/ORVR	EVAP			FTP		SF	FTP FTP			SFTP		
15	0000	150000		LEV3	ULEV50 LEV 3 COM			MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	I	ENGINE DISPLACEMENT (L)		
1	2TWC	(2), DFI, 2T	С, 2н	02S, 2WF	R-HO2S, CAG	2		FULL	*				
*			*				P	ARTIAL	ALL MODELS		3.0		
*			*				PAR	TIAL WITH	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								SSION STD E CLASS		SPECIAL FEATURES		
F	RFMXR01	40NDG	LE	V 3 OPTI	7 3 OPTION2 WITH FEL			LDT4			HCT		
F	RFMXR01	40NDV	LE	V 3 OPTI	OPTION2 WITH FEL			LDT4			HCT		
		·		I	EMISSION CI	REDI	T INFO	ORMATION					
	EDIT FO	OX FLEET AVE. OR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOP			R OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N	N			
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 FTP RAF NMOG/NMHC RATIO HCHO/NMHC RATIO (0-37 (g/mi)				0-375					NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.037			0.038 *				
Soo th	o Attook	mont for Vahi			norativa Ca	milu		o Dianlaga	mont Emission		ontrol Systems Phase		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

This Executive Order hereby supersedes Executive Order A-010-2480 dated June 21, 2023.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 9th day of October 2023.

Rolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HO /mi)	PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*		*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10		0.034	0.050	0.3	1.7	*	*	0.1	4	0.001	0.003
50°F @4K		SOLINE- ER3 E10	0.022	0.100	0.3	1.7	*	*	0.5	16		
					-		NN	IOG+NC	0x (g/mi)	CO (g/mi)		
				FUEL TYP	E		CE	CERT		CER	T	STD
HWFET @ 50K		*						,	*			
HWFET @ UL		L GASOLINE-TIER3 E10						31	0.050			
20°F @ 50K		COLD (	CO E10 RE	EGULAR GA	ASOLINE	(TIER3)				0.8	3	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			0										0			
		-				US06			SC03				COM	POSITE		
	FUEL TYPE		E		)G+NOx	G+NOx CO		PM		NMOG+NOx		NMOG+NOx		со	PM	
				(9	g/mi)	(g/mi)	(mg	g/mi)	(g	/mi)	(g/mi)	(	g/mi)	(g/mi)	(mg/mi)	
@ 4K	*		CERT	*		* *				*	*					
		STD		*	*				* *							
		C		*		*		2		*	*	C	0.050	0.4	*	
@ UL	@ UL GASOLINE- TIER3 E10		STD	*		*		6		*	*		0.057	4.2	*	
			BIN									0.060				
		WH	OLE VE	EHICLE	E EVAPO	ORATIVE E	MISSIO	N STAN	DARD	S AND C	CERTIFIC	ATIO	N LEVELS	i		
						WHOLE \	/EHICLE	EVAPO	ORATI	VE TES	ſING					
	EVAPORATIVE FAMILY		FUEL TYPE		UEL TYPE		YPE 3DH		S (g/test) @ UL			2DHS (g/test) @ UL			RL	UL
					CERT	STD	FEL	CER	T	STD	FE	FEL			STD	
RFMXR0140NDG			GASOLINE- TIER3 E10		0.373	0.500	0.500	0.33	38	0.500	0.5	500 0.00		(	0.05	
RFMXR0140NDV		-	ASOLIN IER3 E		0.191	0.500	0.500	0.20	03	0.500	0.5	.500 0.00			0.05	



ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
		FUEL ONLY EVAP & CANISTER BLEED												
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE		3DHS R (g/test		-	RIG TEST st) @ UL	BLEED CANISTER TEST (g/test) @ 4K						
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD			
RFMXR0140NDG	GASOLINE- TIER3 E10	0.10	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.015	0.020			
RFMXR0140NDV	GASOLINE- TIER3 E10	0.02	0.20	GASOLINE- TIER3 E10		*	*	*	*	0.004	0.020			
E	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)													
EVAPORATIVE	Y CERT					STD								
RFMXR0140NDV RFMXR0140NDV			-001 *					0.02						
RFMXR0140NDG RFMXR0140ND			140NDG	-001 *					0.02					

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

# 2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	BRONCO RAPTOR 4WD	LDT4	3.0	SA10	RFMXR0140NDG	1	P
FORD	RANGER RAPTOR 4WD	LDT4	3.0	SA10	RFMXR0140NDV	1	P