

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	OUP IN	IFOR	MATION					
MOD YEA		TEST GROUF			VEHICLE CLASS(ES)					ATEGORY		FUEL TYPE		
202	4 I	RFMXT02.0S7	з			LDT2		-	SINGLE FUEL HICLE		GASOLINE			
	USEFU	UL LIFE (miles)		VEF	IICLE EMISS	ION C	ATE	GORY	INTERIM / IN	TEF	RMEDIATE IN-USE STD		
EX	H/ORVI	R EV/	NΡ			FTP		SF	ТР	FTP		SFTP		
1	50000	150	00		LEV3	ULEV50	3 CC	MPOSITE	*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L		OBD S	TATUS	E	ENGINE DISPLACEMENT (L)		
1	1 TWC(2), HO2S, WR-HO2S, CAC, TC, DFI, EGR, EGRC								FULL	*				
*	* *								ARTIAL	ALL MODELS	2.0			
*	* *								TIAL WITH FINES	*				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	AP / OR	RVR FAMILY	E	EVAP	ORATIVE	E STD CATE	GORY	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	RFMXR	0125GDF		LEV	V 3 OPTI	ON2 WITH	FEL		LDT2			HCT		
					I	EMISSION CI	REDIT	INFO	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
N N									N N					
					NMOG	AND FLEET		RAGE	INFORMA	TION				
NMOG CH4 FTP RAF RAF NMOG/NMHC RATIO						NMOG+NOX FLEET ST PC+LDT (0-3750 LVW (g/mi)								
* * 1.10 * 0.037 0.038 *								*						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 12th day of September 2023.

Robin U. Lang

Robin U. Lang, Chief University Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG (g/	6+NOx mi)		O mi)	N((g/i	Ox mi)		HO /mi)		PM g/mi)		
			CERT	CERT STD CERT STD		CERT	STD	CERT	STD	CERT	STD			
FTP@50K	*		*	*	*	*	*	*	*	*	*	*		
FTP@UL	GASOLINE- TIER3 E10		0.034	0.050	0.4	1.7	*	*	0	4	0.001	0.003		
50°F @4K		*	*	*	*	*	*	*	*	*				
							NN	NMOG+NOx (g/mi)				CO (g/mi)		
FUEL TYPE					E		CE	CERT S		CER	т	STD		
HWFET @ 50K				*			*	*						
HWFET @ UL			GASOI	LINE-TIE	R3 E10		0.0	16	0.050					
20°F @ 50K		COLD (CO E10 RE	EGULAR G	ASOLINE	(TIER3)				0.4	L	12.5		

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SF	ΓΡΕ	XHAU	JST EM	ISSION	I STANDA	ARDS	AND	CERTIFIC	ATION LE	VELS	S					
						l	JS06				SC03			CC	OMP	OSITE			
	FUEL TY	. TYPE		NMOG+NOx (g/mi)		-	CO (g/mi)		PM (mg/mi)		DG+NOx g/mi)	CO (g/mi)	-	OG+NOx (g/mi)		CO (g/mi)	PM (mg/mi)		
@ 4K	@4K *		CERT	*			*				*	*							
-			STD	*			*				*	*							
	@ UL GASOLINE- TIER3 E10		CERT		*		* 1			*		*	0.040		40 0.7		*		
@ UL			STD	*			*		5	*		*	0.057		.057 4.2		*		
			BIN										0	0.070					
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																			
							HOLE VEHICLE EVAPORATIVE TESTING												
	EVAPORATIVE FAMILY		/E FUEL TYPE		UEL TYPE		3DHS (g/		(g/test) @ UL		2DHS (g/te		HS (g/test)	(g/test) @ UL		RL (g/mi) @ UL			UL
					CERT		STD	FEL CE		RL	STD	FEL		CERT			STD		
RFMXR0125GDF		-	ASOLINE IER3 E1		10 101 0		. 400	0.400	*		0.400	0.40	0	0.00			0.05		
0	ORVR / FU	EL O	NLY / C	ANIS	STER	BLEED) EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CER	TIFICA	TIOI	N LEVE	LS		
FUEL ONLY EVAP & CANISTER BLEED																			
EVAPORATIVE FAMILY		C	ORVR (g/gallo			UL			HS RIG TEST g/test) @ UL		2DHS RIG (g/test) @					CANISTER /test) @ 4K			
		FUE	EL TYPE	C	ERT	STD			CE	RT	STD	CERT	S	STD		ERT	STD		
RFMXR0125GDF			SOLINE- ER3 E10	0	.06	0.20		OLINE- R3 E10	*	•	*	*		*	0.	004	0.020		



EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD									
RFMXR0125GDF	RFMXR0125GDF-001	*	0.02									

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	MAVERICK TREMOR AWD	LDT2	2.0	SA8	RFMXR0125GDF	1	Р