

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	FORM	IATION						
MODE YEAF		EST GROUP	VEHICLE CLASS(ES)					FUEL CATEGORY			FUEL TYPE			
2024	RF	MXD03.57BG			MDV5				EL VEHICLE FFV)		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMI						MISSION CATEGORY INTERIM / IN					ERMEDIATE IN-USE STD			
EXH/ORVR EVAP					FTP			SFTP FTP			SFTP			
15	0000	150000		LEV3	SULEV200 (HOT1 (LA92)		HOT14 A92),	73 SULEV T1435 UC 2), SC03, EST CYCLE)			*			
SPE	CIAL FE	EATURES & EX	HAUS		ON CONTRO	L		OBD STATUS			ENGINE DISPLACEMENT			
1	2 T W	C, DFI, SFI,	2WR-	-HO2S, 2	HO2S, EGR			FULL *						
*			*				P	ARTIAL ALL MODELS			3.5			
*			*					TIAL WITH	*	*				
I		E	/APOF	RATIVE &	REFUELING	(EVA	P/OR	R) FAMIL	(INFORMATION	1				
EVA	P / ORV	R FAMILY	EVA	PORATIVI	E STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
F	RFMXR01	.85NDJ	LE	V 3 OPTI	ON2 WITH FEL			ME	vv5		HCT			
F	RFMXR02	15GDJ	LE	V 3 OPTI	ION2 WITH	FEL		ME	vv5		HCT			
					EMISSION C	REDIT	INFO	RMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY						ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS			
	N N								N		N			
				NMOG	AND FLEE		RAGE	INFORMA	TION					
NMOG RAF	RAHO HDI (3751 I VW-8)				500 GV	0 GVW) MDV (8501-10000 GVW		D NMOG+NOX FLEET STD R) MDV (10,001-14,000 GVWR) (g/mi)						
*	*	1.10		*		*			*		*			
		•												

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 20 th day of November 2023.

Robin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				_		G+NOx /mi)		CO (g/mi)			IOx /mi)		HCH mg/i	-	PM (g/mi)		
					CERT	STE	CER	-	D	CERT	STD	CER	T STD		STD CE		STD
FTP@5	0K		*		*	*	*	*		*	*	*		*	*	* *	
FTP@l	E85-EPA FTP@UL (GASOLIN TIER3 E1		IE-	0.117 (0.131)	0.20				* (*)	* (*)	0 (1)		6 (6)	0.0 (0.0		0.010 (0.010)	
50°F @	60°F @4K *			*	*	*	*		*	*	*		*				
										NMOG+NOx (g/mi)				CO (g/mi)		
					FUEL TYPE						CERT S		STD CER		T S		STD
HWFE	Т @	50K				*				*		*	*				
HWFET @ UL				(GASC	E85-1 DLINE-T	EPA IER3 E10						0.200					
20°F	@ 50	0K				*								*			*
				;	SFTP EX	HAUST	EMISSIO		ARDS	AND C	ERTIFIC	ATION LE	EVEL	S			
					US06					SC03				CO	MPO	OSITE	
	FUEL TYPE		E NMOG+NOx		со	-	M	NMOG+NOx		со		NMOG+NOx		co	PM		
					(g	ı/mi)	(g/mi)	(mg	J/mi)	(g/	/mi)	(g/mi)	(g/mi)		(g	/mi)	(mg/mi)
@ 4K		*	* CEF		Г	*	*				*	*					
				STD		*	*				*	*					
.		E85-EPA		CER	-	*	*		*		*	*	0.089		_	3	0
@ UL	E			STD BIN		*	*		*		*	*	0.350		4	1.0	7
				CER	r	*	*	-	*		*	*		^ 0.096	2	2.2	4
@ UL	-	ASOLINE- IER3 E10		STD	-	*	*		*		*	*	0.350				7
				BIN										*			
			WH	OLE \	/EHICLE	EVAPC		EMISSION			S AND C	ERTIFIC		N LEVEL	S		
							WHOLE										
EVAPORATIVE FAMILY			FUEL TYPE			3DHS (g/test) @ UL				2DHS	6 (g/test)			RL (g/mi) @		ni) @	UL
						CERT	STD	FEL	CE	RT STD		FEL	EL CER		RT		STD
RFMXR0185ND		5NDJ		ASOL: IER3		0.202	0.600	0.600	*	r	0.600	0.60	00	0.02		0.02 0.0	
RFMXF	RFMXR0215GD			ASOL: IER3		0.202	0.600	0.600	*	r	0.600	0.60	.600 0.0		0.00 0.0		0.05



FORD MOTOR COMPANY

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
	FUEL ONLY EVAP & CANISTER BLEED												
ORVR (g/	FUEL -	TYPE	3DHS RIG TEST (g/test) @ UL						ANISTER est) @ 4K				
FUEL TYPE	YPE CERT STD				CERT	STD	CER	т	STD	CERT	STD		
GASOLINE- TIER3 E10 PREM	0.01	0.20			*	*	*		*	0.004	0.030		
GASOLINE- TIER3 E10 PREM	0.01	0.20			*	*	*		*	0.003	0.030		
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)													
EVAPORATIVE FAMILY LEAK FAMIL					Y CERT					STD			
RFMXR0185NDJ RFMXR0185NDJ				-001 *					0.02				
RFMXR0215GDJ RFMXR0215GDJ-			-001 *					0.02					
	ORVR (g/ FUEL TYPE GASOLINE- TIER3 E10 PREM GASOLINE- TIER3 E10 PREM EFFECTIVE FAMILY	ORVR (g/gallon) (FUEL TYPE CERT GASOLINE- TIER3 E10 0.01 PREM GASOLINE- TIER3 E10 0.01 PREM EFFECTIVE LEAK D FAMILY LEA	ORVR (g/gallon) @ UL FUEL TYPE CERT STD GASOLINE- TIER3 E10 0.01 0.20 PREM GASOLINE- TIER3 E10 0.01 0.20 PREM EFFECTIVE LEAK DIAMET FAMILY LEAK FAMIL NDJ RFMXR0185NDJ	ORVR (g/gallon) @ UL FUEL TYPE GASOLINE- TIER3 E10 0.01 PREM 0.01 GASOLINE- TIER3 E10 PREM GASOLINE- TIER3 E10 PREM GASOLINE- TIER3 E10 PREM O.01 0.20 GASOL FAMILY NDJ RFMXR0185NDJ-001	ORVR (g/gallon) @ UL FUEL TYPE FUEL TYPE CERT STD GASOLINE- TIER3 E10 0.01 0.20 GASOLINE- TIER3 E10 GASOLINE- TIER3 E10 0.01 0.20 GASOLINE- TIER3 E10 GASOLINE- TIER3 E10 0.01 0.20 GASOLINE- TIER3 E10 FFECTIVE LEAK DIAMETER STANDARI FAMILY IDJ RFMXR0185NDJ-001	FUEL TYPE FUEL TYPE FUEL TYPE FUEL TYPE STD FUEL TYPE CERT STD GASOLINE- TIER3 E10 0.01 0.20 GASOLINE- TIER3 E10 * GASOLINE- TIER3 E10 0.01 0.20 GASOLINE- TIER3 E10 * PREM 0.01 0.20 GASOLINE- TIER3 E10 * FFECTIVE LEAK DIAMETER STANDARD AND CE FAMILY CE NDJ RFMXR0185NDJ-001 *	FUEL ONLY EVAI ORVR (g/gallon) @ UL FUEL TYPE FUEL TYPE FUEL TYPE GASOLINE- TIER3 E10 O.01 O.20 GASOLINE- TIER3 E10 PREM O.01 O.20 GASOLINE- TIER3 E10 GASOLINE- TIER3 E10 O.01 O.20 GASOLINE- TIER3 E10 PREM O.01 O.20 GASOLINE- TIER3 E10 PREM O.01 O.20 GASOLINE- TIER3 E10 FFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATIONARD FAMILY LEAK FAMILY NDJ RFMXR0185NDJ-001	FUEL ONLY EVAP & CAI FUEL TYPE FUEL TYPE FUEL TYPE STD FUEL TYPE STD CERT 2DH3 GASOLINE- TIER3 E10 0.01 O.20 GASOLINE- TIER3 E10 * * GASOLINE- TIER3 E10 0.01 O.20 GASOLINE- TIER3 E10 * * FFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION L FAMILY CERT NDJ RFMXR0185NDJ-001	FUEL ONLY EVAP & CANISTE ORVR (g/gallon) @ UL FUEL TYPE SUBL TYPE SUBL TYPE SUBL SUBL TYPE SUBL SUBL SUBL SUBL SUBL SUBL SUBL SUBL	FUEL ONLY EVAP & CANISTER BLEE ORVR (g/gallon) @ UL FUEL TYPE FUEL TYPE 3DHS RIG TEST (g/test) @ UL 2DHS RIG TEST (g/test) @ UL FUEL TYPE CERT STD CERT STD QUL GASOLINE- TIER3 E10 0.01 0.20 GASOLINE- TIER3 E10 * * * * * GASOLINE- TIER3 E10 0.01 0.20 GASOLINE- TIER3 E10 *	FUEL ONLY EVAP & CANISTER BLEED ORVR (g/gallon) @ UL FUEL TYPE FUEL TYPE STD BLEED C FUEL TYPE CERT STD O.004 STD CERT STD CERT STD CERT STD O.003 STD STD STD STD <th colspa="</td"></th>		

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment EČS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission: AM: automated manual transmission: AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	TRANSIT T350 VAN 2WD FFV	MDV5	3.5	SA10	RFMXR0215GDJ	1	P
FORD	TRANSIT T350 VAN 2WD FFV	MDV5	3.5	SA10	RFMXR0505NDJ	1	P
FORD	TRANSIT T350 WAGON 2WD FFV	MDV5	3.5	SA10	RFMXR0215GDJ	1	P
FORD	TRANSIT T350 WAGON 2WD FFV	MDV5	3.5	SA10	RFMXR0505NDJ	1	P