

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION					
MODE YEAF		EST GROUP		VEHIC	EHICLE CLASS(ES)				ATEGORY		FUEL TYPE		
2024	l R	KMXT02.5JP3			LDT2		-	SINGLE FUEL HICLE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION								EGORY INTERIM / INTERMEDIATE IN-USE STD					
EXH	I/ORVR	EVAP		FTP		SF	ТР	FTP		SFTP			
15	50000	150000		LEV3	SULEV30	LEV 3 COMPOSITE			*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	EN	ENGINE DISPLACEMENT (L)		
1	DFI	, SFI, WR-HO	2S, н	02S, TWO	C, TC, CAC			FULL	ALL MODELS				
*			*				P	PARTIAL *			2.5		
*			*				PAR	RTIAL WITH * FINES					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
]	rkmxr0	144JPG		LEV 3	OPTION2			LD	рт2 НСТ				
				E	EMISSION CI	REDI	T INFO	ORMATION					
	REDIT F	OX FLEET AVE. OR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG CREDIT FOR DOP			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N N				
				NMOG	AND FLEET	AVE	RAG		TION				
NMOG RAF	CH4 FTP RAF NMOG/NMHC RATIO HCHO/NMHC RATIO (g/mi)				0-375					D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.037			0.038	*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 4th day of December 2023.

Robin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

						CO (g/mi)		NOx (g/mi)		HO /mi)			
	CERT STD CERT S		STD	CERT	CERT STD		STD	CER	T STD				
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- TIER3 E10		0.013	0.030	0.3	1.0	*	*	*	4	0.00	0.003	
50°F @4K	GASOLINE- TIER3 E10		0.008	0.060	0.3	1.0	*	* *		8			
				FUEL TYP	E		NN	IOG+N	Ox (g/mi)		CO (g/mi)		
				FUELITP	E		CE	RT	STD	CER	Т	STD	
HWFET @ 50P				*			*	*		*			
HWFET @ UL			GASOI	LINE-TIEF	R3 E10		0.0	800	0.030				
20°F @ 50K		COLD	CO E10 R	EGULAR G	ASOLINE	(TIER3)				0.5	5	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			361		nAUS		33101	STANDA	ARDS A		CERTIFIC		VELS				
						ι	JS06				SC03		C	OMPOSI	ΓE		
	FUEL TY	PE		NMOC (g/	G+NO /mi)	x	CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CC (g/m		PM (mg/mi)	
@ 4K	*		CERT	*			*				*	*					
Ŭ			STD				*			*		*					
			CERT		*		*		•	*		*	0.013	0.2	2	*	
@ UL	GASOLIN TIER3 E		STD	*			* 6		5	*		*	0.057	4.2	2	*	
			BIN										0.030				
		WHC	DLE VEH	ICLE	EVA	PORA	TIVE E	MISSION	STAN	DAR	DS AND C	ERTIFICA	TION LEVE	LS			
WHOLE VEHICLE EVAPORATIVE TESTING																	
	EVAPORATIVE FAMILY		FUEL TYPE		'E 3DHS ((g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi) @		UL		
				CERT		S	STD FEL		CERT		STD	FEL	CE	RT	STD		
RKMXR0144JPG			SOLINE EV3 E1(0).247	0.	400	*	0.23	35	0.400	*	0.	00	0.05		
(ORVR / FUI	EL OI	NLY / CA	ANIST	ER B	LEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFICA	TION LE	VEL	.S	
									FU	EL C	NLY EVA	P & CANIS	TER BLEE	D			
	ORATIVE AMILY			g/gallon) @ UL			-		-	HS RIG TEST g/test) @ UL		-	RIG TEST			CANISTER /test) @ 4K	
		FUE	EL TYPE	CEF	RT	STD			CEF	RT	STD	CERT	STD	CERT		STD	
RKMXI	R0144JPG		OLINE- R3 E10	0.0	01 (0.20		OLINE- 3 E10	*		*	*	*	0.010		0.020	

CALIFORNIA

KIA CORPORATION

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
RKMXR0144JPG	RKMXR0144JPG-MQ4	0.00	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	SORENTO AWD	LDT2	2.5	AMS8	RKMXR0144JPG	1	F
KIA	SORENTO FWD	LDT2	2.5	AMS8	RKMXR0144JPG	1	F