

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST G		IFORI	MATION					
MODE YEAF	- T	EST GROUP	VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE			
2024	R	JLXT03.0PTC		LDT4					IN HYBRID		GASOLINE		
	USEFU	L LIFE (miles)		VEF	IICLE EMIS	SSION C	ATEC	GORY	INTERIM / IN	ITER	FERMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP		FTP SF				ТР	FTP		SFTP		
150000 150000				LEV3	SULEV30			SULEV	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD	STATUS	E	ENGINE DISPLACEMENT (L)		
1	WR-HO2S, TWC, HO2S(2), DFI, TC, CAC							FULL	ALL MODELS				
*			*				P	ARTIAL	*		3.0		
*			*					TIAL WITH FINES	l *				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								ISSION STD LE CLASS	S	SPECIAL FEATURES		
I	RJLXR0	175M1C		LEV 3 OPTION2				LDT4			*		
				I	EMISSION	CREDIT	INFC	RMATION					
ALL	GR	CE FOR TEST OUP ZEV	OG+NOX 'E. CRED NDED W/		NMOG CREDIT FOR NON-PZEV ZERO- EVAP		NMOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS				
	ALL MODELS N								N		N		
			•	NMOG	AND FLE	ET AVE	RAGE		ATION				
NMOG RAF				O/NMHC ATIO	C NMOG+NOX FLEET PC+LDT (0-3750 LV (g/mi)					0	IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*		0.037			0.038		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this $\underline{28th}$ day of October 2023.

Rolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

GASOLINE-

LEV3 E10

0.021

0.20

*

RJLXR0175M1C

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	· STD	
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	GASOLINE- LEV3 E10		0.020	0.030	0.63	1.0	*	*	*	4	0.001	L 0.003	
50°F @4K		SOLINE- V3 E10	0.019	0.060	0.19	1.0	*	*	*	8			
					-		NN	IOG+NC	Dx (g/mi)	CO (g/mi)			
				FUEL TYP	E		CE	RT	STD	CER	т	STD	
HWFET @ 50K				*			*	·	*				
HWFET @ UL			GASO	LINE-LEV	3 E10		0.0	053	0.030				
20°F @ 50K			GASO	LINE-LEV	3 E10					0.4	4	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS															
						L					SC03		COMPOSITE			
	FUEL TY	PE			OG+N((g/mi)	Ох	CO (g/mi)	Pl (mg/			DG+NOx g/mi)	CO (g/mi)	NMOG+NO (g/mi)	x CO (g/m		
@ 4K	@ 4K *		CERT		*		*				*	*				
•			STD		*		*				*	*				
			CERT		0.009		0.46	.46 0.8		0	0.0047 0.		*	*	*	
@ UL	GASOLINI LEV3 E1	I SID		0.050			9.6 6		i	0	0.020 3.2		*	*	*	
			BIN										*			
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																
						WH	IOLE V	/EHICLE	EVAP	ORA	TIVE TEST	ING				
	ORATIVE	FUEL TYPE		ΡE	30	OHS (g	ı/test) @ UL			2DHS (g/test) @ UL			F	RL (g/mi) @ UL		
				CERT		T S	TD FEL C		CEF	RT	STD	FEL	CE	RT	STD	
RJLXR0175M1C		-	ASOLIN LEV3 E1		0.20	0.207 0.5		*	*	* 0.500		*	0.0	001 0.05		
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																
F								FL	JEL C	NLY EVA	P & CANIS	STER BLEE	D			
	EVAPORATIVE FAMILY		ORVR (g	J/gall	lon) @	UL	FUE	L TYPE	-	-	IG TEST) @ UL		RIG TEST t) @ UL	BLEED CANISTER TEST (g/test) @ 4K		
		FUEL		E CI	ERT	STD			CE	RT	STD	CERT	STD	CERT	STD	

*

*

*

*



JAGUAR LAND ROVER LIMITED

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
RJLXR0175M1C	RJLXR0175M1C-001	*	0.02						

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	LAND ROVER	RANGE ROVER P460 PHEV	LDT4	3.0	SA8	RJLXR0175M1C	1	F
2	LAND ROVER	RANGE ROVER P550 PHEV	LDT4	3.0	SA8	RJLXR0175M1C	1	F
3	LAND ROVER	RANGE ROVER SPORT P460 PHEV	LDT4	3.0	SA8	RJLXR0175M1C	1	F
4	LAND ROVER	RANGE ROVER SPORT P550 PHEV	LDT4	3.0	SA8	RJLXR0175M1C	1	F

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL NUMBER	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV	
	PHEVITPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE
1	TZEV	71.996	71.724	48.724	79.177	79.780	1.22
2	TZEV	71.996	71.724	48.724	79.177	79.780	1.22
3	TZEV	71.996	71.724	48.724	79.177	79.780	1.22
4	TZEV	71.996	71.724	48.724	79.177	79.780	1.22