

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRC	OUP IN	IFOR	MATION					
MOD YEA		ΤE	ST GROUP		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
202	4	RMA	XV03.0SPR		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USE	FUL	LIFE (miles)		VEH	VEHICLE EMISSION CATEGORY				Y INTERIM / INTERMEDIATE IN-USE STD				
EX	H/OR	VR	EVAP			FTP SI				FTP		SFTP		
1	50000	0	15000)	LEV3	ULEV70	LEV	3 CC	MPOSITE	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS									OBD S	TATUS	ENGINE DISPLACEMENT			
1	1 DFI, SFI, 2TC, 2CAC, 2WR-HO2S, 2TWC, 2HO2S, GPF								FULL	JLL ALL MODELS				
*				*				Р	ARTIAL	RTIAL *		3.0		
*				*					TIAL WITH	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EV	AP / 0	ORVF	RFAMILY	EVA	PORATIVE	E STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
	RMAXI	R011	2240	L	EV 3 OPTI	V 3 OPTION2 WITH FEL			PC			*		
					E	EMISSION CI	REDIT	INFC	ORMATION					
	REDIT	FOI	(FLEET AVE. R EXTENDED RANTY			EDIT FOR N ZERO-EVAP	ON-P2	ZEV NMOG CREDIT FOR DOR			ર	OPTIONAL EXH. STD FOR WORK TRUCKS		
			N			N			N			N		
					NMOG	AND FLEET	AVE	RAGE		TION				
NMO(RAF	WOG CH4 NMOG/NMHC HCHO/NMHC				PC+LDT (i+NOX FLEET STD .DT (0-3750 LVW) (g/mi)								
*	*	;	1.10		*	0	.037			0.038		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 12th day of October 2023.

Rolin U. Lang

Robin U. Lang, Chief Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

	NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
*	*	*	*	*	*	*	*	*	*	*
GASOLINE- TIER3 E10 PREM	0.0349	0.070	0.57	1.7	*	*	*	4	0.0006	0.003
GASOLINE- TIER3 E10 PREM	0.0551	0.140	0.68	1.7	*	*	*	16		
	GASOLINE- TIER3 E10 PREM GASOLINE- TIER3 E10	(g/r CERT * * GASOLINE- TIER3 E10 GASOLINE- TIER3 E10 0.0551	(g/mi)CERTSTD**GASOLINE- TIER3 E100.0349 0.03490.070 0.070GASOLINE- TIER3 E100.0551 0.05510.140	(g/mi) (g/mi) CERT STD CERT * * * * GASOLINE- TIER3 E10 0.0349 0.070 0.57 PREM 0.0551 0.140 0.68	(g/mi) (g/mi) CERT STD CERT STD * * * * * GASOLINE- TIER3 E10 0.0349 0.070 0.577 1.7 GASOLINE- TIER3 E10 0.0551 0.140 0.688 1.7	(g/mi) (g/mi) (g/mi) (g/mi) CERT STD CERT STD CERT * * * * * * GASOLINE- TIER3 E10 0.0349 0.070 0.57 1.7 * GASOLINE- TIER3 E10 0.0551 0.140 0.68 1.7 *	(g/mi) (g/mi) (g/mi) CERT STD CERT STD CERT STD * * * * * * * GASOLINE- TIER3 E10 0.0349 0.070 0.57 1.7 * * GASOLINE- TIER3 E10 0.0551 0.140 0.68 1.7 * *	(g/mi) (g/mi) (g/mi) (g/mi) (mg CERT STD CERT STD CERT STD CERT CERT STD STD CERT STD CERT STD STD CERT STD		$ \begin{array}{c c c c c c c c c c c c c c c c c c c $

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUEL ITFE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.0133	0.070			
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			1.09	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS														
					US06			SC03			COM	IPOSIT	E		
	FUEL TYPE			NMOG+NOx (g/mi)	CO (g/mi)	-	M NI (/mi)	MOG+NOx (g/mi)	CO (g/mi)	-	DG+NOx g/mi)	CO (g/m			
				(9/111)	(9/111)	(ing	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(9/111)	(9/111)	()	g/iiii)	(9/11	i) (iiig/iii)		
@ 4K	*		CERT	*	* *			*	*						
			STD	*	*			*	*						
			CERT	*	*	1	.1	*	*	0.0203		0.4	8 *		
@ UL	GASOLINI TIER3 E: PREM		STD	*	*		6	*	*	0	0.057		*		
		BIN								0	.070				
		wно	LE VE	HICLE EVAP	ORATIVE E	MISSION	STANDA	RDS AND O	ERTIFIC	ATION	N LEVELS	;			
					WHOLE \	/EHICLE	EVAPOR	ATIVE TES	ING						
	ORATIVE					PE 3DH	S (g/test) (@ UL	2DHS (g/test) @ UL				RL (g/mi) @ UL		@ UL
				CERT	STD	FEL	CERT	STD	FEL	L CERT			STD		
RMAXR0112240		TIH	SOLIN ER3 E PREM		0.300	0.300	0.1758	0.300	0.30	00 0.004		:	0.05		



MASERATI S.P.A.

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
			FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g	gallon) @	DUL	FUEL TYPE		3DHS R (g/test	IG TEST) @ UL		RIG TEST st) @ UL	BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD		
RMAXR0112240	GASOLINE- TIER3 E10 PREM	0.004	0.20	GASOLINE- TIER3 E10 PREM		*	*	*	*	0.0085	0.020		
I	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY LEAK F				Y		CERT			STD				
RMAXR0112	RMAXR0	AXR0112240-LF1			×	,		0.02					

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MASERATI	MC20	PC	3.0	SA8	RMAXR0112240	1	F
MASERATI	MC20 SPYDER	PC	3.0	SA8	RMAXR0112240	1	F