

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR		NFO	RMATION							
MODE YEAR		TEST GROUP			VEHICLE CLASS(ES)			FUE	FUEL CATEGORY			FUEL TYPE			
2024	RM	BXV02.0HY5		PC			PLUG-IN HYBRID LECTRIC VEHICLE			GASOLINE					
l	USEFUL	LIFE (miles)		VEF	IICLE EMIS	SION C	САТ	EGORY		INTERIM / IN	TE	ERMEDIATE IN-USE STD			
EXH	/ORVR	EVAP		FTP				SFTP	TP FTP			SFTP			
15	0000	150000		LEV3	ULEV70	LEV	3	COMPOSITE	Ξ	E *			*		
SPE	ATURES & EXI SYS		DL		OBD) ST	STATUS		ENGINE DISPLACEMEN (L)						
1	DFI,	SFI, TC, CAC	(2),	WR-HO2S	, HO2S, T	WC		FULL		*					
*			*			PARTIAL		*		2.0					
*	* PAR								ГН	ALL MODELS	1				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION															
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR									SSION STD E CLASS	SPECIAL FEATURES				
R	MBXR01	60LNP	LEV	V 3 OPTION2 WITH FEL					PC			*			
					EMISSION C	REDIT	r in	FORMATIO	N	1					
ALL	GR	E FOR TEST OUP EV				-PZ	CREDIT FOR PZEV ZERO- EVAP		NMOG CREDIT FOR DOR			R OPTIONAL EXH. STD FOR WORK TRUCKS			
		*		N				N	N			N			
				NMOG	AND FLEE	T AVE	RA		MAT	TION					
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO		O/NMHC ATIO	PC+LDT		0-3750 LVW) L			NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi			IOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	(0.037 0.038							*		
See the	- Attach	ment for Vehic		dels Eva	norative E	amily	Enc	ning Displa		ment Emission	5	ont	rol Systems Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have 12 deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$250 per vehicle for the third through twelfth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2024 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$47,363 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 29th day of March 2024.

Rolin U. Lang

Robin U. Lang, Chief *O* Emissions Certification and Compliance Division



FUEL TYPE

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

		NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HO /mi)				
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K		*	*	*	*	*	*	*	*	*	*	*	
FTP@UL	TIE	OLINE- R3 E10 PREM	0.055	0.070	0.9	1.7	*	*	*	4	0.001	0.003	
50°F @4K		*	*	*	*	*	*	*	*	*			
							NN	IOG+N	Ox (g/mi)	CO (g/mi)			
				FUEL TYP	E		CE	RT	STD	CER	CERT S		
HWFET @) 50K			*			*	*					
HWFET @ UL			GASOLIN	E-TIER3	E10 PREM	1	0.0	0.070					
20°F @	50K	COLD	LD CO E10 PREMIUM GASOLINE (TIER3)							1.2	2	10.0	
			SFTP EXH	IAUST EM	ISSION S	TANDARD	S AND CE	RTIFIC	ATION LEVE	LS			

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			55	IPE	XHAU		12210N	STAND	ARDS	AND	CERTIFIC	ATION LE	VEL	3				
						ι	JS06			SC03				COMPOSITE				
	FUEL TY	PE			OG+N (g/mi)		CO (g/mi)	Pl (mg			DG+NOx g/mi)	CO (g/mi)		OG+NO g/mi)	x	CO (g/mi)	PM (mg/mi)	
@4K *			CERT		*		*				*	*						
-		Γ	STD	*			*				*	*						
			CERT		*		*	* 3		*		*	0.040			1.1	*	
@ UL	@ UL GASOLINE				*		*	* 6		*		*	0.057			4.2	*	
			BIN										0	0.060				
WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS																		
						W	IOLE V	'EHICLE	EVAP	ORA	TIVE TEST	ING						
	ORATIVE AMILY	FUEL TYPE		ΡE	3	DHS (g	/test) @ UL			2Dł	HS (g/test)	@ UL		F	RL (g	g/mi) @	UL	
					CER	T S	STD FEL		CE	ERT STD		FEL		CE	RT		STD	
RMBXR0160LNP		-	ASOLINI IER3 E: PREM				300	0.300	0.1	84	0.300	0.300		0.00		0.05		
(ORVR / FU	EL O	ONLY / C	ANI	STER	BLEED	EVAP	ORATIVE	EMIS	SION	I STANDA	RDS AND	CER	RTIFICA	TIO	N LEVE	LS	
									FL	JEL C	ONLY EVA	P & CANIS	TEF	R BLEE	D			
	ORATIVE AMILY	(ORVR (g	/gal	lon) @) UL				HS RIG TEST g/test) @ UL		2DHS F (g/tes					D CANISTER (g/test) @ 4K	
		FUI	EL TYPE	C	ERT	STD			CE	RT	STD	CERT		STD	C	ERT	STD	
RMBXR0160LNP		TIH	SOLINE- ER3 E1(PREM		.01	0.20		*	ł.	*	*	*	*		*		*	

CALIFORNIA

MERCEDES-BENZ AG

Executive Order: A-003-0867 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
RMBXR0160LNP	RMBXR0160LNP-LNP	*	0.02							

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	MERCEDES-BENZ	AMG C 63 S E PERFORMANCE	PC	2.0	А9	RMBXR0160LNP	1	\$

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL PHEV TYPE		UDDS AER	UDDS EAER	US06 AER	HIGHW	ZEV		
NUMBER		(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE	
1	*	0.909	6.99	*	3.552	7.566	0.00	