

Executive Order: A-037-0050-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION												
MOD YEA		EST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE	
202	4 RI	TXV03.5JHB		PC			1	DEDICATED SINGLE FUEL VEHICLE			GASOLINE	
USEFUL LIFE (miles) VEHICLE EMISSION C						ATEC	ATEGORY INTERIM / INTERMEDIATE IN-USE S					
EX	H/ORVR	EVAP			FTP		SF	TP	FTP		SFTP	
1	50000	150000)	LEV3	ULEV125	LEV	3 UL	EV STAND ONE	*		*	
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	TATUS	EN	NGINE DISPLACEMENT (L)	
1	1 SFI, SC, 2HO2S(2), 2WU-TWC, TWC, CAC							FULL	ALL MODELS			
*	* *						P	PARTIAL *			3.5	
*	* *							RTIAL WITH *				
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION											
EV	AP / ORV	R FAMILY	EVA	PORATIVE	STD CATE	ATEGORY EVAP EMISSION STD VEHICLE CLASS			SI	PECIAL FEATURES		
	RLTXR01	130ЈНВ	LE	V 3 OPTI	ION2 WITH FEL			PC			*	
				I	EMISSION CI	REDIT	INFC	RMATION				
	REDIT FO	OX FLEET AVE. OR EXTENDED RRANTY	ı		EDIT FOR N ZERO-EVAP	ON-P	ZEV	NMOG C	REDIT FOR DOI		OPTIONAL EXH. STD FOR WORK TRUCKS	
		N			N				N		N	
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION			
NMO(CH4 RAF	FTP NMOG/NMHO RATIO		IO/NMHC RATIO	PC+1111 (0-3/50		50 LVW) LD1		NMOG+NOX FLEET STI LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10		*	0	.037			0.038		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-037-0050-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-037-0050 dated February 29, 2024.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this 30th day of May 2024.

Robin U. Lang, Chief

Emissions Certification and Compliance Division

Robin U. Lang

Executive Order: A-037-0050-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUS	I EMISS	ION S	IANDARDS	AND CE	RIFICA	ATION LEVE	LS (F	IP, HWFEI,	, 50°F, 20°F)	
•	0.11			0114					0114110	

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- LEV3 E10	0.0540	0.125	0.65	2.1	*	*	*	4	0.0003	0.003
50°F @4K	GASOLINE- LEV3 E10	0.1306	0.250	1.00	2.1	*	*	*	16		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-LEV3 E10	0.0302	0.125			
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			1.28	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COM	IPOSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	0.0401	1.38	4.4	0.0535	0.42	*	*	*
@ UL	GASOLINE- LEV3 E10	STD	0.120	9.6	6	0.070	3.2	*	*	*
		BIN						*		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

Ī				WHOLE \						
EVAPORATIVE FUEL		FUEL TYPE	3DHS (g/test) @ UL			2DI	HS (g/test) (RL (g/mi) @ UL		
			CERT	STD	FEL	CERT	STD	FEL	CERT	STD
	RLTXR0130JHB	GASOLINE- LEV3 E10 PREM	0.3570	0.300	0.450	0.2690	0.300	0.450	0.000	0.05

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				FUEL ONLY EVAP & CANISTER BLEED							
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL		FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD	
RLTXR0130JHB	GASOLINE- TIER3 E10	0.164	0.20	GASOLINE- LEV3 E10 PREM	*	*	*	*	0.0113	0.020	



Executive Order: A-037-0050-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTI\	EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY LEAK FAMILY CERT STD										
RLTXR0130JHB										

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; cGPF (coated gasoline particulate filter); HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIŔ/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2024 MODEL YEAR: VEHICLE MODELS INFORMATION **EVAPORATIVE EXH ENGINE (L) TRANS TYPE** MAKE MODEL **VEH CLASS** OBD **FAMILY ECS** RLTXR0130JHB LOTUS EMIRA V6 PC 3.5 M6,SA6 F 1